

SANYO

No.676D

2SB808/2SD1012

PNP/NPN Epitaxial Planar Silicon Transistors

Low-Voltage Large-Current
Amp Applications

():2SB808

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$



			unit
Collector to Base Voltage	V_{CB0}	(-) 20	V
Collector to Emitter Voltage	V_{CEO}	(-) 15	V
Emitter to Base Voltage	V_{EBO}	(-) 5	V
Collector Current	I_C	(-) 0.7	A
Collector Current(Pulse)	I_{CP}	(-) 1.5	A
Collector Dissipation	P_C	250	mW
Junction Temperature	T_j	125	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +125	$^\circ\text{C}$

Electrical Characteristics at $T_a=25^\circ\text{C}$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB}=(-)15\text{V}, I_E=0$		(-) 1.0		μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=(-)4\text{V}, I_C=0$		(-) 1.0		μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=(-)2\text{V}, I_C=(-)50\text{mA}$	160*		960*	
	$h_{FE(2)}$	$V_{CE}=(-)2\text{V}, I_C=(-)500\text{mA}$	80			
		Pulse				
Gain-Bandwidth Product	f_T	$V_{CE}=(-)10\text{V}, I_C=(-)50\text{mA}$		250		MHz
Common Base Output Capacitance	C_{ob}	$V_{CB}=(-)10\text{V}, f=1\text{MHz}$		(13)		pF
Collector to Emitter Saturation Voltage	$V_{CE(sat)1}$	$I_C=(-)5\text{mA}, I_B=(-)0.5\text{mA}$	(-) 1.5	(-) 3.5		mV
	$V_{CE(sat)2}$	$I_C=(-)100\text{mA}, I_B=(-)10\text{mA}$	(-) 60	(-) 120		mV
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=(-)100\text{mA}, I_B=(-)10\text{mA}$	(-) 0.8	(-) 1.2		V
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C=(-)10\mu\text{A}, I_E=0$	(-) 20			V
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=(-)1\text{mA}, R_{BE}=\infty$	(-) 15			V
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E=(-)10\mu\text{A}, I_C=0$	(-) 5			V

* The 2SB808/2SD1012 are classified by 50mA h_{FE} as follows :









2SB808	160	F	320	280	G	560	
2SD1012	160	F	320	280	G	560	480 H 960

Package Dimensions 2033
(unit: mm)B: Base
C: Collector
E: Emitter

SANYO: SPA

SANYO Electric Co., Ltd. Semiconductor Business Headquarters


TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN



Sample Application Circuit : Low-voltage 3V(P_O 120mW) ITL-OTL power amp.

. Circuit configuration

For obtaining an output of more than 100mW, the middle-point voltage at the output stage and the collector voltage of the driver transistor must be $V_{CC}/2$. Therefore, the output stage is of quasi complementary configuration composed of npn/npn transistors. The phase is reversed by the 2SA608 and the middle-point voltage at the output stage and the collector voltage of the driver transistor are made to be $V_{CC}/2$ so that the output can be maximized.








R_1 : Used control idle current
 For $R_1 = 820\Omega$, use rank F for [TR4,5(2SD1012)].
 For $R_1 = 680\Omega$, use rank G for [TR4,5(2SD1012)].

. Main Specifications

Characteristic	Conditions	f=400Hz	f=1kHz	unit
Current dissipation	Quiescent, total current dissipation	11.0 to 15.5	11.0 to 15.5	mA
Output power	THD=10%	120 to 125	127 to 130	mW
Voltage gain	$P_O=10\text{mW}$	43.3 to 45.5	43.5 to 45.7	dB
Total harmonic distortion	$P_O=50\text{mW}$	1.4 to 2.6	1.3 to 2.5	%
Input resistance	$P_O=10\text{mW}$	10.4 to 20.5	11.0 to 21.0	k Ω

Note : For above-mentioned h_{FE} rank.





■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.