

SANYO

No.1720A

2SA1415/2SC3645

PNP/NPN Epitaxial Planar Silicon Transistors

High-Voltage Switching,
Predriver Applications**Features**

- Adoption of FBET process
- High breakdown voltage ($V_{CEO} = 160V$)
- Excellent linearity of h_{FE} and small c_{ob}
- Fast switching speed
- Very small size marking it easy to provide high-density, small-sized hybrid ICs

(): 2SA1415

Absolute Maximum Ratings at $T_a = 25^\circ C$

			unit
Collector to Base Voltage	V_{CBO}	(-)180	V
Collector to Emitter Voltage	V_{CEO}	(-)160	V
Emitter to Base Voltage	V_{EBO}	(-)5	V
Collector Current	I_C	(-)140	mA
Collector Current(Pulse)	I_{CP}	(-)200	mA
Collector Dissipation	$P_C(1)$	500	mW
	$P_C(2)$ Mounted on ceramic board ($250mm^2 \times 0.8mm$)	1.3	W
Junction Temperature	T_j	150	$^\circ C$
Storage Temperature	T_{stg}	-55 to +150	$^\circ C$


Electrical Characteristics at $T_a = 25^\circ C$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)80V, I_E = 0$			(-)100	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)4V, I_C = 0$			(-)100	nA
DC Current Gain	h_{FE}	$V_{CE} = (-)5V, I_C = (-)10mA$	100※		400※	
Gain-Bandwidth Product	f_T	$V_{CE} = (-)10V, I_C = (-)10mA$		150		MHz
Output Capacitance	c_{ob}	$V_{CB} = (-)10V, f = 1MHz$		(4.0)		pF
				3.0		
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)50mA, I_B = (-)5mA$	(-0.14)	(-0.4)		V
			0.07	0.3		
Turn-on Time	t_{on}	See specified Test Circuit.		0.1		μs
Storage Time	t_{stg}	"		1.5		μs
Fall Time	t_f	"		0.1		μs

※ : The 2SA1415/2SC3645 are classified by 10mA h_{FE} as follows :

100	R	200	140	5	280	200	T	400
-----	---	-----	-----	---	-----	-----	---	-----

Marking 2SA1415 : AA h_{FE} rank : R,S,T
 2SC3645 : CA


Switching Time Test Circuit

$$I_C = 10I_{B1} = 10I_{B2} = 10mA$$

(For PNP, the polarity is reversed.)

Unit (Resistance : Ω , Capacitance : F)**Package Dimensions 2038**

(unit: mm)



















E: Emitter
 C: Collector
 B: Base

SANYO: PCP
 (Bottom View)

SANYO Electric Co., Ltd. Semiconductor Business Headquarters

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.