

9097250 TOSHIBA (DISCRETE/OPTO)

67C 08884

D T-33-01

TO-126 (S)



(5) TO-126 (S) PACKAGE SERIES

Application

Type No.		I _C (A)	V _{CEO} (V)	P _C T _C =25°C (W)	hFE		V _{CE(sat)} MAX.		f _T TYP.			Cob TYP. f=1MHz (pF)	V _{CB} (V)	TO-126 CROSS REFERENCE NO.
NPN	PNP				V _{CE} (V)	I _C (A)	V _{CE} (V)	I _C (A)	V _{CE} (V)	I _C (A)	(MHz)			
2SC3423	2SA1360	0.05	150	5	80~240	10	10	10m	1	200	10	1.8/2.5	10	
2SC3424	2SA1361		250	5	50 MIN.	20	25m	10m	1	80	10	—	—	
2SC3619		0.1	300	5	30~150	10	20m	10m	1	70	10	3	20	
2SC3620		0.15	300	5	40~170	10	50m	1	0.1	20	110	3.5	50	(1)
2SC3419	2SA1356	0.8	40	5	70~240	2	50m	0.5	0.5	100	2	10/20	10	(3)
2SC3425			400	10	20~100	5	0.1	0.1	0.5	10	—	—	—	(2)
2SC3421	2SA1358	1	120	10	80~240	5	0.1	0.5	1	120	5	15/30	10	(4)
2SC3621	2SA1408	1.5	150	10	60~320	5	0.2	0.5	1.5	20MIN	5	—	—	(5)
2SC3422	2SA1359	3	40	10	80~240	2	0.5	2	0.8	100	2	35	10	(6)
2SC3420		5	20	10	140~600	2	0.5	1	1	100	2	40	10	(7)
	2SA1357		20	10	100~320	2	0.5	1	1	170	2	62	10	(8)
2SD1508		1.5	30	10	4000MIN.	2	0.15	1	1.5	1	—	—	—	(9)
2SD1509	2SB1067	2	80	10	2000MIN.	2	1	1	1.5	10/50	2	20/30	10	(10)

Low V_{CE(sat)}Strobo Flash
Strobo Flash**DARLINGTON**