

2SB943

Silicon PNP Epitaxial Planar Type

Power Switching

Complementary Pair with 2SD1268


■ Features

- Low collector-emitter saturation voltage ($V_{CE(sat)}$)
- Good linearity of DC current gain (h_{FE})
- High collector current (I_C)
- "Full Pack" package for simplified mounting on a heat sink with one screw

■ Absolute Maximum Ratings ($T_c=25^\circ\text{C}$)

Item	Symbol	Value	Unit
Collector-base voltage	V_{CB0}	-130	V
Collector-emitter voltage	V_{CE0}	-80	V
Emitter-base voltage	V_{EB0}	-7	V
Peak collector current	I_{CP}	-6	A
Collector current	I_C	-3	A
Collector power dissipation	$T_c=25^\circ\text{C}$	30	W
	$T_a=25^\circ\text{C}$	2	
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 ~ +150	$^\circ\text{C}$

■ Package Dimensions












■ Electrical Characteristics ($T_c=25^\circ\text{C}$)

Item	Symbol	Condition	min.	typ.	max.	Unit
Collector cutoff current	I_{CB0}	$V_{CB} = -100\text{ V}, I_E = 0$			-10	μA
Emitter cutoff current	I_{EB0}	$V_{EB} = -5\text{ V}, I_C = 0$			-50	μA
Collector-emitter voltage	V_{CE0}	$I_C = -10\text{ mA}, I_B = 0$	-80			V
DC current gain	h_{FE1}	$V_{CE} = -2\text{ V}, I_C = -0.1\text{ A}$	45			
	h_{FE2}^*	$V_{CE} = -2\text{ V}, I_C = -0.5\text{ A}$	60		260	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -2\text{ A}, I_B = -0.1\text{ A}$			-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C = -2\text{ A}, I_B = -0.1\text{ A}$			-1.5	V
Transition frequency	f_T	$V_{CE} = -10\text{ V}, I_C = -0.5\text{ A}, f = 10\text{ MHz}$		30		MHz
Turn-on time	t_{on}	$I_C = -0.5\text{ A}$ $I_{B1} = -50\text{ mA}, I_{B2} = 50\text{ mA}$		0.3		μs
Storage time	t_{stg}			1.1		μs
Collector current fall time	t_f			0.3		μs

* h_{FE2} Classifications

Class	R	Q	P
h_{FE2}	60 ~ 120	90 ~ 180	130 ~ 260



Note) Refer to P.177 (on 2SB941/A) for $R_{th(jc)} - t$ characteristics.