



PPC PRODUCTS CORPORATION

SEMICONDUCTOR SPECIALIST

PNP DEVICE	CASE	BREAKDOWN VOLTAGES			h_{FE}				SAT. VOLTAGES (Max.)			
		V_{CB}	V_{CE}	V_{EB}	V_{CE} (V)	I_{C} (A)	Min.	Max.	I_{C} (A)	I_{B} (A)	V_{CE} (V)	V_{BE} (V)
2N5876	TO-3	80	80	6	4	4	20	100	4	0.5	1	2
2N5879	TO-3	60	60	6	4	6	20	100	6	0.7	1	2
2N5880	TO-3	80	80	6	4	6	20	100	6	0.7	1	2
2N5883	TO-3	60	60	5	4	25	20	100	25	1.5	1	2
2N5884	TO-3	80	80	5	4	25	20	100	25	1.5	1	2
2N5954	TO-66	90	80	5	4	2	20	100	2	0.2	1	2
2N5955	TO-66	70	60	5	4	2.5	20	100	2.5	0.25	1	2
2N5956	TO-66	50	40	5	4	3	20	100	3	0.3	1	2
2N5958	TO-61	100	100	8	10	10	30	120	10	0.5	0.5	1
2N5960	TO-61/I	100	100	8	10	10	30	120	10	0.5	0.5	1
2N5967	TO-63	100	100	8	10	10	30	120	10	1.5	1.8	2
2N5969	TO-63/I	100	100	8	10	10	30	120	10	1.5	1.8	2
2N6029	TO-3	100	100	7	2	8	25	100	8	1	1	2
2N6030	TO-3	120	120	7	2	8	20	80	8	1	1	2
2N6031	TO-3	140	140	7	2	8	15	60	8	1	1	2
2N6049	TO-66	90	55	7	4	0.5	25	100	0.5	0.05	0.5	1
2N6061	TO-63	100	100	8	10	20	20	120	20	2	1.8	2
2N6127	TO61/I	100	80	5	5	5	30	120	5	0.5	0.9	2
2N6182	TO-59	80	80	6	2	2	30	120	2	0.2	0.7	1
2N6183	TO-59	80	80	6	2	2	60	240	2	0.2	0.7	1
2N6184	TO-59	100	100	6	2	2	30	120	2	0.2	0.7	1
2N6185	TO-59	100	100	6	2	2	60	240	2	0.2	0.7	1
2N6186	TO-59/I	80	80	6	2	2	30	120	2	0.1	1.2	2
2N6187	TO-59/I	80	80	6	2	2	60	240	2	0.1	1.2	2
2N6188	TO-59/I	100	100	6	2	2	30	120	2	0.1	1.2	2
2N6189	TO-59/I	100	100	6	2	2	60	240	2	0.1	1.2	2
2N6190	TO-5	80	80	6	2	2	30	120	2	0.5	1.2	2
2N6191	TO-5	80	80	6	2	2	60	240	2	0.5	1.2	2
2N6192	TO-5	100	100	6	2	2	30	120	2	0.5	1.2	2
2N6193	TO-5	100	100	6	2	2	60	240	2	0.5	1.2	2
2N6211	TO-66	275	225	6	2	1	10	100	1	0.125	1.4	1
2N6212	TO-66	350	300	6	3	1	10	100	1	0.125	1.6	1

6856191 0001051 148