

ISDN MAGNETICS

U Interface Transformers

bel

TM00203

- Water-soluble flux and total-immersion cleaning compatible
- Qualified per Bellcore TR-TSY-000357-1
- Compatible with various Lucent transceiver ICs
- UL and CSA approved


ELECTRICAL SPECIFICATIONS at 25° C

Part Number	Turns Ratio ± 2%	Secondary Inductance* mH min	Leakage Inductance μH max	DCR Ω		Isolation Vrms min
				Pri	Sec	
2754H2	1.0 : 1.5	77.0	172	5.2 - 5.6	12.35 - 13.55	1000
2754J2	1.0 : 1.5	77.0	172	6.4 - 7.35	11.7 - 13.65	1000
2754K2	1.0 : 1.5	77.0	172	6.1 - 7.4	14.1 - 17.4	1500

* Measured at 1 kHz, 0.1 Vac


Part Number	Compatible Transceiver ICs	
	IC Mfr	IC Part Number
2754H2	Lucent	T7234 T7237 T7256 T7264
2754J2		
2754K2		

SCHEMATIC



MECHANICAL

2754H2
2754J2
2754K2



©2001 Bel Fuse Inc. Specifications subject to change without notice. 02.01

CORPORATE

Bel Fuse Inc.
198 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com