

DESIGNED TO MEET UL/CSA STANDARDS

5 x 20 mm Time Lag Fuse (Slo-Blo® Type Fuse)



- Designed to UL/CSA/ANCE 248 Standard.
- Available in Cartridge and Axial Lead Format.
- Available in ratings of 0.200 to 5 amperes.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
110%	4 hours, Minimum
135%	1 hour, Maximum
200%	5 seconds, Minimum

AGENCY APPROVALS: Listed by Underwriters Laboratories and Certified by CSA. Approved by MITI from 1 through 5 amperes.

PATENTED

ORDERING INFORMATION:

Cartridge Catalog Number	Axial Lead Catalog Number	Ampere Rating	Voltage Rating	Nominal Resistance Cold Ohms	Nominal Melting I ² t A ² Sec.
239.200	238.200	.200	250	8.40	0.170
239.250	238.250	.250	250	3.00	0.3508
239.300	238.300	.300	250	2.25	0.630
239.400	238.400	.400	250	1.46	1.53
239.500	238.500	.500	250	0.865	2.04
239.600	238.600	.600	250	0.688	2.48
239.700	238.700	.700	250	0.550	4.23
239.750	238.750	.750	250	0.453	5.57
239.800	238.800	.800	250	0.403	7.77
239.001	238.001	1	250	0.313	11.60
239.1.25	238.1.25	1.25	250	0.200	20.05
239.01.6	238.01.6	1.60	250	0.122	31.25
239.002	238.002	2	250	0.0975	51.95
239.02.5	238.02.5	2.50	250	0.053	81.85
239.003	238.003	3	250	0.0480	133.0
239.3.15	238.3.15	3.15	250	0.0425	131.5
239.004	238.004	4	125	0.0313	278.0
239.005	238.005	5	125	0.0208	311.0

