



1MBI300JP-120 (TENTATIVE)

1. Outline Drawing

Unit : mm

* Isolation Voltage : AC 2500 V 1 minute




This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

1) Revised page 2-4 and added page 4-11 Apr 5'93 A.Yamashita

DATE	NAME	APPROVED	Fuji Electric Co., Ltd.	
DRAWN	Dec - 11 - 93	A. Yamashita	DWG. NO.	MT5F5033
CHECKED	Dec - 15 - 93	T. Miyasaka		
REVISIONS				

2. Equivalent Circuit



3. Absolute Maximum Ratings (Tj=25°C)

Items		Symbols	Ratings	Units
Collector-emitter voltage		V_{CES}	1 2 0 0	V
Gate-emitter voltage		V_{GES}	$\pm 2 0$	V
Collector current	Continuous	I_c	3 0 0	A
	1 ms	I_c pulse	6 0 0	
		$-I_c$	3 0 0	
	1 ms	$-I_c$ pulse	6 0 0	
Max.power dissipation		PC	1 6 0 0	W
Operating temperature		Tj	+1 5 0	°C
Storage temperature		Tstg	- 4 0 ~ + 1 2 5	°C
Isolation voltage		Vis	AC 2 5 0 0 (1min)	V
Screw Torque		Mounting *1	3. 5	N · m
		Terminals *2	4. 5	
		Terminals *3	1. 7	

Note : *1 Recommendable Value : 2.5 ~ 3.5 N · m (M5) or (M6)

Note : *2 Recommendable Value : 3.5 ~ 4.5 N · m (M6)

Note : *3 Recommendable Value : 1.3 ~ 1.7 N · m (M4)

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

REVISIONS	DATE	NAME	APPROVED	Fuji Electric Co., Ltd.	DWG. NO.	MT5F5033	2/11	2	
	DRAWN	-	-						
	CHECKED	-	-						

4. Static electrical characteristics

(at $T_j=25^\circ\text{C}$ unless otherwise specified)

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Zero gate voltage collector current	I_{CES}			4.0	$T_j = 25^\circ\text{C}$ $V_{GE}=0\text{V}$	mA
					$T_j=125^\circ\text{C}$ $V_{CE}=1200\text{V}$	mA
Gate-emitter leakage current	I_{GES}			60	$V_{CE}=0\text{V}$ $V_{GE}=\pm 20\text{V}$	μA
Gate-emitter threshold voltage	$V_{GE(th)}$		5.0		$V_{CE}=20\text{V}$ $I_C=300\text{mA}$	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		2.2		$V_{GE}=15\text{V}$ $I_C=300\text{A}$	V

5. Dynamic ratings (at $T_j=25^\circ\text{C}$ unless otherwise specified)

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Input capacitance	C_{ies}		36000		$V_{GE}=0\text{V}$	pF
Output capacitance	C_{oes}		—		$V_{CE}=10\text{V}$	
Reverse transfer capacitance	C_{res}		—		$f=1\text{MHz}$	
Turn-on time	t_{on}		0.95		$V_{CC}=600\text{V}$ $I_C=300\text{A}$ $V_{GE}=\pm 15\text{V}$ $R_G=2.7\Omega$	μs
	t_r		0.30			
Turn-off time	t_{off}		1.15			
	t_f		0.20			

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

REVISIONS	DATE	NAME	APPROVED	Fuji Electric Co., Ltd.	DWG. NO.	MT5F5033	3/11	12	
	DRAWN	-	-						
	CHECKED	-	-						

6. Characteristics of reverse diode (at $T_j=25^{\circ}\text{C}$ unless otherwise specified)

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Diode forward on-voltage	V_F		2.5		$I_F = 300\text{A}$ $V_{GE} = 0\text{V}$	V
Reverse recovery time	t_{rr}			350	$I_F = 300\text{A}$ $-di/dt = 900\text{A}/\mu\text{s}$	ns

7. Thermal resistance characteristics

Items	Symbols	Characteristics			Conditions	Units
		min.	typ.	max.		
Thermal resistance	$R_{th(j-c)}$			0.078	IGBT(MBT)	$^{\circ}\text{C}/\text{W}$
	$R_{th(j-c)}$			0.150	Diode	
	* $R_{th(c-f)}$		0.0125		the base to cooling fin	

* This is the value which is defined mounting on the additional cooling fin with thermal compound.

This material and the information herein is the property of Fuji Electric Co., Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.

REVISIONS		DATE	NAME	APPROVED	Fuji Electric Co., Ltd.	DWG. NO. MT5 F 5033	4/11	Q
	DRAWN	-	-					
	CHECKED	-	-					