



Led Signalleuchten Einbaudurchmesser 8 mm
Led Indicators Body diameter 8 mm

Blinkend mit Innenreflektor
Flashing Led with interior reflector

Bestell-Nr.	Farbe	V _{OP} +10%	I _{OP max.}	V _F	I _{V typ.} (mcd)	I _{F max.}	Abb.	Abmessungen, siehe Zeichnungsnr.		A
Part No.	Colour	(V)	(mA)	(V)	*I _F = 20mA	(mA)	Illu.	Dimensions, see Drawing No.	19050-A	
1907*000	Rot Red	3,5-13	38-56	9	nicht meßbar not measurable	56	A			
1907*001	Grün Green	3,5-13	38-56	9		56	A			
1907*002	Gelb Yellow	3,5-13	38-56	9		56	A			
1907*003	S. rot S. red	3,5-13	38-56	9		56	A			
1907*050	Rot Red	3,5-13	38-56	9		56	C			
1907*051	Grün Green	3,5-13	38-56	9		56	C			
1907*052	Gelb Yellow	3,5-13	38-56	9		56	C			
1907*053	S. rot S. red	3,5-13	38-56	9		56	C			
1907*350	Rot Red	24	20-35				B	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19050-B	B
1907*351	Grün Green	24	20-35				B			
1907*352	Gelb Yellow	24	20-35				B			
1907*353	S. rot S. red	24	20-35				B			
										
								19070050 - 19070053, wird als verkürzte Ausführung mit Steckkontakten geliefert, siehe Zeichnung Nr. 19050-C 19070050 - 19070053, short version with tabs, see drawing no. 19050-C		C
Arbeitstemperatur (T _{OP}): -55°C - +70°C Lagertemperatur (T _{STG}): -55°C - +100°C * Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert. Glanzchrom = 0 Schwarzchrom = 1 Beispiel: 1907 <u>0</u> 000 rot mit Glanzchrom 1907 <u>1</u> 000 rot mit Schwarzchrom Blinkfrequenz: (2,5 - 1,5 Hz./Cyc.) abhängig von angelegter Spannung								Operating temperature (T _{OP}): -55°C - +70°C Storage temperature (T _{STG}): -55°C - +100°C * The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1. Bright chrome = 0 Black chrome = 1 Example: 1907 <u>0</u> 000 red with bright chrome 1907 <u>1</u> 000 red with black chrome Flashing frequency: (2,5 - 1,5 Hz./Cyc.) depending on supply voltage		
Led Signalleuchten mit anderen Spannungen auf Anfrage Technische Änderungen vorbehalten								Led Indicators with other voltages upon request Specification subject to change without notice		