



Led Signalleuchten Einbaudurchmesser 8 mm
Led Indicators Body diameter 8 mm

Außenreflektor
Exterior reflector

Bestell-Nr.	Farbe	V _{OP} +10% (V)	I _{OP max.} (mA)	V _F (V)	I _{V typ.} (mcd) *I _F = 20mA	I _{F max.} (mA)	Abb.	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19040-A	A
1904*000	Rot Red			1,6/2,0	*4,0	75	A			
1904*001	Grün Green			2,0/2,6	*25,0	45	A			
1904*002	Gelb Yellow			2,0/2,6	*25,0	45	A			
1904*003	Super rot Super red			2,0/2,6	*20,0	45	A			
1904*050	Rot Red			1,6/2,0	*4,0	75	C			
1904*051	Grün Green			2,0/2,6	*25,0	45	C			
1904*052	Gelb Yellow			2,0/2,6	*25,0	45	C			
1904*053	Super rot Super red			2,0/2,6	*20,0	45	C			
1904*150	Rot Red	6	30		4,5		B		19040-B	B
1904*151	Grün Green	6	30		40,0		B			
1904*152	Gelb Yellow	6	30		38,0		B			
1904*153	Super rot Super red	6	30		30,0		B			
1904*250	Rot Red	12	30		4,5		B			
1904*251	Grün Green	12	30		40,0		B			
1904*252	Gelb Yellow	12	30		38,0		B			
1904*253	Super rot Super red	12	30		30,0		B			
1904*350	Rot Red	24	22		4,0		B	19040050 - 19040053, wird als verkürzte Ausführung mit Steckkontakten geliefert, siehe Zeichnung Nr. 19040-C 19040050 - 19040053, short version with tabs, see drawing no. 19040-C		C
1904*351	Grün Green	24	22		27,0		B			
1904*352	Gelb Yellow	24	22		27,0		B			
1904*353	Super rot Super red	24	22		22,0		B			

Blaue Led Signalleuchten lieferbar.

Bei Bestellung bitte an die letzte Stelle der jeweiligen Bestellnummer die "7" einsetzen.

Blue Led Indicators can be supplied.

When ordering, please use on the relevant partnumber the "7" for the last digit.

Arbeitstemperatur (T_{OP}): -55°C - +70°C
Lagertemperatur (T_{STG}): -55°C - +100°C

* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0 Schwarzchrom = 1

Beispiel: 19040000 rot mit Glanzchrom
 19041000 rot mit Schwarzchrom

Operating temperature (T_{OP}): -55°C - +70°C
Storage temperature (T_{STG}): -55°C - +100°C

* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0 Black chrome = 1

Example: 19040000 red with bright chrome
 19041000 red with black chrome

Led Signalleuchten mit anderen Spannungen auf Anfrage

Technische Änderungen vorbehalten

Led Indicators with other voltages upon request

Specification subject to change without notice