


**Led Signalleuchten Einbaudurchmesser 6 mm**  
**Led Indicators Body diameter 6 mm**

**Zweifarbige, mit Innenreflektor**  
**Duo Led, with interior reflector**

| Bestell-Nr. | Farbe                | V <sub>OP</sub><br>+10% | I <sub>OP max.</sub> | V <sub>F</sub>     | I <sub>V typ.</sub> (mcd) | I <sub>F max.</sub> | Abb.  | Abmessungen, siehe Zeichnungsnr.                                                    | A |
|-------------|----------------------|-------------------------|----------------------|--------------------|---------------------------|---------------------|-------|-------------------------------------------------------------------------------------|---|
| Part No.    | Colour               | (V)                     | (mA)                 | (V)                | *I <sub>F</sub> = 20mA    | (mA)                | Illu. | Dimensions, see Drawing No.                                                         |   |
| 1903*004    | Super red/<br>Green  |                         |                      | 2,0/2,2<br>2,2/2,8 | *14/22                    | 30                  | A     |  |   |
| 1903*005    | Super red/<br>Yellow |                         |                      | 2,0/2,2<br>2,2/2,8 | *14/14                    | 30                  | A     |                                                                                     |   |
| 1903*006    | Green/<br>Yellow     |                         |                      | 2,0/2,2<br>2,2/2,8 | *22/14                    | 30                  | A     |                                                                                     |   |
| 1903*054    | Super red/<br>Green  |                         |                      | 2,0/2,2<br>2,2/2,8 | *14/22                    | 30                  | B     |                                                                                     |   |
| 1903*055    | Super red/<br>Yellow |                         |                      | 2,0/2,2<br>2,2/2,8 | *14/14                    | 30                  | B     |                                                                                     |   |
| 1903*056    | Green/<br>Yellow     |                         |                      | 2,0/2,2<br>2,2/2,8 | *22/14                    | 30                  | B     |                                                                                     |   |
| 1903*154    | Super red/<br>Green  | 6                       | 30                   |                    | 19/34                     |                     | B     |                                                                                     |   |
| 1903*155    | Super red/<br>Yellow | 6                       | 30                   |                    | 19/20                     |                     | B     |                                                                                     |   |
| 1903*156    | Green/<br>Yellow     | 6                       | 30                   |                    | 34/20                     |                     | B     |                                                                                     |   |
| 1903*254    | Super red/<br>Green  | 12                      | 30                   |                    | 19/34                     |                     | B     | Abmessungen, siehe Zeichnungsnr.<br>Dimensions, see Drawing No. 19030-B             | B |
| 1903*255    | Super red/<br>Yellow | 12                      | 30                   |                    | 19/20                     |                     | B     |                                                                                     |   |
| 1903*256    | Green/<br>Yellow     | 12                      | 30                   |                    | 34/20                     |                     | B     |                                                                                     |   |
| 1903*354    | Super red/<br>Green  | 24                      | 18                   |                    | 13/20                     |                     | B     |                                                                                     |   |
| 1903*355    | Super red/<br>Yellow | 24                      | 18                   |                    | 13/13                     |                     | B     |                                                                                     |   |
| 1903*356    | Green/<br>Yellow     | 24                      | 18                   |                    | 20/13                     |                     | B     |                                                                                     |   |
|             |                      |                         |                      |                    |                           |                     |       |                                                                                     |   |
|             |                      |                         |                      |                    |                           |                     |       |                                                                                     |   |
|             |                      |                         |                      |                    |                           |                     |       |                                                                                     |   |

Arbeits temperatur (T<sub>OP</sub>): -55°C - +70°C  
Lagertemperatur (T<sub>STG</sub>): -55°C - +100°C

\* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0      Schwarzchrom = 1

Beispiel:      19030004 super rot / grün mit Glanzchrom  
19031004 super rot / grün mit Schwarzchrom

Operating temperature (T<sub>OP</sub>): -55°C - +70°C  
Storage temperature (T<sub>STG</sub>): -55°C - +100°C

\* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0      Black chrome = 1

Example:      19030004 super red / green with bright chrome  
19031004 super red / green with black chrome

**Led Signalleuchten mit anderen Spannungen auf Anfrage**  
Technische Änderungen vorbehalten

**Led Indicators with other voltages upon request**  
Specification subject to change without notice