


Specification Sheet

#1900 MityLite

#1950 MityLite Minisystem



MATERIAL

Body, Lens & Spring Pad:

Polycarbonate Resin

Spring & Retainer:

Phosphor Bronze

'O' Ring:

014, EP 70 Shore

Lamp Module:

Vacuum Metallized, Xenon Fired

Catalyst:

DeOxo Type D

CANDLE POWER

4.000 CP

LUMENS

3.8

WEIGHT W/BATTERIES

0.05 Kg

BATTERIES

2 Alkaline 'AAA' Cells

AMPS

0.60

VOLTS

3.00

WATTS

1.80

LAMP LIFE

20 Hours

BATTERY BURN TIME

2 Hours @ 10° C

PACKAGING

#1900 T – Packed in Clear Plastic Tubes (48 units)

#1900 C – Blister Packed on Color Hang Card (48 Units)

#1900 M – Plastic Counter Top Display Tray with 12 Carded MityLites

#1950 – Minisystem Shrink Wrapped (48 units)

#1950 C – Blister Packed on Color Hang Card (48 units)

ACCESSORIES

#1901 – Replacement 'O' Ring

#1902 – Lite bender Adaptor

#1904 – Replacement Lamp Module

Red or Blue-Green Night Vision Lens

700 – Helmet Lite Holder



Lite Bender

COLORS

Black, Yellow, Orange, Blue & White

Minisystem only Black & Yellow

APPROVALS

FM

Factory Mutual – United States

CSA

Canadian Standards

CENELEC

European Standards

AUS

Australian Standards

IP67

European Certificate, Ingress Protection

ATEX

European Certificate, Category 3 (Zone II)

CE  II 3 G Ex N IIC T4