

## Philips Components

|               |                       |
|---------------|-----------------------|
| Document No.  | 853-0685              |
| ECN No.       | 99799                 |
| Date of Issue | June 14, 1990         |
| Status        | Product Specification |
| ECL Products  |                       |

# 10189 Inverter

Hex Inverter with Enable

## FEATURES

- Typical propagation delay: 2.0ns
- Typical supply current ( $-I_{EE}$ ): 30mA

## DESCRIPTION

The 10189 includes six inverters offering individual inputs and outputs and a common enable input, driving all outputs Low. Each input is connected to  $V_{EE}$  via a pull-down resistor resulting in high input impedance and eliminating the need for tying unused inputs Low.

Due to open emitter outputs, the 10189 features OR capability with high fan-out for driving 50 $\Omega$  lines.


## ORDERING INFORMATION

| DESCRIPTION        | ORDER CODE |
|--------------------|------------|
| 16-Pin Plastic DIP | 10189N     |
| 16-Pin Ceramic DIP | 10189F     |


## PIN DESCRIPTION

| PINS                    | DESCRIPTION         |
|-------------------------|---------------------|
| $D_0 - D_5$             | Data Inputs         |
| $\bar{E}$               | Common Enable Input |
| $\bar{Q}_0 - \bar{Q}_5$ | Data Outputs        |

## PIN CONFIGURATION



## LOGIC DIAGRAM



Inverter

10189

ABSOLUTE MAXIMUM RATINGS

| SYMBOL          | PARAMETER                                                                           |                 | LIMITS               | UNIT |
|-----------------|-------------------------------------------------------------------------------------|-----------------|----------------------|------|
| V <sub>EE</sub> | Supply voltage                                                                      |                 | −8.0                 | V    |
| V <sub>IN</sub> | Input voltage (V <sub>IN</sub> should never be more negative than V <sub>EE</sub> ) |                 | 0 to V <sub>EE</sub> | V    |
| I <sub>O</sub>  | Output source current (continuous)                                                  |                 | −50                  | mA   |
| T <sub>S</sub>  | Storage temperature range                                                           |                 | −55 to +150          | °C   |
| T <sub>J</sub>  | Maximum junction temperature                                                        | Ceramic Package | +165                 | °C   |
|                 |                                                                                     | Plastic Package | +150                 | °C   |

**NOTE:**  
Operation beyond the limits set forth in this table may impair the useful life of the device. Unless otherwise noted, these limits are specified over the operating ambient temperature range.

DC OPERATING CONDITIONS

| SYMBOL                              | PARAMETER                           | TEST CONDITIONS        | LIMITS |      |       | UNIT |
|-------------------------------------|-------------------------------------|------------------------|--------|------|-------|------|
|                                     |                                     |                        | MIN.   | NOM. | MAX.  |      |
| V <sub>CC1</sub> , V <sub>CC2</sub> | Circuit ground                      |                        | 0      | 0    | 0     | V    |
| V <sub>EE</sub>                     | Supply voltage (negative)           |                        |        | −5.2 |       | V    |
| V <sub>IH</sub>                     | High level input voltage            | T <sub>A</sub> = −30°C |        |      | −890  | mV   |
|                                     |                                     | T <sub>A</sub> = +25°C |        |      | −810  | mV   |
|                                     |                                     | T <sub>A</sub> = +85°C |        |      | −700  | mV   |
| V <sub>IHT</sub>                    | High level input threshold voltage  | T <sub>A</sub> = −30°C | −1205  |      |       | mV   |
|                                     |                                     | T <sub>A</sub> = +25°C | −1105  |      |       | mV   |
|                                     |                                     | T <sub>A</sub> = +85°C | −1035  |      |       | mV   |
| V <sub>ILT</sub>                    | Low level input threshold voltage   | T <sub>A</sub> = −30°C |        |      | −1500 | mV   |
|                                     |                                     | T <sub>A</sub> = +25°C |        |      | −1475 | mV   |
|                                     |                                     | T <sub>A</sub> = +85°C |        |      | −1440 | mV   |
| V <sub>IL</sub>                     | Low level input voltage             | T <sub>A</sub> = −30°C | −1890  |      |       | mV   |
|                                     |                                     | T <sub>A</sub> = +25°C | −1850  |      |       | mV   |
|                                     |                                     | T <sub>A</sub> = +85°C | −1825  |      |       | mV   |
| T <sub>A</sub>                      | Operating ambient temperature range |                        | −30    | +25  | +85   | °C   |

**NOTE:**  
When operating at other than the specified V<sub>EE</sub> voltage (−5.2V), the DC and AC Electrical Characteristics will vary slightly from specified values.

## Inverter

10189

**DC ELECTRICAL CHARACTERISTICS**  $V_{CC1} = V_{CC2} = \text{ground}$ ,  $V_{EE} = -5.2V \pm 0.010V$ ,  $T_A = -30^\circ\text{C}$  to  $+85^\circ\text{C}$  output loading  $50\Omega$  to  $-2.0V \pm 0.010V$  unless otherwise specified<sup>1,3</sup>

| SYMBOL                                |                                        | PARAMETER              |                                                                                                                                                                    | TEST CONDITIONS <sup>2</sup>                                                                                           |    | LIMITS |      |      | UNIT |
|---------------------------------------|----------------------------------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|----|--------|------|------|------|
|                                       |                                        |                        |                                                                                                                                                                    |                                                                                                                        |    | MIN.   | TYP. | MAX. |      |
| V <sub>OH</sub>                       | High level output voltage              | T <sub>A</sub> = −30°C | Apply V <sub>ILMIN</sub> to all inputs.                                                                                                                            | −1060                                                                                                                  |    | −890   | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +25°C |                                                                                                                                                                    | −960                                                                                                                   |    | −810   | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +85°C |                                                                                                                                                                    | −890                                                                                                                   |    | −700   | mV   |      |      |
| V <sub>OHT</sub>                      | High level output threshold voltage    | T <sub>A</sub> = −30°C | Apply V <sub>ILT</sub> to each D <sub>n</sub> input, one at a time, with V <sub>ILMIN</sub> applied to E input and V <sub>IHMAX</sub> applied to all other inputs. | −1080                                                                                                                  |    |        | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +25°C |                                                                                                                                                                    | −980                                                                                                                   |    |        | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +85°C |                                                                                                                                                                    | −910                                                                                                                   |    |        | mV   |      |      |
| V <sub>OLT</sub>                      | Low level output threshold voltage     | T <sub>A</sub> = −30°C | Apply V <sub>IHT</sub> to each D <sub>n</sub> input, one at a time, with V <sub>ILMIN</sub> applied to E input and V <sub>ILMIN</sub> applied to all other inputs. |                                                                                                                        |    | −1655  | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +25°C |                                                                                                                                                                    |                                                                                                                        |    | −1630  | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +85°C |                                                                                                                                                                    |                                                                                                                        |    | −1595  | mV   |      |      |
| V <sub>OL</sub>                       | Low level output voltage               | T <sub>A</sub> = −30°C | Apply V <sub>IHMAX</sub> to all D <sub>n</sub> inputs with V <sub>ILMIN</sub> applied to E input.                                                                  | −1890                                                                                                                  |    | −1675  | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +25°C |                                                                                                                                                                    | −1850                                                                                                                  |    | −1650  | mV   |      |      |
|                                       |                                        | T <sub>A</sub> = +85°C |                                                                                                                                                                    | −1825                                                                                                                  |    | −1615  | mV   |      |      |
| I <sub>IH</sub>                       | High level input current               | Other inputs           | T <sub>A</sub> = −30°C                                                                                                                                             | Apply V <sub>IHMAX</sub> to each input under test, one at a time, with V <sub>ILMIN</sub> applied to all other inputs. |    |        | 425  | μA   |      |
|                                       |                                        |                        | T <sub>A</sub> = +25°C                                                                                                                                             |                                                                                                                        |    |        | 265  | μA   |      |
|                                       |                                        |                        | T <sub>A</sub> = +85°C                                                                                                                                             |                                                                                                                        |    |        | 265  | μA   |      |
|                                       |                                        | E input                | T <sub>A</sub> = −30°C                                                                                                                                             | Apply V <sub>IHMAX</sub> to E input with V <sub>ILMIN</sub> applied to all other inputs.                               |    |        | 890  | μA   |      |
|                                       |                                        |                        | T <sub>A</sub> = +25°C                                                                                                                                             |                                                                                                                        |    |        | 555  | μA   |      |
|                                       |                                        |                        | T <sub>A</sub> = +85°C                                                                                                                                             |                                                                                                                        |    |        | 555  | μA   |      |
| I <sub>IL</sub>                       | Low level input current                | T <sub>A</sub> = −30°C | Apply V <sub>ILMIN</sub> to each input under test, one at a time, with V <sub>IHMAX</sub> applied to all other inputs.                                             | 0.5                                                                                                                    |    |        | μA   |      |      |
|                                       |                                        | T <sub>A</sub> = +25°C |                                                                                                                                                                    | 0.5                                                                                                                    |    |        | μA   |      |      |
|                                       |                                        | T <sub>A</sub> = +85°C |                                                                                                                                                                    | 0.3                                                                                                                    |    |        | μA   |      |      |
| −I <sub>EE</sub>                      | V <sub>EE</sub> supply current         | T <sub>A</sub> = −30°C |                                                                                                                                                                    |                                                                                                                        |    | 44     | mA   |      |      |
|                                       |                                        | T <sub>A</sub> = +25°C |                                                                                                                                                                    |                                                                                                                        | 30 | 40     | mA   |      |      |
|                                       |                                        | T <sub>A</sub> = +85°C |                                                                                                                                                                    |                                                                                                                        |    | 44     | mA   |      |      |
| $\frac{\Delta V_{OH}}{\Delta V_{EE}}$ | High level output voltage compensation | T <sub>A</sub> = +25°C |                                                                                                                                                                    |                                                                                                                        |    | 0.016  |      | V/V  |      |
| $\frac{\Delta V_{OL}}{\Delta V_{EE}}$ | Low level output voltage compensation  |                        |                                                                                                                                                                    |                                                                                                                        |    | 0.250  |      | V/V  |      |
| $\frac{\Delta V_{BB}}{\Delta V_{EE}}$ | Reference bias voltage compensation    |                        |                                                                                                                                                                    |                                                                                                                        |    | 0.148  |      | V/V  |      |

**NOTES:**

- The specified limits represent the worst case values for the parameter. Since these worst case values normally occur at the supply voltage and temperature extremes, additional noise immunity can be achieved by decreasing the allowable operating condition ranges.
- Conditions for testing shown in the tables are not necessarily worst case. For worst case testing guidelines, refer to DC Testing, Chapter 1, Section 3.
- The specified limits shown in the DC Electrical Characteristics table can be met only after thermal equilibrium has been established. Thermal equilibrium is established by applying power for at least 2 minutes, while maintaining transverse airflow of 2.5 meters/sec (500 linear feet/min) over the device, mounted either in a test socket or on a printed circuit board. Test voltage values are given in the DC Operating Conditions table.

## Inverter

10189

AC ELECTRICAL CHARACTERISTICS  $V_{CC1} = V_{CC2} = \text{ground}$ ,  $V_{EE} = -5.2V \pm 0.010V$ 

| SYMBOL                               | PARAMETER                                             | TEST<br>CONDITIONS | LIMITS                 |              |                        |              |              |                        |              |          | UNIT |
|--------------------------------------|-------------------------------------------------------|--------------------|------------------------|--------------|------------------------|--------------|--------------|------------------------|--------------|----------|------|
|                                      |                                                       |                    | T <sub>A</sub> = -30°C |              | T <sub>A</sub> = +25°C |              |              | T <sub>A</sub> = +85°C |              |          |      |
|                                      |                                                       |                    | MIN.                   | MAX.         | MIN.                   | TYP.         | MAX.         | MIN.                   | MAX.         |          |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation delay<br>D <sub>n</sub> to Q <sub>n</sub> | Waveform 1         | 1.00<br>1.00           | 3.30<br>3.30 | 1.00<br>1.00           | 2.00<br>2.00 | 2.90<br>2.90 | 1.00<br>1.00           | 3.30<br>3.30 | ns<br>ns |      |
| t <sub>PLH</sub><br>t <sub>PHL</sub> | Propagation delay<br>E to Q <sub>n</sub>              | Waveform 2         | 1.10<br>1.10           | 3.90<br>3.90 | 1.10<br>1.10           | 2.50<br>2.50 | 3.50<br>3.50 | 1.10<br>1.10           | 3.90<br>3.90 | ns<br>ns |      |
| t <sub>TLH</sub><br>t <sub>THL</sub> | Transition time<br>20% to 80%, 80% to 20%             | Waveform 1, 2      | 1.10<br>1.10           | 3.60<br>3.60 | 1.10<br>1.10           | 2.00<br>2.00 | 3.30<br>3.30 | 1.10<br>1.10           | 3.70<br>3.70 | ns<br>ns |      |

## NOTE:

For AC test setup information, see AC Testing, Chapter 2, Section 3.

## AC WAVEFORMS

