

BOX 343409/CORAL GABLES/FLORIDA 33134/PHONE 305/448-8200

POWER SUPPLY SPECIFICATIONS *

INPUT VOLTAGE AND FREQUENCY: 105 to 125Vac-50 to 440Hz

INPUT ISOLATION: 50 Mohms

VOLTAGE OUTPUT TOLERANCE: Factory set at $\pm 1\%$ (fixed)OPERATING TEMPERATURE: -25°C to $+71^{\circ}\text{C}$ TEMPERATURE COEFFICIENT: $0.02\%/^{\circ}\text{C}$ typicalSTORAGE TEMPERATURE: -25°C to 85°C *115 VAC, 50 to 400 Hz, $@25^{\circ}\text{C}$

FEATURES


P.C Card Mounting. Optional Chassis Mounting With Terminal Barrier Strip.


Short Circuit Protection

Single, Dual and Triple Outputs

Five Year Warranty

CASES A,B,C,D





BOX 343409/CORAL GABLES/FLORIDA 33134/PHONE 305/448-8200

PRICE LISTEFFECTIVE 6/1/86POWER SUPPLIES

<u>Model No.</u>	<u>Output Voltage Vdc</u>	<u>Output Current mA</u>	<u>Regulation Line</u>	<u>Load</u>	<u>Ripple and Noise</u>	<u>Case Size</u>	<u>Price</u>
1.5.1000	+5	1000	0.02%	0.05%	1.0mVRMS	B	\$52.50
1.5.2000	+5	2000	0.02%	0.1%	1.0mVRMS	D	\$74.50
2.15.100	+15	100	0.02%	0.02%	1.0mVRMS	A	\$42.50
2.15.200	+15	200	0.02%	0.05%	1.0mVRMS	B	\$68.50
2.15.350	+15	350	0.02%	0.05%	1.0mVRMS	C	\$82.50
3.15.100-5	+15/+5	100/500	0.02%	0.1%	1.0mVRMS	C	\$87.50

MOUNTING KITS

Terminal strip type. Plug-in mating sockets with barrier type terminal strips. Fits all model power supplies listed above.

<u>Model No.</u>	<u>Price</u>
MSB-1 (accommodates one power supply)	\$16.50
MSB-2 (accommodates two power supplies)	\$27.50
Bench Master (converts a power supply to a bench model)	\$34.50

CUTTING AND BENDING TOOLS

<u>Model No.</u>	<u>Price</u>
TP/3	\$62.50
TP/3 Tips	\$21.50
PR-1	\$62.50