

BAT54 / A / C / S


Silicon epitaxial planar type

Features


- Small surface mounting type
- High reliability
- High speed ($t_{rr} < 5\text{ ns}$)

Mechanical data

Case : SOT-23
Terminals : Solder plated, solderable per MIL-STD-750,
Method 2026
Mounting Position : Any



Marking Code



MAXIMUM RATINGS (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Repetitive peak reverse voltage		V_{RRM}			30	V
Reverse voltage		V_R			30	V
Peak forward surge current	$t_p < 10\text{ ms}$	I_{FSM}			600	mA
Repetitive peak forward current	$t_p < 1\text{ s}$	I_{FRM}			300	mA
Forward current		I_F			200	mA
Junction temperature		T_j			125	$^{\circ}\text{C}$
Storage temperature		T_{STG}	-55		+150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS (AT $T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Forward voltage	$I_F = 0.1\text{mA}$	V_F			0.240	V
	$I_F = 1\text{mA}$	V_F			0.320	V
	$I_F = 10\text{mA}$	V_F			0.400	V
	$I_F = 30\text{mA}$	V_F			0.500	V
	$I_F = 100\text{mA}$	V_F			0.800	V
Reverse current	$V_R = 25\text{V}$	I_R			2.0	μA
Diode capacitance	$V_R = 1\text{V}$, $f = 1\text{MHz}$	C_D			10.0	pF
Reverse recovery time	$I_F = 10\text{mA}$, $V_R = 10\text{mA}$, $I_{RR} = 0.1 \times I_R$, $R_L = 100\Omega$	t_{rr}			5	ns

RATING AND CHARACTERISTIC CURVES for each diode (BAT54 / A / C / S)

FIG.1-TYPICAL FORWARD CHARACTERISTICS




FIG.2 - Leakage Current CHARACTERISTICS






FIG.3-TYPICAL JUNCTION CAPACITANCE



- Notes :
1. A 2.0 Kohm variable resistor adjusted for a forward Current (I_F) of 10mA.
 2. Input pulse is adjusted so $I_R(\text{peak})$ is equal to 10 mA.
 3. $t_p \gg t_{rr}$.

t

Recovery Time Equivalent Test Circuit