

Silicon NPN Power Transistors

2SD869

DESCRIPTION

- With TO-3 package
- Built-in damper diode
- High voltage ,high speed
- Low collector saturation voltage

APPLICATIONS

- For color TV horizontal output applications

PINNING(see fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings(Ta=℃)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	1500	V
V _{CEO}	Collector-collector voltage	Open base	600	V
V _{EBO}	Emitter-base voltage	Open collector	5	V
I _C	Collector current		3.5	A
I _E	Emitter current		-3.5	A
P _T	Total power dissipation	T _C =25℃	50	W
T _j	Junction temperature		150	℃
T _{stg}	Storage temperature		-65~150	℃

Silicon NPN Power Transistors**2SD869****CHARACTERISTICS**T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =200m A; I _C =0	5			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =3 A; I _B =0.8 A			8.0	V
V _{BEsat}	Base-emitter saturation voltage	I _C =3 A; I _B =0.8 A			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =500V; I _E =0			10	μ A
h _{FE}	DC current gain	I _C =0.5A ; V _{CE} =5V	8			
V _F	Diode forward voltage	I _F =3.5A			2.0	V
f _T	Transition frequency	I _C =0.1A ; V _{CE} =10V		3		MHz
C _{OB}	Collector output capacitance	I _E =0 ; V _{CB} =10V; f=1MHz		95		pF
t _f	Fall time	I _C =3A; I _{B1end} =0.8A			1.0	μ s

Silicon NPN Power Transistors

2SD869

PACKAGE OUTLINE




Fig.2 Outline dimensions