


NKK® SERIES B PUSHBUTTON SWITCHES

MOMENTARY & ALTERNATE/ANTISTATIC/WASHABLE

TYPICAL SWITCH ORDERING EXAMPLE



POLES AND CIRCUITS			
POLE & THROW	MODEL	PLUNGER POSITION & TERMINAL NUMBERS () = Momentary	
		Normal	Down
SPDT	BB15 BB16	ON ON	(ON) ON
CONNECTED TERMINALS		2-3	2-1
SCHEMATIC			
DPDT	BB25 BB26	ON ON	(ON) ON
CONNECTED TERMINALS		2-3 5-6	2-1 5-4
SCHEMATIC			
Terminal numbers are not actually on the switch.			

OPTIONAL SLIP-ON CAPS	
F AT475 .201" Dia. Cap	H AT496 .295" Dia. Cap
Material: Polycarbonate Colors Available: A Black B White C Red Freon or alcohol cleaning solvents are recommended for protection of polycarbonate parts.	

PLUNGER
A .213" Long
Standard color: White
For other color options & plunger lengths, contact factory.

TERMINALS
Terminal dimensions are in the following drawings. Note that the single pole alternate action model is in a double pole base.

NKK® SERIES B PUSHBUTTON SWITCHES

MOMENTARY & ALTERNATE/ANTISTATIC/WASHABLE

Single pole alternate action detail drawings and footprints are located at the end of the next page.


P

Straight Terminals without Bracket/Single Pole

For Single Pole Momentary



BB15AP-FA Model Shown




P

Straight Terminals without Bracket/Double Pole

For DP Momentary or SP & DP Alternate Action



BB25AP-FA Model Shown




B

Straight Terminals with Bracket/Single Pole

For SP Momentary



BB15AB-FA Model Shown




B

Straight Terminals with Bracket/Double Pole

For DP Momentary or SP & DP Alternate Action



BB25AB-FA Model Shown




H

Right Angle Terminals with Bracket/Single Pole

For Single Pole Momentary






BB15AH-FA Model Shown




Pushbuttons

For DP Momentary or SP & DP Alternate Action



All alternate action models have double pole bases.



MOMENTARY & ALTERNATE/ANTISTATIC/WASHABLE

GENERAL SPECIFICATIONS

Electrical Capacity: (Resistive Load)	0.4VA maximum @ 28V AC/DC maximum (Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)
Contact Resistance:	50 milliohms maximum
Insulation Resistance:	500 megohms minimum @ 500V DC
Dielectric Strength:	500V AC minimum
Mechanical Life:	50,000 operations min (momentary); 25,000 operations min (alternate action)
Electrical Life:	50,000 operations min (momentary); 25,000 operations min (alternate action)
Ambient Temp Range:	-25°C through +70°C (-13°F through +158°F)
Travel:	Momentary: Pretravel 0.7mm (.028"); Overtravel 0.4mm (.016"); Total 1.1mm (.043") Alternate: Pretravel 1.0mm (.039"); Overtravel 1.0mm (.039"); Total 2.0mm (.079")
Nominal Operating Force:	260 grams (momentary); 300 grams (alternate action)


MATERIALS & FINISHES

Plunger	Polyacetal
Bushing	Carbon blended polyamide
Case Housing	Glass fiber reinforced polyamide
Support Bracket	Tin plated phosphor bronze
Movable Contact	Phosphor bronze with gold plating over silver plating
Stationary Contacts	Brass with gold plating over nickel undercoating
Terminals	Brass with gold plating over nickel undercoating

SEALED FOR WASHABILITY

Sealed-body construction permits Series B pushbutton switches to be subjected to time- and money-saving automated soldering techniques. They can be safely cleaned of flux without fear of compromising operating characteristics; **the actuator must be in UP position during washing and cap removal.** Alcohol cleaning solvents are recommended.

LATCHDOWN DIMENSIONS



The latchdown feature on maintained circuits provides visible, audible, and tactile feedback.

Toggles

Pushbuttons

NKK®

SERIES B

SUPER-SUBMINIATURE/PCB/ANTISTATIC/WASHABLE

A-25-13

DISTINCTIVE FEATURES



Available with toggles, paddles, and pushbuttons.


Industry's smallest alternate action pushbutton

Locking lever mechanism offered as a toggle option.

Smooth round 6mm diameter bushing simplifies panel layout.


Antistatic superstructure prevents static discharge to the contacts.

Patented Sliding Twin Crossbar (STC) contact mechanism provides smoother, positive detent and more reliable logic-level operation.



Totally sealed body prevents contact contamination and allows wave soldering and washing.


.100" x .100" terminal spacing conforms to standard PC board grids.





NKK®**SERIES B****SUPER-SUBMINIATURE/PCB/ANTISTATIC/WASHABLE****APPLICATIONS**

- Toggles
- Pushbuttons

Ultraminiaturized B Series PC mountable switches feature an antistatic bushing which is smooth and round, Sliding Twin Crossbar (STC) contacts and sealed construction. They are recommended for use in products where reliability is essential and space is restricted. Typical applications include computers, peripherals, communications systems, medical equipment, home videos, cameras and small measuring instruments.

**ANTISTATIC CONSTRUCTION**

The switch is grounded to the PC board by means of the carbon impregnated bushing and the support bracket. Static electricity from an operator's touch travels a safe path from actuator through the bushing and bracket to the PC board, rather than traveling into the contacts.

STC CONTACT MECHANISM

NKK's patented, award-winning STC contact mechanism offers benefits unavailable in conventional mechanisms. The movable twin contact surfaces pinch the stationary contacts to provide increased contact stability and unparalleled logic-level reliability. Continued reliability is assured since the gold-plated contacts are wiped clean with each actuation. Furthermore, if one side of the twin contacts should fail to conduct, the other side functions as a backup, or fail-safe path for the current. The combination of rounded movable and stationary contacts provides smooth contact feel previously unavailable in sliding contact type mechanisms.

SEALED FOR WASHABILITY

Sealed-body construction permits Series B switches to be subjected to time- and money-saving automated soldering techniques. As a result, they can be safely cleaned of flux without fear of compromising operating characteristics.

NKK®
switches

D 98E ■ 6428776 0001919 674 ■

• 7850 E. Gelding Dr. • Scottsdale, AZ 85260 • Phone (602) 991-0942 • Fax (602) 998-1435