


# MAX3238

## 3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH $\pm 15$ -kV ESD (HBM) PROTECTION

SLLS349J – JUNE 1999 – REVISED MARCH 2004

- RS-232 Bus-Pin ESD Protection Exceeds  $\pm 15$  kV Using Human-Body Model (HBM)
- Meets or Exceeds the Requirements of TIA/EIA-232-F and ITU v.28 Standards
- Operates With 3-V to 5.5-V  $V_{CC}$  Supply
- Operates Up To 250 kbit/s
- Five Drivers and Three Receivers
- Low Standby Current . . . 1  $\mu$ A Typical
- External Capacitors . . .  $4 \times 0.1 \mu$ F
- Accepts 5-V Logic Input With 3.3-V Supply
- Always-Active Noninverting Receiver Output (ROUT1B)
- Alternative High-Speed Pin-Compatible Device (1 Mbit/s)
  - SNx5C3238
- Applications
  - Battery-Powered Systems, PDAs, Notebooks, Subnotebooks, Laptops, Palmtop PCs, Hand-Held Equipment, Modems, and Printers

DB OR PW PACKAGE  
(TOP VIEW)



### description/ordering information

The MAX3238 consists of five line drivers, three line receivers, and a dual charge-pump circuit with  $\pm 15$ -kV ESD (HBM) protection pin to pin (serial-port connection pins, including GND). The device meets the requirements of TIA/EIA-232-F and provides the electrical interface between notebook and subnotebook computer applications. The charge pump and four small external capacitors allow operation from a single 3-V to 5.5-V supply. In addition, the device includes an always-active noninverting output (ROUT1B), which allows applications using the ring indicator to transmit data while the device is powered down. These devices operate at data signaling rates up to 250 kbit/s and a maximum of 30-V/ $\mu$ s driver output slew rate.

### ORDERING INFORMATION

| $T_A$         | PACKAGE†   |              | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|---------------|------------|--------------|-----------------------|------------------|
| –0°C to 70°C  | SSOP (DB)  | Tube of 50   | MAX3238CDB            | MAX3238C         |
|               |            | Reel of 2000 | MAX3238CDBR           |                  |
|               | TSSOP (PW) | Tube of 50   | MAX3238CPW            | MA3238C          |
|               |            | Reel of 2000 | MAX3238CPWR           |                  |
| –40°C to 85°C | SSOP (DB)  | Tube of 50   | MAX3238IDB            | MAX3238I         |
|               |            | Reel of 2000 | MAX3238IDBR           |                  |
|               | TSSOP (PW) | Tube of 50   | MAX3238IPW            | MB3238I          |
|               |            | Reel of 2000 | MAX3238IPWR           |                  |

† Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 2004, Texas Instruments Incorporated

**description/ordering information (continued)**

Flexible control options for power management are featured when the serial port and driver inputs are inactive. The auto-powerdown plus feature functions when FORCEON is low and  $\overline{\text{FORCEOFF}}$  is high. During this mode of operation, if the device does not sense valid signal transitions on all receiver and driver inputs for approximately 30 s, the built-in charge pump and drivers are powered down, reducing the supply current to 1  $\mu\text{A}$ . By disconnecting the serial port or placing the peripheral drivers off, auto-powerdown plus occurs if there is no activity in the logic levels for the driver inputs. Auto-powerdown plus can be disabled when FORCEON and  $\overline{\text{FORCEOFF}}$  are high. With auto-powerdown plus enabled, the device activates automatically when a valid signal is applied to any receiver or driver input. INVALID is high (valid data) if any receiver input voltage is greater than 2.7 V or less than  $-2.7$  V, or has been between  $-0.3$  V and 0.3 V for less than 30  $\mu\text{s}$ . INVALID is low (invalid data) if all receiver input voltages are between  $-0.3$  V and 0.3 V for more than 30  $\mu\text{s}$ . Refer to Figure 5 for receiver input levels.

**Function Tables****EACH DRIVER**

| INPUTS |         |                              |  | OUTPUT<br>DOUT | DRIVER STATUS   |
|--------|---------|------------------------------|--|----------------|---|
| DIN    | FORCEON | $\overline{\text{FORCEOFF}}$ | TIME ELAPSED SINCE LAST<br>RIN OR DIN TRANSITION |                |   |
| X      | X       | L                            | X  | Z              | Powered off   |
| L      | H       | H                            | X  | H              | Normal operation with<br>auto-powerdown plus disabled |
| H      | H       | H                            | X  | L              |   |
| L      | L       | H                            | <30 s  | H              | Normal operation with<br>auto-powerdown plus enabled  |
| H      | L       | H                            | <30 s  | L              |   |
| L      | L       | H                            | >30 s  | Z              | Powered off by<br>auto-powerdown plus feature         |
| H      | L       | H                            | >30 s  | Z              |   |

H = high level, L = low level, X = irrelevant, Z = high impedance


**EACH RECEIVER**

| INPUTS |           |                              |  | OUTPUTS |      | RECEIVER STATUS  |
|--------|-----------|------------------------------|--|---------|------|--|
| RIN1   | RIN2–RIN3 | $\overline{\text{FORCEOFF}}$ | TIME ELAPSED SINCE LAST RIN<br>OR DIN TRANSITION | ROUT1B  | ROUT |  |
| L      | X         | L                            | X  | L       | Z    | Powered off while<br>ROUT1B is active                            |
| H      | X         | L                            | X  | H       | Z    |  |
| L      | L         | H                            | <30 s  | L       | H    | Normal operation with<br>auto-powerdown plus<br>disabled/enabled |
| L      | H         | H                            | <30 s  | L       | L    |  |
| H      | L         | H                            | <30 s  | H       | H    |  |
| H      | H         | H                            | <30 s  | H       | L    |  |
| Open   | Open      | H                            | >30 s  | L       | H    |  |

H = high level, L = low level, X = irrelevant, Z = high impedance (off), Open = input disconnected or connected driver off

**MAX3238**  
**3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER**  
**WITH  $\pm 15$ -kV ESD (HBM) PROTECTION**  
SLLS349J – JUNE 1999 – REVISED MARCH 2004

logic diagram (positive logic)



**MAX3238****3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER****WITH  $\pm 15$ -kV ESD (HBM) PROTECTION**

SLLS349J – JUNE 1999 – REVISED MARCH 2004

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>**

|   |                            |
|---|----------------------------|
| Supply voltage range, $V_{CC}$ (see Note 1)                                   | –0.3 V to 6 V              |
| Positive output supply voltage range, $V_+$ (see Note 1)                      | –0.3 V to 7 V              |
| Negative output supply voltage range, $V_-$ (see Note 1)                      | 0.3 V to –7 V              |
| Supply voltage difference, $V_+ - V_-$ (see Note 1)                           | 13 V                       |
| Input voltage range, $V_I$ : Driver ( $\overline{\text{FORCEOFF}}$ , FORCEON) | –0.3 V to 6 V              |
| Receiver  | –25 V to 25 V              |
| Output voltage range, $V_O$ : Driver  | –13.2 V to 13.2 V          |
| Receiver (INVALID)  | –0.3 V to $V_{CC} + 0.3$ V |
| Package thermal impedance, $\theta_{JA}$ (see Notes 2 and 3): DB package      | 62°C/W                     |
| PW package  | 62°C/W                     |
| Operating virtual junction temperature, $T_J$                                 | 150°C                      |
| Storage temperature range, $T_{stg}$  | –65°C to 150°C             |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltages are with respect to network GND.

2. Maximum power dissipation is a function of  $T_J(\text{max})$ ,  $\theta_{JA}$ , and  $T_A$ . The maximum allowable power dissipation at any allowable ambient temperature is  $P_D = (T_J(\text{max}) - T_A)/\theta_{JA}$ . Operating at the absolute maximum  $T_J$  of 150°C can affect reliability.

3. The package thermal impedance is calculated in accordance with JESD 51-7.

**recommended operating conditions (see Note 4 and Figure 6)**

|                |   |   | MIN              | NOM | MAX | UNIT |
|----------------|---|---|------------------|-----|-----|------|
| Supply voltage |   | $V_{CC} = 3.3$ V                            | 3                | 3.3 | 3.6 | V    |
|                |   | $V_{CC} = 5$ V                              | 4.5              | 5   | 5.5 |      |
| $V_{IH}$       | Driver and control high-level input voltage | DIN, $\overline{\text{FORCEOFF}}$ , FORCEON | $V_{CC} = 3.3$ V |     | 2   | V    |
|                |   |   | $V_{CC} = 5$ V   |     | 2.4 |      |
| $V_{IL}$       | Driver and control low-level input voltage  | DIN, $\overline{\text{FORCEOFF}}$ , FORCEON |                  |     | 0.8 | V    |
| $V_I$          | Driver and control input voltage            | DIN, $\overline{\text{FORCEOFF}}$ , FORCEON | 0                |     | 5.5 | V    |
| $V_I$          | Receiver input voltage                      |   | –25              |     | 25  | V    |
| $T_A$          | Operating free-air temperature              | MAX3238C                                    | 0                |     | 70  | °C   |
|                |   | MAX3238I                                    | –40              |     | 85  |      |

NOTE 4: Testing supply conditions are C1–C4 = 0.1  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.15$  V; C1–C4 = 0.22  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.3$  V; and C1 = 0.047  $\mu$ F and C2–C4 = 0.33  $\mu$ F at  $V_{CC} = 5$  V  $\pm 0.5$  V.

**electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 6)**

| PARAMETER       |   | TEST CONDITIONS                        | MIN   | TYP‡ | MAX | UNIT |    |
|-----------------|---|--|---|------|-----|------|----|
| I <sub>I</sub>  | Input leakage current                     | $\overline{\text{FORCEOFF}}$ , FORCEON | ±0.01   |      | ±1  | μA   |    |
| I <sub>CC</sub> | Supply current<br>(T <sub>A</sub> = 25°C) | Auto-powerdown plus disabled           | No load,<br>$\overline{\text{FORCEOFF}}$ and FORCEON at V <sub>CC</sub>                                       |      | 0.5 | 2    | mA |
|                 |   | Powered off                            | No load, $\overline{\text{FORCEOFF}}$ at GND  |      | 1   | 10   |    |
|                 |   | Auto-powerdown plus enabled            | No load, $\overline{\text{FORCEOFF}}$ at V <sub>CC</sub> ,<br>FORCEON at GND,<br>All RIN are open or grounded |      | 1   | 10   | μA |

<sup>‡</sup> All typical values are at  $V_{CC} = 3.3$  V or  $V_{CC} = 5$  V, and  $T_A = 25^\circ\text{C}$ .

NOTE 4: Testing supply conditions are C1–C4 = 0.1  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.15$  V; C1–C4 = 0.22  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.3$  V; and C1 = 0.047  $\mu$ F and C2–C4 = 0.33  $\mu$ F at  $V_{CC} = 5$  V  $\pm 0.5$  V.



**MAX3238**  
**3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER**  
**WITH  $\pm 15$ -kV ESD (HBM) PROTECTION**  
 SLLS349J – JUNE 1999 – REVISED MARCH 2004

## DRIVER SECTION

**electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 6)**

| PARAMETER                              | TEST CONDITIONS  | MIN | TYP†       | MAX       | UNIT          |
|--|--|-----|------------|-----------|---------------|
| $V_{OH}$ High-level output voltage     | All DOUT at $R_L = 3\text{ k}\Omega$ to GND  | 5   | 5.4        |           | V             |
| $V_{OL}$ Low-level output voltage      | All DOUT at $R_L = 3\text{ k}\Omega$ to GND  | –5  | –5.4       |           | V             |
| $I_{IH}$ High-level input current      | $V_I = V_{CC}$   |     | $\pm 0.01$ | $\pm 1$   | $\mu\text{A}$ |
| $I_{IL}$ Low-level input current       | $V_I$ at GND   |     | $\pm 0.01$ | $\pm 1$   | $\mu\text{A}$ |
| $I_{OS}$ Short-circuit output current‡ | $V_{CC} = 3.6\text{ V}$ , $V_O = 0\text{ V}$   |     | $\pm 35$   | $\pm 60$  | mA            |
|  | $V_{CC} = 5.5\text{ V}$ , $V_O = 0\text{ V}$   |     | $\pm 40$   | $\pm 100$ |               |
| $r_o$ Output resistance                | $V_{CC}$ , $V_+$ , and $V_- = 0\text{ V}$ , $V_O = \pm 2\text{ V}$   | 300 | 10M        |           | $\Omega$      |
| $I_{off}$ Output leakage current       | $\overline{\text{FORCEOFF}} = \text{GND}$ , $V_O = \pm 12\text{ V}$ , $V_{CC} = 3\text{ V to } 3.6\text{ V}$   |     |            | $\pm 25$  | $\mu\text{A}$ |
|  | $\overline{\text{FORCEOFF}} = \text{GND}$ , $V_O = \pm 10\text{ V}$ , $V_{CC} = 4.5\text{ V to } 5.5\text{ V}$ |     |            | $\pm 25$  |               |

† All typical values are at  $V_{CC} = 3.3\text{ V}$  or  $V_{CC} = 5\text{ V}$ , and  $T_A = 25^\circ\text{C}$ .

‡ Short-circuit durations should be controlled to prevent exceeding the device absolute power-dissipation ratings, and not more than one output should be shorted at a time.

NOTE 4: Testing supply conditions are C1–C4 =  $0.1\text{ }\mu\text{F}$  at  $V_{CC} = 3.3\text{ V} \pm 0.15\text{ V}$ ; C1–C4 =  $0.22\text{ }\mu\text{F}$  at  $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ ; and C1 =  $0.047\text{ }\mu\text{F}$  and C2–C4 =  $0.33\text{ }\mu\text{F}$  at  $V_{CC} = 5\text{ V} \pm 0.5\text{ V}$ .

**switching characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 6)**

| PARAMETER   | TEST CONDITIONS  | MIN                                      | TYP† | MAX | UNIT                   |
|---|--|--|------|-----|------------------------|
| Maximum data rate                                       | $C_L = 1000\text{ pF}$ ,<br>One DOUT switching,<br>$R_L = 3\text{ k}\Omega$ ,<br>See Figure 1                  | 150                                      | 250  |     | kbit/s                 |
| $t_{sk(p)}$ Pulse skew§                                 | $C_L = 150\text{ pF to } 2500\text{ pF}$ ,<br>$R_L = 3\text{ k}\Omega$ to $7\text{ k}\Omega$ ,<br>See Figure 2 |  | 100  |     | ns                     |
| $SR(tr)$ Slew rate, transition region<br>(see Figure 1) | $V_{CC} = 3.3\text{ V}$ ,<br>$R_L = 3\text{ k}\Omega$ to $7\text{ k}\Omega$                                    | $C_L = 150\text{ pF to } 1000\text{ pF}$ | 6    | 30  | $\text{V}/\mu\text{s}$ |
|   |  | $C_L = 150\text{ pF to } 2500\text{ pF}$ | 4    | 30  |                        |

† All typical values are at  $V_{CC} = 3.3\text{ V}$  or  $V_{CC} = 5\text{ V}$ , and  $T_A = 25^\circ\text{C}$ .

§ Pulse skew is defined as  $|t_{PLH} - t_{PHL}|$  of each channel of the same device.

NOTE 4: Testing supply conditions are C1–C4 =  $0.1\text{ }\mu\text{F}$  at  $V_{CC} = 3.3\text{ V} \pm 0.15\text{ V}$ ; C1–C4 =  $0.22\text{ }\mu\text{F}$  at  $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ ; and C1 =  $0.047\text{ }\mu\text{F}$  and C2–C4 =  $0.33\text{ }\mu\text{F}$  at  $V_{CC} = 5\text{ V} \pm 0.5\text{ V}$ .

## RECEIVER SECTION

**electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 6)**

| PARAMETER  | TEST CONDITIONS               | MIN              | TYP†             | MAX      | UNIT       |
|--|-------------------------------|------------------|------------------|----------|------------|
| $V_{OH}$ High-level output voltage                 | $I_{OH} = -1$ mA              | $V_{CC} - 0.6$ V | $V_{CC} - 0.1$ V |          | V          |
| $V_{OL}$ Low-level output voltage                  | $I_{OL} = 1.6$ mA             |                  |                  | 0.4      | V          |
| $V_{IT+}$ Positive-going input threshold voltage   | $V_{CC} = 3.3$ V              |                  | 1.5              | 2.4      | V          |
|  | $V_{CC} = 5$ V                |                  | 1.8              | 2.4      |            |
| $V_{IT-}$ Negative-going input threshold voltage   | $V_{CC} = 3.3$ V              | 0.6              | 1.2              |          | V          |
|  | $V_{CC} = 5$ V                | 0.8              | 1.5              |          |            |
| $V_{hys}$ Input hysteresis ( $V_{IT+} - V_{IT-}$ ) |                               |                  | 0.3              |          | V          |
| $I_{off}$ Output leakage current (except ROUT1B)   | $\overline{FORCEOFF} = 0$ V   |                  | $\pm 0.05$       | $\pm 10$ | $\mu$ A    |
| $r_i$ Input resistance                             | $V_I = \pm 3$ V to $\pm 25$ V | 3                | 5                | 7        | k $\Omega$ |

† All typical values are at  $V_{CC} = 3.3$  V or  $V_{CC} = 5$  V, and  $T_A = 25^\circ\text{C}$ .

NOTE 4: Testing supply conditions are C1–C4 = 0.1  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.15$  V; C1–C4 = 0.22  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.3$  V; and C1 = 0.047  $\mu$ F and C2–C4 = 0.33  $\mu$ F at  $V_{CC} = 5$  V  $\pm 0.5$  V.

**switching characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4)**

| PARAMETER   | TEST CONDITIONS                                     | MIN | TYP† | MAX | UNIT |
|---|---|-----|------|-----|------|
| $t_{PLH}$ Propagation delay time, low- to high-level output | $C_L = 150$ pF, See Figure 3                        |     | 150  |     | ns   |
| $t_{PHL}$ Propagation delay time, high- to low-level output |   |     | 150  |     | ns   |
| $t_{en}$ Output enable time                                 | $C_L = 150$ pF, $R_L = 3$ k $\Omega$ , See Figure 4 |     | 200  |     | ns   |
| $t_{dis}$ Output disable time                               |   |     | 200  |     | ns   |
| $t_{sk(p)}$ Pulse skew‡                                     | See Figure 3  |     | 50   |     | ns   |

† All typical values are at  $V_{CC} = 3.3$  V or  $V_{CC} = 5$  V, and  $T_A = 25^\circ\text{C}$ .

‡ Pulse skew is defined as  $|t_{PLH} - t_{PHL}|$  of each channel of the same device.

NOTE 4: Testing supply conditions are C1–C4 = 0.1  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.15$  V; C1–C4 = 0.22  $\mu$ F at  $V_{CC} = 3.3$  V  $\pm 0.3$  V; and C1 = 0.047  $\mu$ F and C2–C4 = 0.33  $\mu$ F at  $V_{CC} = 5$  V  $\pm 0.5$  V.

**MAX3238**  
**3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER**  
**WITH  $\pm 15$ -kV ESD (HBM) PROTECTION**  
 SLLS349J – JUNE 1999 – REVISED MARCH 2004

## AUTO-POWERDOWN PLUS SECTION

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Figure 5)

| PARAMETER               | TEST CONDITIONS   | MIN            | TYP† | MAX | UNIT |
|-------------------------|---|----------------|------|-----|------|
| $V_{T+}(\text{valid})$  | Receiver input threshold for INVALID high-level output voltage<br>$\text{FORCEON} = \text{GND}$ ,<br>$\text{FORCEOFF} = V_{CC}$ |                |      | 2.7 | V    |
| $V_{T-}(\text{valid})$  | Receiver input threshold for INVALID high-level output voltage<br>$\text{FORCEON} = \text{GND}$ ,<br>$\text{FORCEOFF} = V_{CC}$ | -2.7           |      |     | V    |
| $V_{T}(\text{invalid})$ | Receiver input threshold for INVALID low-level output voltage<br>$\text{FORCEON} = \text{GND}$ ,<br>$\text{FORCEOFF} = V_{CC}$  | -0.3           |      | 0.3 | V    |
| $V_{OH}$                | INVALID high-level output voltage<br>$I_{OH} = -1 \text{ mA}$ , $\text{FORCEON} = \text{GND}$ ,<br>$\text{FORCEOFF} = V_{CC}$   | $V_{CC} - 0.6$ |      |     | V    |
| $V_{OL}$                | INVALID low-level output voltage<br>$I_{OL} = 1.6 \text{ mA}$ , $\text{FORCEON} = \text{GND}$ ,<br>$\text{FORCEOFF} = V_{CC}$   |                |      | 0.4 | V    |


† All typical values are at  $V_{CC} = 3.3 \text{ V}$  or  $V_{CC} = 5 \text{ V}$ , and  $T_A = 25^\circ\text{C}$ .

switching characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Figure 5)

| PARAMETER            | MIN | TYP† | MAX | UNIT          |
|----------------------|-----|------|-----|---------------|
| $t_{\text{valid}}$   |     | 0.1  |     | $\mu\text{s}$ |
| $t_{\text{invalid}}$ |     | 50   |     | $\mu\text{s}$ |
| $t_{\text{en}}$      |     | 25   |     | $\mu\text{s}$ |
| $t_{\text{dis}}$     | 15  | 30   | 60  | s             |

† All typical values are at  $V_{CC} = 3.3 \text{ V}$  or  $V_{CC} = 5 \text{ V}$ , and  $T_A = 25^\circ\text{C}$ .



## PARAMETER MEASUREMENT INFORMATION



NOTES: A.  $C_L$  includes probe and jig capacitance.



B. The pulse generator has the following characteristics: PRR = 250 kbit/s,  $Z_O = 50 \Omega$ , 50% duty cycle,  $t_r \leq 10 \text{ ns}$ ,  $t_f \leq 10 \text{ ns}$ .

**Figure 1. Driver Slew Rate**

**PARAMETER MEASUREMENT INFORMATION**

**TEST CIRCUIT**

**VOLTAGE WAVEFORMS**



 NOTES: A.  $C_L$  includes probe and jig capacitance.

 B. The pulse generator has the following characteristics: PRR = 250 kbit/s,  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10$  ns,  $t_f \leq 10$  ns.

**Figure 2. Driver Pulse Skew**

**TEST CIRCUIT**

**VOLTAGE WAVEFORMS**

 NOTES: A.  $C_L$  includes probe and jig capacitance.

 B. The pulse generator has the following characteristics:  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10$  ns,  $t_f \leq 10$  ns.

**Figure 3. Receiver Propagation Delay Times**

**TEST CIRCUIT**

**VOLTAGE WAVEFORMS**

 NOTES: A.  $C_L$  includes probe and jig capacitance.

 B. The pulse generator has the following characteristics:  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10$  ns,  $t_f \leq 10$  ns.

 C.  $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .

 D.  $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .

**Figure 4. Receiver Enable and Disable Times**




# MAX3238

## 3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH $\pm 15$ -kV ESD (HBM) PROTECTION


SLLS349J – JUNE 1999 – REVISED MARCH 2004

### PARAMETER MEASUREMENT INFORMATION



TEST CIRCUIT

- NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics: PRR = 5 kbit/s,  $Z_O = 50 \Omega$ , 50% duty cycle,  $t_r \leq 10$  ns,  $t_f \leq 10$  ns.



† Auto-powerdown plus disables drivers and reduces supply current to 1  $\mu$ A.




Figure 5.  $\overline{\text{INVALID}}$  Propagation-Delay Times and Supply-Enabling Time


# MAX3238

## 3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER

### WITH $\pm 15$ -kV ESD (HBM) PROTECTION

SLLS349J – JUNE 1999 – REVISED MARCH 2004

#### APPLICATION INFORMATION



V<sub>CC</sub> vs CAPACITOR VALUES

| V <sub>CC</sub>    | C1            | C2, C3, and C4 |
|--------------------|---------------|----------------|
| 3.3 V $\pm$ 0.15 V | 0.1 $\mu$ F   | 0.1 $\mu$ F    |
| 3.3 V $\pm$ 0.3 V  | 0.22 $\mu$ F  | 0.22 $\mu$ F   |
| 5 V $\pm$ 0.5 V    | 0.047 $\mu$ F | 0.33 $\mu$ F   |
| 3 V to 5.5 V       | 0.22 $\mu$ F  | 1 $\mu$ F      |

† C3 can be connected to V<sub>CC</sub> or GND.

NOTES: A. Resistor values shown are nominal.

B. Nonpolarized ceramic capacitors are acceptable. If polarized tantalum or electrolytic capacitors are used, they should be connected as shown.

Figure 6. Typical Operating Circuit and Capacitor Values

**PACKAGING INFORMATION**

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/Ball Finish | MSL Peak Temp <sup>(3)</sup> |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| MAX3238CDB       | ACTIVE                | SSOP         | DB              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238CDBE4     | ACTIVE                | SSOP         | DB              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238CDBR      | ACTIVE                | SSOP         | DB              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238CDBRE4    | ACTIVE                | SSOP         | DB              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238CDBRG4    | ACTIVE                | SSOP         | DB              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-2-260C-1YEAR           |
| MAX3238CPW       | ACTIVE                | TSSOP        | PW              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238CPWR      | ACTIVE                | TSSOP        | PW              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IDB       | ACTIVE                | SSOP         | DB              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IDBE4     | ACTIVE                | SSOP         | DB              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IDBR      | ACTIVE                | SSOP         | DB              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IDBRE4    | ACTIVE                | SSOP         | DB              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IPW       | ACTIVE                | TSSOP        | PW              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IPWE4     | ACTIVE                | TSSOP        | PW              | 28   | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IPWR      | ACTIVE                | TSSOP        | PW              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |
| MAX3238IPWRE4    | ACTIVE                | TSSOP        | PW              | 28   | 2000        | Green (RoHS & no Sb/Br) | CU NIPDAU        | Level-1-260C-UNLIM           |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the

accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## DB (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE

28 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-150

## PW (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE PACKAGE

14 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-153

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| <b>Products</b>  |  | <b>Applications</b> |  |
|------------------|--|---------------------|--|
| Amplifiers       | <a href="http://amplifier.ti.com">amplifier.ti.com</a>             | Audio               | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                   |
| Data Converters  | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>     | Automotive          | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>         |
| DSP              | <a href="http://dsp.ti.com">dsp.ti.com</a>                         | Broadband           | <a href="http://www.ti.com/broadband">www.ti.com/broadband</a>           |
| Interface        | <a href="http://interface.ti.com">interface.ti.com</a>             | Digital Control     | <a href="http://www.ti.com/digitalcontrol">www.ti.com/digitalcontrol</a> |
| Logic            | <a href="http://logic.ti.com">logic.ti.com</a>                     | Military            | <a href="http://www.ti.com/military">www.ti.com/military</a>             |
| Power Mgmt       | <a href="http://power.ti.com">power.ti.com</a>                     | Optical Networking  | <a href="http://www.ti.com/opticalnetwork">www.ti.com/opticalnetwork</a> |
| Microcontrollers | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a> | Security            | <a href="http://www.ti.com/security">www.ti.com/security</a>             |
|                  |  | Telephony           | <a href="http://www.ti.com/telephony">www.ti.com/telephony</a>           |
|                  |  | Video & Imaging     | <a href="http://www.ti.com/video">www.ti.com/video</a>                   |
|                  |  | Wireless            | <a href="http://www.ti.com/wireless">www.ti.com/wireless</a>             |

Mailing Address: Texas Instruments  
Post Office Box 655303 Dallas, Texas 75265

Copyright © 2005, Texas Instruments Incorporated