

ZXMN6A09K


60V N-CHANNEL ENHANCEMENT MODE MOSFET IN D-PAK

SUMMARY

$V_{(BR)DSS} = 60V$; $R_{DS(on)} = 0.045\Omega$; $I_D = 11.2A$

DESCRIPTION

This new generation of Trench MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage power management applications.




DPAK

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- D-Pak (TO-252) package

APPLICATIONS

- DC-DC Converters
- Power Management functions
- Disconnect switches
- Motor control




ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXMN6A09KTC	13"	16mm	2500 units

DEVICE MARKING

- ZXMN
6A09K

PINOUT



TOP VIEW

ZXMN6A09K

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-source voltage	V_{DSS}	60	V
Gate-source voltage	V_{GS}	± 20	V
Continuous drain current @ $V_{GS}=10V$; $T_A=25^\circ C$ ^(b) @ $V_{GS}=10V$; $T_A=70^\circ C$ ^(b) @ $V_{GS}=10V$; $T_A=25^\circ C$ ^(a)	I_D	11.2 9.0 7.3	A
Pulsed drain current ^(c)	I_{DM}	40	A
Continuous source current (body diode) ^(b)	I_S	10.8	A
Pulsed source current (body diode) ^(c)	I_{SM}	40	A
Power dissipation at $T_A=25^\circ C$ ^(a) Linear derating factor	P_D	4.3 34.4	W mW/ $^\circ C$
Power dissipation at $T_A=25^\circ C$ ^(b) Linear derating factor	P_D	10.1 80.8	W mW/ $^\circ C$
Power dissipation at $T_A=25^\circ C$ ^(d) Linear derating factor	P_D	2.15 17.2	W mW/ $^\circ C$
Operating and storage temperature range	T_J, T_{stg}	-55 to +150	$^\circ C$

THERMAL RESISTANCE


PARAMETER	SYMBOL	VALUE	UNIT
Junction to ambient ^(a)	$R_{\theta JA}$	29	$^\circ C/W$
Junction to ambient ^(b)	$R_{\theta JA}$	12.3	$^\circ C/W$
Junction to ambient ^(d)	$R_{\theta JA}$	58	$^\circ C/W$

NOTES

- (a) For a device surface mounted on 50mm x 50mm x 1.6mm FR4 PCB with high coverage of single sided 2oz copper, in still air conditions.
 (b) For a device surface mounted on FR4 PCB measured at $t \leq 10$ sec.
 (c) Repetitive rating 50mm x 50mm x 1.6mm FR4 PCB, $D=0.02$ pulse width=300 μs - pulse width limited by maximum junction temperature.
 (d) For a device surface mounted on 50mm x 50mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions.

ZXMN6A09K

TYPICAL CHARACTERISTICS



ZXMN6A09K

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
STATIC						
Drain-source breakdown voltage	V _{(BR)DSS}	60			V	I _D = 250μA, V _{GS} =0V
Zero gate voltage drain current	I _{DSS}			1	μA	V _{DS} = 60V, V _{GS} =0V
Gate-body leakage	I _{GSS}			100	nA	V _{GS} =±20V, V _{DS} =0V
Gate-source threshold voltage	V _{GS(th)}	1.0			V	I _D = 250μA, V _{DS} =V _{GS}
Static drain-source on-state resistance ⁽¹⁾	R _{DS(on)}			0.045	Ω	V _{GS} = 10V, I _D = 7.3A
				0.070	Ω	V _{GS} = 4.5V, I _D = 5.6A
Forward transconductance ⁽¹⁾ ⁽³⁾	g _{fs}		15		S	V _{DS} = 15V, I _D = 7.3A
DYNAMIC ⁽³⁾						
Input capacitance	C _{iss}		1426		pF	V _{DS} = 30V, V _{GS} =0V f=1MHz
Output capacitance	C _{oss}		134		pF	
Reverse transfer capacitance	C _{rss}		64		pF	
SWITCHING ⁽²⁾ ⁽³⁾						
Turn-on-delay time	t _{d(on)}		4.8		ns	V _{DD} = 30V, I _D = 1A R _G ≅6.0Ω, V _{GS} = 10V (refer to test circuit)
Rise time	t _r		4.6		ns	
Turn-off delay time	t _{d(off)}		32.5		ns	
Fall time	t _f		14.5		ns	
Total gate charge	Q _g		15		nC	V _{DS} = 30V, V _{GS} = 4.5V I _D = 5.6A
Total gate charge	Q _g		29		nC	V _{DS} = 30V, V _{GS} = 10V I _D = 7.3A
Gate-source charge	Q _{gs}		7.0		nC	
Gate drain charge	Q _{gd}		4.7		nC	
SOURCE-DRAIN DIODE						
Diode forward voltage ⁽¹⁾	V _{SD}		0.85	0.95	V	T _j =25°C, I _S = 6.6A, V _{GS} =0V
Reverse recovery time ⁽³⁾	t _{rr}		25.6		ns	T _j =25°C, I _S = 3A, di/dt=100A/μs
Reverse recovery charge ⁽³⁾	Q _{rr}		26.0		nC	

NOTES


(1) Measured under pulsed conditions. Pulse width $\leq 300\mu\text{s}$; duty cycle $\leq 2\%$.

(2) Switching characteristics are independent of operating junction temperature.

(3) For design aid only, not subject to production testing.


ZXMN6A09K

TYPICAL CHARACTERISTICS




ZXMN6A09K

TYPICAL CHARACTERISTICS



ZXMN6A09K

PACKAGE OUTLINE



Controlling dimensions are in millimeters. Approximate conversions are given in inches

PACKAGE DIMENSIONS

DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	2.18	2.38	0.086	0.094	e	2.30 BSC		0.090 BSC	
A1	—	0.127	—	0.005	H	9.40	10.41	0.370	0.410
b	0.635	0.89	0.025	0.035	L	1.40	1.78	0.055	0.070
b2	0.762	1.114	0.030	0.045	L1	2.74 REF		0.108 REF	
b3	5.20	5.46	0.205	0.215	L2	0.051 BSC		0.020 BSC	
c	0.457	0.609	0.018	0.024	L3	0.89	1.27	0.035	0.050
c2	0.457	0.584	0.018	0.023	L4	0.635	1.01	0.025	0.040
D	5.97	6.22	0.235	0.245	L5	1.14	1.52	0.045	0.060
D1	5.20	—	0.205	—	Θ1°	0°	10°	0°	10°
E	6.35	6.73	0.250	0.265	Θ°	0°	15°	0°	15°
E1	4.32	—	0.170	—	—	—	—	—	—

© Zetex plc 2003

Corporate Headquarters

Zetex plc
Fields New Road
Chadderton
Oldham, OL9 8NP
United Kingdom
Telephone (44) 161 622 4444
Fax: (44) 161 622 4446
hq@zetex.com

Regional sales offices

Europe
Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49
europe.sales@zetex.com

Americas
Zetex Inc
700 Veterans Memorial Hwy
Hauppauge, NY 11788
USA
Telephone: (1) 631 360 2222
Fax: (1) 631 360 8222
usa.sales@zetex.com

Asia Pacific
Zetex (Asia) Ltd
3701-04 Metroplaza Tower 1
Hing Fong Road, Kwai Fong
Hong Kong
Telephone: (852) 26100 611
Fax: (852) 24250 494
asia.sales@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com

ISSUE 3 - JANUARY 2004

