




Standard Metallized Polyester Capacitors



(All dimensions in millimeters)

1313DFR

Epoxy Dipped (Radial Leads)

Lead Specs. - Tinned Copperweld

L	S	DIA.
10.0	7.5	0.6
12.5	10.0	0.6
18.0	15.0	0.8
26.0	22.5	0.8
31.0	27.5	0.8
44.0	38.0	0.8

DIMENSIONS and RATINGS

Cap.	1313DFR-3 100 VDC			1313DFR-3 160 VDC			1313DFR-3 250 VDC			1313DFR-3 400 VDC			1313DFR-3 630 VDC			1313DFR-3 1000 VDC			
μF	T	H	L	T	H	L	T	H	L	T	H	L	T	H	L	T	H	L	
.001	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	12.5	
.0012	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.5	12.5	
.0015	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	9.0	12.5	
.0022	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	
.0027	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	
.0039	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	
.0047	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.5	12.5	
.0056	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	9.0	10.0	4.5	9.5	12.5	
.0068	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	9.0	12.5	5.0	10.0	12.5	
.0082	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	5.0	10.0	12.5	
.01	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	5.5	11.0	12.5	
.012	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.5	10.0	5.0	10.0	12.5	6.0	12.0	12.5	
.015	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	10.0	5.5	11.0	12.5	5.0	10.0	18.0	
.018	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.0	9.0	12.5	6.0	11.5	12.5	5.5	11.0	18.0	
.022	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	6.0	12.0	12.5	6.0	12.0	18.0	
.027	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.5	12.5	5.0	10.0	18.0	6.5	12.5	18.0	
.033	4.0	8.0	10.0	4.0	8.0	10.0	4.0	8.5	10.0	5.0	10.0	12.5	5.5	11.0	18.0	7.0	13.0	18.0	
.039	4.0	8.0	10.0	4.0	8.0	10.0	4.0	9.0	10.0	6.0	11.0	12.5	6.0	11.5	18.0	7.5	13.5	18.0	
.047	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	10.0	6.5	12.0	12.5	6.0	12.0	18.0	7.0	13.0	26.0	
.056	4.0	8.0	10.0	4.0	8.0	10.0	4.0	9.0	12.5	5.0	10.0	18.0	6.5	12.5	18.0	8.0	15.0	26.0	
.068	4.0	8.0	10.0	4.0	8.0	10.0	4.5	9.0	12.5	5.5	11.0	18.0	7.0	13.0	18.0	8.5	16.0	26.0	
.082	4.0	8.0	10.0	4.0	8.5	10.0	4.5	9.5	12.5	5.5	11.5	18.0	7.5	13.5	18.0	9.0	16.5	26.0	
.1	4.0	8.0	10.0	4.0	9.0	10.0	5.0	10.0	12.5	6.5	12.5	18.0	7.0	13.0	26.0	9.5	18.0	26.0	
.12	4.0	8.0	10.0	5.5	11.0	12.5	5.5	11.0	12.5	7.0	13.0	18.0	8.0	14.0	26.0	9.0	16.5	31.0	
.15	4.0	8.0	10.0	4.5	9.0	12.5	6.5	12.0	12.5	7.5	13.5	18.0	8.5	15.0	26.0	10.0	19.0	31.0	
.18	4.0	8.5	10.0	4.5	9.5	12.5	5.0	10.0	18.0	6.5	12.5	26.0	9.0	17.0	26.0	10.5	20.0	31.0	
.22	4.0	8.5	10.0	5.0	10.0	12.5	5.5	11.0	18.0	7.0	13.0	26.0	10.0	19.0	26.0	11.5	21.0	31.0	
.27	4.0	8.5	10.0	5.5	11.0	12.5	6.0	12.0	18.0	8.0	14.5	26.0	9.5	17.0	31.0	12.5	23.0	31.0	
.33	4.0	9.0	10.0	6.0	12.0	12.5	6.5	12.5	18.0	8.5	16.0	26.0	10.0	19.0	31.0	13.5	25.0	31.0	
.39	4.0	9.0	12.5	5.0	10.0	18.0	7.0	13.0	18.0	9.0	17.0	26.0	11.0	20.5	31.0	14.5	27.0	31.0	
.47	4.5	9.5	12.5	5.5	11.0	18.0	7.5	13.5	18.0	9.5	18.0	26.0	12.0	22.0	31.0	16.5	30.0	31.0	
.56	5.0	10.0	12.5	6.0	12.0	18.0	7.0	13.0	26.0	10.0	19.0	31.0	13.0	23.0	31.0	15.0	27.0	44.0	
.68	5.5	10.5	12.5	7.0	13.0	18.0	8.0	14.0	26.0	10.5	20.0	31.0	13.5	25.0	31.0	16.5	30.0	44.0	
.82	6.0	11.5	12.5	7.5	13.5	18.0	8.5	15.5	26.0	11.5	22.0	31.0	14.5	27.0	31.0	17.0	32.0	44.0	
1.0	6.5	12.0	12.5	8.0	14.0	18.0	9.0	16.5	26.0	13.0	24.0	31.0	16.5	30.0	31.0	20.0	35.0	44.0	
1.2	6.0	12.0	18.0	7.5	13.5	26.0	9.5	17.0	26.0	14.0	25.5	31.0	15.0	27.0	44.0				
1.5	6.5	12.5	18.0	8.0	14.0	26.0	10.0	19.0	26.0	15.5	27.0	31.0	16.5	30.0	44.0				
1.8	7.0	13.0	18.0	8.5	15.5	26.0	9.5	17.0	31.0	16.5	30.3	31.0	18.0	33.0	44.0				
2.2	7.5	13.5	18.0	9.0	17.0	26.0	10.0	19.0	31.0	17.0	32.0	31.0	20.5	36.0	44.0				
2.7	7.0	13.0	26.0	9.5	18.0	26.0	11.5	21.0	31.0	15.5	28.0	44.0							
3.3	7.5	13.5	26.0	10.5	20.0	26.0	15.0	26.0	31.0	17.0	32.0	44.0							
3.9	8.0	14.5	26.0	10.0	19.0	31.0	13.5	25.0	31.0	18.0	33.0	44.0							
4.7	8.5	16.0	26.0	11.0	21.0	31.0	15.0	26.0	31.0	20.0	35.0	44.0							
5.6	9.0	17.0	26.0	12.0	22.0	31.0	14.5	25.0	44.0										
6.8	9.5	18.0	26.0	13.0	24.0	31.0	16.0	30.0	44.0										

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.

ELECTRONIC FILM CAPACITORS, INC.

Reidville Industrial Park * 41 Interstate Lane * WATERBURY, CONNECTICUT 06705

Phone (203) 755-5629 * E-Mail: efc@filmcapacitors.com * FAX (203) 755-0659