

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER


ELM304X Series
ELM306X Series
ELM308X Series

Features:

- ELM304X V_{DRM} of 400V, ELM306X V_{DRM} of 600V and ELM308X V_{DRM} of 800V
- High isolation voltage between input and output (Viso=3750 V rms)
- Zero voltage crossing
- Pb free and RoHS compliant.
- UL approved (No. E214129)
- VDE approved (No.40028116)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved



Schematic



Description

The ELM304X, ELM306X and ELM308X devices consist of a GaAs infrared emitting diode optically coupled to a monolithic silicon detector performing the function of a zero voltage crossing bilateral triac driver.

They are designed for use with a discrete power triac in the interface of logic systems to equipment powered from 110 to 240 VAC lines, such as solid-state relays, industrial controls, motors, solenoids and consumer appliances, etc.

Pin Configuration

1. Anode
2. Cathode
3. Terminal
4. Terminal

Applications

- Solenoid/valve controls
- Light controls
- Static power switch
- AC motor drivers
- E.M. contactors
- Temperature controls
- AC Motor starters
- Solid state relays



LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Absolute Maximum Ratings (T_a=25°C)

Parameter			Symbol	Rating	Unit
Input	Forward current		I _F	60	mA
	Peak forward current (1us pulse, 300pps)		I _{F(PK)}	1	A
	Reverse voltage		V _R	6	V
	Power dissipation		P _D	100	mW
Output	Off-state Output Terminal Voltage	M304X	V _{DRM}	400	V
		M306X		600	
		M308X		800	
	On state RMS Current		I _{T(RMS)}	70	mA(RMS)
	Power dissipation		P _D	300	mW
	Isolation voltage ^{*1}			V _{iso}	3750
Operating temperature			T _{opr}	-40~+110	°C
Storage temperature			T _{stg}	-55~+150	°C
Soldering temperature ^{*2}			T _{sol}	260	°C

Notes

*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 & 3 are shorted together, and pins 4, 5 & 6 are shorted together.

*2 For 10 seconds.



LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Electrical Characteristics ($T_a=25^{\circ}\text{C}$ unless specified otherwise)

Input

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Forward voltage	V_F	-	-	1.5	V	$I_F = 30\text{mA}$
Reverse Leakage current	I_R	-	-	10	μA	$V_R = 6\text{V}$

Output

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Peak Blocking Current	I_{DRM1}	-	-	100	nA	$V_{\text{DRM}} = \text{Rated } V_{\text{DRM}}$ $I_F = 0\text{mA}$
Peak On-state Voltage	V_{TM}	-	-	3	V	$I_{\text{TM}}=100\text{mA peak}$
Critical Rate of Rise off-state Voltage	dv/dt	1000	-	-	V/ μs	
Inhibit Voltage (MT1-MT2 voltage above which device will not trigger)	V_{INH}	-	-	20	V	$I_F = \text{Rated } I_{\text{FT}}$
Leakage in Inhibited State	I_{DRM2}	-	-	1000	μA	$I_F = \text{Rated } I_{\text{FT}}$, $V_{\text{DRM}} = \text{Rated } V_{\text{DRM}}$, off state

Transfer Characteristics

Parameter		Symbol	Min.	Typ.*	Max.	Unit	Condition
LED Trigger Current	3042	I _{FT}	-	-	10	mA	Main terminal Voltage=3V
	3062						
	3082						
	3043		-	-	5		
	3063						
	3083						
3044	-	-	3				
3064							
3084							
Holding Current		I _H	-	280	-	μA	

* Typical values at $T_a = 25^{\circ}\text{C}$









LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Typical Performance Curves





LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Figure 7. Off-State Output Terminal Voltage
vs. Ambient Temperature




Figure 8. Leakage in Inhibit State
vs. Ambient Temperature






Figure 9. Inhibit Voltage vs. Ambient Temperature



4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Figure 10. Static dv/dt Test Circuit & Waveform



Measurement Method

The high voltage pulse is set to the required V_{PEAK} value and applied to the D.U.T. output side through the RC circuit above. LED current is not applied. The waveform V_T is monitored using a x100 scope probe. By varying R_{TEST} , the dv/dt (slope) is increased, until the D.U.T. is observed to trigger (waveform collapses). The dv/dt is then decreased until the D.U.T. stops triggering. At this point, τ_{RC} is recorded and the dv/dt calculated.

$$dv/dt = \frac{0.632 \times V_{PEAK}}{\tau_{RC}}$$

For example, $V_{PEAK} = 600V$ for EL306X series. The dv/dt value is calculated as follows:

$$dv/dt = \frac{0.63 \times 600}{\tau_{RC}} = \frac{378}{\tau_{RC}}$$



LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Order Information

Part Number

ELM304X(Z)-V
or **ELM306X(Z)-V**
or **ELM308X(Z)-V**

Note

X = Part No. (2 for $I_{FT}=10mA$, 3 for $I_{FT}=5mA$, 4 for $I_{FT}=3mA$)

Z = Tape and reel option (TA, TB or none).

V = VDE safety approved optional


Option	Description	Packing quantity
None	Standard	100 units per tube
None	Standard + VDE safety optional	100 units per tube
(TA)	TA tape & reel option	3000 units per reel
(TB)	TB tape & reel option	3000 units per reel
(TA)-V	TA tape & reel option + VDE safety optional	3000 units per reel
(TB)-V	TB tape & reel option + VDE safety optional	3000 units per reel

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER


ELM304X Series
ELM306X Series
ELM308X Series

Package Drawings

(Dimensions in mm)



Recommended pad layout for surface mount leadform





LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Device Marking



Notes


EL	denotes Everlight
M3063	denotes Device Number
Y	denotes 1 digit Year code
WW	denotes 2 digit Week code
V	denotes VDE safety (optional)

EVERLIGHT


4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

**ELM304X Series
ELM306X Series
ELM308X Series**

Tape & Reel Packing Specifications



Tape dimensions



Dimension No.	A	B	D0	D1	E	F
Dimension (mm)	4.4 ± 0.1	7.4 ± 0.1	1.5 + 0.1/-0	1.5 ± 0.1	1.7 5± 0.1	7.5 ± 0.1

Dimension No.	P0	P1	P2	t	W	K
Dimension (mm)	4.0 ± 0.15	8.0 ± 0.1	2.0 ± 0.1	0.25 ± 0.03	16.0 ± 0.2	2.4 ± 0.1




LIGHTING FOREVER

4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

Solder Reflow Temperature Profile



4 PIN SOP ZERO CROSS TRIAC PHOTOCOUPLER

ELM304X Series
ELM306X Series
ELM308X Series

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.

EVERLIGHT