

GP1S25

Side Lead Type Ultra-compact Photointerrupter

■ Features


1. Side lead ultra-compact transmission type
2. Conforming to solder reflow
 - Pre-heat : 160 °C, MAX. 120 sec
 - Reflow : (200 °C, MAX. 60 sec)
240 °C, MAX. 10 sec)
3. Slit : 0.3 mm
4. Gap : 1.6 mm

■ Applications

1. CD-ROM drives
2. FDDs

■ Outline Dimensions

(Unit : mm)



■ Absolute Maximum Ratings

(Ta=25°C)

	Parameter	Symbol	Rating	Unit
Input	Forward current	I _F	50	mA
	Reverse voltage	V _R	6	V
	Power dissipation	P	75	mW
Output	Collector-emitter voltage	V _{CEO}	35	V
	Emitter-collector voltage	V _{ECO}	6	V
	Collector current	I _C	20	mA
	Collector power dissipation	P _C	75	mW
	Total power dissipation	P _{tot}	100	mW
	Operating temperature	T _{opr}	- 25 to + 85	°C
	Storage temperature	T _{stg}	- 40 to + 100	°C
	* ¹ Soldering temperature	T _{sol}	260	°C

*1 Soldering time : For 3 seconds (hand soldering)

■ Electro-optical Characteristics

(Ta=25 °C)

Parameter		Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage	V _F	I _F = 20mA	-	1.2	1.4	V
	Reverse current	I _R	V _R = 3V	-	-	10	μA
Output	Dark current	I _{CEO}	V _{CE} = 20V	-	-	100	nA
Transfer characteristics	Collector current	I _C	V _{CE} = 5V, I _F = 5mA	50	-	300	μA
	Collector-emitter saturation voltage	V _{CE(sat)}	I _F = 10mA, I _C = 50 μA	-	-	0.4	V
Response time	Rise time	t _r	V _{CE} = 5V, I _C = 100 μ A	-	35	100	μs
	Fall time	t _f	R _L = 1 000 Ω	-	35	100	μs

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Power dissipation vs. Ambient Temperature




Fig. 3 Forward Current vs. Forward Voltage




Fig. 4 Collector Current vs. Forward Current




Fig. 5 Collector Current vs. Collector-emitter Voltage




Fig. 7 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig. 9 Response Time vs. Load Resistance




Fig. 6 Relative Collector Current vs. Ambient Temperature





Fig. 8 Dark Current vs. Ambient Temperature



Test Circuit for Response Time






Fig. 10 Detecting Position Characteristics (1)**Fig. 11 Detecting Position Characteristics (2)**

- Please refer to the chapter "Precautions for Use".