

## 74F189

### 64-Bit Random Access Memory with 3-STATE Outputs

#### General Description

The F189 is a high-speed 64-bit RAM organized as a 16-word by 4-bit array. Address inputs are buffered to minimize loading and are fully decoded on-chip. The outputs are 3-STATE and are in the high impedance state whenever the Chip Select ( $\overline{CS}$ ) input is HIGH. The outputs are active only in the Read mode and the output data is the complement of the stored data.

#### Features


- 3-STATE outputs for data bus applications
- Buffered inputs minimize loading
- Address decoding on-chip
- Diode clamped inputs minimize ringing

#### Ordering Code:


| Order Number | Package Number | Package Description                                                        |
|--------------|----------------|----------------------------------------------------------------------------|
| 74F189SC     | M16B           | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide |
| 74F189SJ     | M16D           | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide              |
| 74F189PC     | N16E           | 16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide     |

Devices also available in Tape and Reel. Specify by appending suffix "X" to the ordering code.

#### Logic Symbols



#### Connection Diagram




| Pin Names                                         | Description                     | U.L.<br>HIGH/LOW | Input I <sub>IH</sub> /I <sub>IL</sub><br>Output I <sub>OH</sub> /I <sub>OL</sub> |
|---------------------------------------------------|---------------------------------|------------------|-----------------------------------------------------------------------------------|
| A <sub>0</sub> –A <sub>3</sub>                    | Address Inputs                  | 1.0/1.0          | 20 μA/–0.6 mA                                                                     |
| $\overline{\text{CS}}$                            | Chip Select Input (Active LOW)  | 1.0/1.0          | 20 μA/–1.2 mA                                                                     |
| $\overline{\text{WE}}$                            | Write Enable Input (Active LOW) | 1.0/1.0          | 20 μA/–0.6 mA                                                                     |
| D <sub>0</sub> –D <sub>3</sub>                    | Data Inputs                     | 1.0/1.0          | 20 μA/–0.6 mA                                                                     |
| $\overline{\text{O}}_0$ – $\overline{\text{O}}_3$ | Inverted Data Outputs           | 150/40 (33.3)    | –3.0 mA/24 mA (20 mA)                                                             |

## Function Table

| Inputs    |           | Operation | Condition of Outputs      |
|-----------|-----------|-----------|---------------------------|
| <u>CS</u> | <u>WE</u> |           |                           |
| L         | L         | Write     | High Impedance            |
| L         | H         | Read      | Complement of Stored Data |
| H         | X         | Inhibit   | High Impedance            |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial

### Block Diagram



**Absolute Maximum Ratings**(Note 1)

|                                             |                   |
|---------------------------------------------|-------------------|
| Storage Temperature                         | –65°C to +150°C   |
| Ambient Temperature under Bias              | –55°C to +125°C   |
| Junction Temperature under Bias             | –55°C to +175°C   |
| V <sub>CC</sub> Pin Potential to Ground Pin | –0.5V to +7.0V    |
| Input Voltage (Note 2)                      | –0.5V to +7.0V    |
| Input Current (Note 2)                      | –30 mA to +5.0 mA |

## Voltage Applied to Output

in HIGH State (with V<sub>CC</sub> = 0V)Standard Output –0.5V to V<sub>CC</sub>

3-STATE Output –0.5V to +5.5V

## Current Applied to Output

in LOW State (Max)

**Recommended Operating Conditions**

|                              |                |
|------------------------------|----------------|
| Free Air Ambient Temperature | 0°C to +70°C   |
| Supply Voltage               | +4.5V to +5.5V |

**Note 1:** Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.


**Note 2:** Either voltage limit or current limit is sufficient to protect inputs.

**DC Electrical Characteristics**


| Symbol           | Parameter                         | Min                 | Typ  | Max  | Units | V <sub>CC</sub> | Conditions                                              |
|------------------|-----------------------------------|---------------------|------|------|-------|-----------------|---------------------------------------------------------|
| V <sub>IH</sub>  | Input HIGH Voltage                | 2.0                 |      |      | V     |                 | Recognized as a HIGH Signal                             |
| V <sub>IL</sub>  | Input LOW Voltage                 |                     |      | 0.8  | V     |                 | Recognized as a LOW Signal                              |
| V <sub>CD</sub>  | Input Clamp Diode Voltage         |                     |      | –1.2 | V     | Min             | I <sub>IN</sub> = –18 mA                                |
| V <sub>OH</sub>  | Output HIGH Voltage               | 10% V <sub>CC</sub> | 2.5  |      | V     | Min             | I <sub>OH</sub> = –1 mA                                 |
|                  |                                   | 10% V <sub>CC</sub> | 2.4  |      |       |                 | I <sub>OH</sub> = –3 mA                                 |
|                  |                                   | 5% V <sub>CC</sub>  | 2.7  |      |       |                 | I <sub>OH</sub> = –1 mA                                 |
|                  |                                   | 5% V <sub>CC</sub>  | 2.7  |      |       |                 | I <sub>OH</sub> = –3 mA                                 |
| V <sub>OL</sub>  | Output LOW Voltage                |                     |      | 0.5  | V     | Min             | I <sub>OL</sub> = 24 mA                                 |
| I <sub>IH</sub>  | Input HIGH Current                |                     |      | 5.0  | μA    | Max             | V <sub>IN</sub> = 2.7V                                  |
| I <sub>BVI</sub> | Input HIGH Current Breakdown Test |                     |      | 7.0  | μA    | Max             | V <sub>IN</sub> = 7.0V                                  |
| I <sub>CEX</sub> | Output HIGH Leakage Current       |                     |      | 50   | μA    | Max             | V <sub>OUT</sub> = V <sub>CC</sub>                      |
| V <sub>ID</sub>  | Input Leakage Test                | 4.75                |      |      | V     | 0.0             | I <sub>ID</sub> = 1.9 μA<br>All Other Pins Grounded     |
| I <sub>OD</sub>  | Output Leakage Circuit Current    |                     |      | 3.75 | μA    | 0.0             | V <sub>IOD</sub> = 150 mV<br>All Other Pins Grounded    |
| I <sub>IL</sub>  | Input LOW Current                 |                     | –0.6 |      | mA    | Max             | V <sub>IN</sub> = 0.5V (except $\overline{\text{CS}}$ ) |
|                  |                                   |                     | –1.2 |      |       |                 | V <sub>IN</sub> = 0.5V ( $\overline{\text{CS}}$ )       |
| I <sub>OZH</sub> | Output Leakage Current            |                     |      | 50   | μA    | Max             | V <sub>OUT</sub> = 2.7V                                 |
| I <sub>OZL</sub> | Output Leakage Current            |                     |      | –50  | μA    | Max             | V <sub>OUT</sub> = 0.5V                                 |
| I <sub>OS</sub>  | Output Short-Circuit Current      | –60                 | –150 |      | mA    | Max             | V <sub>OUT</sub> = 0V                                   |
| I <sub>ZZ</sub>  | Bus Drainage Test                 |                     |      | 500  | μA    | 0.0V            | V <sub>OUT</sub> = 5.25V                                |
| I <sub>CCZ</sub> | Power Supply Current              |                     | 37   | 55   | mA    | Max             | V <sub>O</sub> = HIGH Z                                 |

| AC Electrical Characteristics |                                                       |                                                                             |      |                                                             |                                                                                       |                                                          |                                                                                    |       |       |
|-------------------------------|-------------------------------------------------------|-----------------------------------------------------------------------------|------|-------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------------------------|------------------------------------------------------------------------------------|-------|-------|
| Symbol                        | Parameter                                             | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |      |                                                             | T <sub>A</sub> = -55°C to +125°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |                                                          | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |       | Units |
|                               |                                                       | Min                                                                         | Typ  | Max                                                         | Min                                                                                   | Max                                                      | Min                                                                                | Max   |       |
| t <sub>PLH</sub>              | Access Time, HIGH or LOW                              | 10.0                                                                        | 18.5 | 26.0                                                        | 9.0                                                                                   | 32.0                                                     | 10.0                                                                               | 27.0  | ns    |
| t <sub>PHL</sub>              | A <sub>n</sub> to $\overline{O_n}$                    | 8.0                                                                         | 13.5 | 19.0                                                        | 8.0                                                                                   | 23.0                                                     | 8.0                                                                                | 20.0  |       |
| t <sub>PZH</sub>              | Access Time, HIGH or LOW                              | 3.5                                                                         | 6.0  | 8.5                                                         | 3.5                                                                                   | 10.5                                                     | 3.5                                                                                | 9.5   | ns    |
| t <sub>PZL</sub>              | $\overline{CS}$ to $\overline{O_n}$                   | 5.0                                                                         | 9.0  | 13.0                                                        | 5.0                                                                                   | 15.0                                                     | 5.0                                                                                | 14.0  |       |
| t <sub>PHZ</sub>              | Disable Time, HIGH or LOW                             | 2.0                                                                         | 4.0  | 6.0                                                         | 2.0                                                                                   | 8.0                                                      | 2.0                                                                                | 7.0   | ns    |
| t <sub>PLZ</sub>              | $\overline{CS}$ to $\overline{O_n}$                   | 3.0                                                                         | 5.5  | 8.0                                                         | 2.5                                                                                   | 10.0                                                     | 3.0                                                                                | 9.0   |       |
| t <sub>PZH</sub>              | Write Recovery Time,                                  | 6.5                                                                         | 15.0 | 28.0                                                        | 6.5                                                                                   | 37.5                                                     | 6.5                                                                                | 29.0  | ns    |
| t <sub>PZL</sub>              | HIGH or LOW $\overline{WE}$ to $\overline{O_n}$       | 6.5                                                                         | 11.0 | 15.5                                                        | 6.5                                                                                   | 17.5                                                     | 6.5                                                                                | 16.5  |       |
| t <sub>PHZ</sub>              | Disable Time, HIGH or LOW                             | 4.0                                                                         | 7.0  | 10.0                                                        | 3.5                                                                                   | 12.0                                                     | 4.0                                                                                | 11.0  | ns    |
| t <sub>PLZ</sub>              | $\overline{WE}$ to $\overline{O_n}$                   | 5.0                                                                         | 9.0  | 13.0                                                        | 5.0                                                                                   | 15.0                                                     | 5.0                                                                                | 14.0  |       |
| AC Operating Requirements     |                                                       |                                                                             |      |                                                             |                                                                                       |                                                          |                                                                                    |       |       |
| Symbol                        | Parameter                                             | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V                           |      | T <sub>A</sub> = -55°C to +125°C<br>V <sub>CC</sub> = +5.0V |                                                                                       | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V |                                                                                    | Units |       |
|                               |                                                       | Min                                                                         | Max  | Min                                                         | Max                                                                                   | Min                                                      | Max                                                                                |       |       |
| t <sub>S</sub> (H)            | Setup Time, HIGH or LOW                               | 0                                                                           |      | 0                                                           |                                                                                       | 0                                                        |                                                                                    | ns    |       |
| t <sub>S</sub> (L)            | A <sub>n</sub> to $\overline{WE}$                     | 0                                                                           |      | 0                                                           |                                                                                       | 0                                                        |                                                                                    |       |       |
| t <sub>H</sub> (H)            | Hold Time, HIGH or LOW                                | 2.0                                                                         |      | 2.0                                                         |                                                                                       | 2.0                                                      |                                                                                    |       |       |
| t <sub>H</sub> (L)            | A <sub>n</sub> to $\overline{WE}$                     | 2.0                                                                         |      | 2.0                                                         |                                                                                       | 2.0                                                      |                                                                                    |       |       |
| t <sub>S</sub> (H)            | Setup Time, HIGH or LOW                               | 10.0                                                                        |      | 11.0                                                        |                                                                                       | 10.0                                                     |                                                                                    | ns    |       |
| t <sub>S</sub> (L)            | D <sub>n</sub> to $\overline{WE}$                     | 10.0                                                                        |      | 11.0                                                        |                                                                                       | 10.0                                                     |                                                                                    |       |       |
| t <sub>H</sub> (H)            | Hold Time, HIGH or LOW                                | 0                                                                           |      | 2.0                                                         |                                                                                       | 0                                                        |                                                                                    |       |       |
| t <sub>H</sub> (L)            | D <sub>n</sub> to $\overline{WE}$                     | 0                                                                           |      | 2.0                                                         |                                                                                       | 0                                                        |                                                                                    |       |       |
| t <sub>S</sub> (L)            | Setup Time, LOW<br>$\overline{CS}$ to $\overline{WE}$ | 0                                                                           |      | 0                                                           |                                                                                       | 0                                                        |                                                                                    | ns    |       |
| t <sub>H</sub> (L)            | Hold Time, LOW<br>$\overline{CS}$ to $\overline{WE}$  | 6.0                                                                         |      | 7.5                                                         |                                                                                       | 6.0                                                      |                                                                                    |       |       |
| t <sub>W</sub> (L)            | $\overline{WE}$ Pulse Width, LOW                      | 6.0                                                                         |      | 15.0                                                        |                                                                                       | 6.0                                                      |                                                                                    |       |       |

# Physical Dimensions inches (millimeters) unless otherwise noted




**16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS013, 0.300" Wide Body Package Number M16B**



**16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide Package Number N16E**

## Physical Dimensions

inches (millimeters) unless otherwise noted (Continued)



Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)