

TOSHIBA BIPOLAR DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TD62384AP, TD62384F, TD62384AF TD62385AP, TD62385F, TD62385AF


8CH LOW INPUT ACTIVE DARLINGTON SINK DRIVER

The TD62384AP/F/AF and TD62385AP/F/AF are non-inverting transistor arrays, which are comprised of eight NPN darlington output stages and PNP input stages. These devices are Low Level input active drivers and are suitable for operations with TTL, 5V CMOS and 5V Microprocessor which have sink current output drivers. Applications include relay, hammer, lamp and LED driver.

FEATURES


- Output current (single output) 500mA (Max.)
- High sustaining voltage 35V (TD62384F, 385F)
50V (TD62384AP/AF, 385AP/AF) (Min.)
- Low level active input
- Standard supply voltage
- Inputs compatible with TTL and 5V CMOS
- Package type-AP : DIP-18pin
- Package type-F, AF : SOP-18pin

TYPE	V _{IN} (ON)
TD62384AP / F / AF	- 20V~V _{CC} - 2.8V
TD62385AP / F / AF	0V~V _{CC} - 3.7V





Weight
DIP18-P-300-2.54D : 1.47g (Typ.)
SOP18-P-375-1.27 : 0.41g (Typ.)

PIN CONNECTION (TOP VIEW)



961001EBA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

SCHEMATICS (EACH DRIVER)
TD62384AP / F / AF

TD62385AP / F / AF


(*) The input and output parasitic diodes cannot be used as clamp diodes.

MAXIMUM RATING (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Supply Voltage		V_{CC}	- 0.5~7.0	V
Output Sustaining Voltage	AP / AF	$V_{CE(SUS)}$	- 0.5~50	V
	F		- 0.5~35	
Output Current		I_{OUT}	500	mA / ch
Input Voltage		V_{IN} (Note 1)	- 22~ $V_{CC} + 0.5$	V
		V_{IN} (Note 2)	- 0.5~7	
Input Current		I_{IN}	- 10	mA
Power Dissipation	AP	P_D (Note 3)	1.47	W
	F / AF		0.96	
Operating Temperature		T_{opr}	- 40~85	°C
Storage Temperature		T_{stg}	- 55~150	°C

(Note 1) TD62384AP / AF / F

(Note 2) TD62385AP / AF / F

(Note 3) Delated above 25°C in the proportion of 11.7mW/°C (AP-Type), 7.7mW/°C (F, AF-Type).

RECOMMENDED OPERATING CONDITIONS (Ta = - 40~85°C)

CHARACTERISTIC		SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage		V _{CC}	—	4.5	5.0	5.5	V
Output Sustaining Voltage	AP / AF	V _{CE (SUS)}	—	0	—	50	V
	F		—	0	—	35	
Output Current	AP	I _{OUT}	T _{pw} = 25ms, Duty = 50%, 8 Circuits	0	—	115	mA / ch
	F / AF		T _a = 85°C, T _j = 120°C	0	—	78	
				T _{pw} = 25ms, Duty = 10%, 1 Circuit	0	—	
Input Voltage	TD62384	V _{IN}	—	− 20	—	V _{CC}	V
	TD62385			0	—	5.5	
Power Dissipation	AP	P _D	—	—	—	0.52	W
	F / AF		—	—	—	0.35	


ELECTRICAL CHARACTERISTIC (Ta = 25°C)

CHARACTERISTIC			SYMBOL	TEST CIRCUIT	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Output Leakage Current		AP / AF	I _{CEX}	1	V _{CC} = 5.5V, I _{IN} = 0, Ta = 85°C	V _{OUT} = 50V	—	—	100	μA
		F			V _{OUT} = 35V					
Output Saturation Voltage			V _{CE} (sat)	2	V _{CC} = 4.5V, I _{OUT} = 350mA V _{IN} = V _{IN} (ON) MAX.		—	1.4	2.0	V
Input Current		(Output On)	I _{IN} (ON)	3	V _{CC} = 5.5V, V _{IN} = 0.4V		—	− 0.32	− 0.45	mA
					V _{CC} = 5.5V, V _{IN} = − 20V		—	—	− 2.6	
		(Output Off)	I _{IN} (OFF)	4	—		—	—	− 4.0	μA
Input Voltage	(Output On)	TD62384	V _{IN} (ON)	5	—		—	—	V _{CC} − 2.8	V
		TD62385			—		—	—	V _{CC} − 3.7	
Supply Current			I _{CC} (ON)	6	V _{CC} = 5.5V, V _{IN} = 0		—	17	22	mA
			I _{CC} (OFF)		V _{CC} = 5.5V, V _{IN} = V _{CC}		—	—	100	μA
Turn-On Delay			t _{ON}	7	V _{CC} = 5V, V _{OUT} = 50V		—	0.1	—	μs
Turn-Off Delay			t _{OFF}		R _L = 163Ω, C _L = 15pF (Note 1)		—	3	—	


(Note 1) F-Type : V_{OUT} = 35V, R_L = 116Ω

TEST CIRCUIT


1. I_{CEX}




2. $V_{CE(sat)}$




3. $I_{IN(ON)}$




4. $I_{IN(OFF)}$





5. $V_{IN(ON)}$



6. I_{CC}









7. t_{ON} , t_{OFF}



- (Note 1) Pulse Width $50\mu s$, Duty Cycle 10%
Output Impedance 50Ω , $t_r \leq 5ns$, $t_f \leq 10ns$
(Note 2) C_L includes probe and jig capacitance.


PRECAUTIONS for USING

Utmost care is necessary in the design of the output line, V_{CC} and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.



OUTLINE DRAWING
DIP18-P-300-2.54D




Unit : mm



Weight : 1.47g (Typ.)

OUTLINE DRAWING
SOP18-P-375-1.27

Unit : mm



Weight : 0.41g (Typ.)