


Features

- Low Forward Voltage Drop
- Guard Ring Construction for Transient Protection
- Fast Switching
- Low Leakage Current
- Three Fully Isolated Schottky Diodes

Mechanical Data

- Case: SOT-363, Plastic
- Case material - UL Flammability Rating 94V-0
- Moisture sensitivity: Level 1 per J-STD-020A
- Polarity: See Diagram
- Leads: Solderable per MIL-STD-202, Method 208
- Marking: KLL
- Weight: 0.006 grams (approx.)
- Ordering Information, See Below



SOT-363		
Dim	Min	Max
A	0.10	0.30
B	1.15	1.35
C	2.00	2.20
D	0.65 Nominal	
F	0.30	0.40
H	1.80	2.20
J	—	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.25
α	0°	8°
All Dimensions in mm		

Maximum Ratings @ T_A = 25°C unless otherwise specified

Characteristic	Symbol	SD103ATW	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V _{RRM} V _{RWM} V _R	40	V
RMS Reverse Voltage	V _{R(RMS)}	28	V
Forward Continuous Current (Note 1)	I _{FM}	350	mA
Average Rectified Current (Note 1)	I _O	175	mA
Non-Repetitive Peak Forward Surge Current (Note 1) @ t ≤ 10ms	I _{FSM}	1.0	A
Power Dissipation	P _d	200	mW
Thermal Resistance, Junction to Ambient Air	R _{θJA}	500	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +125	°C

Electrical Characteristics @ T_A = 25°C unless otherwise specified


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 2)	V _{(BR)R}	40	—	—	V	I _{RS} = 100μA (pulsed)
Forward Voltage Drop (Note 2)	V _F	—	0.27	—	V	I _F = 1mA
		—	0.32	—	V	I _F = 5mA
		—	0.36	0.37	V	I _F = 20mA
		—	0.44	0.50	V	I _F = 100mA
Reverse Current (Note 2)	I _R	—	0.2	2.0	μA	V _R = 10V
		—	0.4	5.0	μA	V _R = 30V
Total Capacitance	C _T	—	50	—	pF	V _R = 0V, f = 1.0MHz
Reverse Recovery Time	t _{rr}	—	10	—	ns	I _F = I _R = 200mA, I _{rr} = 0.1 x I _R , R _L = 100Ω

Ordering Information (Note 3)

Device	Packaging	Shipping
SD103ATW-7	SOT-363	3000/Tape & Reel

- Notes: 1. This is the maximum rating of single Diode (D₁ or D₂ or D₃). In the case of using two or three diodes, the maximum ratings per diode are 75% of the ratings for single diode operation.
 2. Short duration test pulse used to minimize self-heating effect.
 3. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information




KLL = Product Type Marking Code
YM = Date Code Marking
Y = Year ex: N = 2002
M = Month ex: 9 = September

Date Code Key


Year	2002	2003	2004	2005	2006	2007	2008	2009
Code	N	O	P	S	T	U	V	W

Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D




T_A, AMBIENT TEMPERATURE (°C)

Fig. 1 Power Derating Curve



V_F, FORWARD VOLTAGE (V)

Fig. 2 Typical Forward Characteristics



V_R, REVERSE VOLTAGE (V)

Fig. 3 Typ. Total Capacitance vs Reverse Voltage