

TOSHIBA BIPOLAR DIGITAL INTEGRATED CIRCUIT SILICON MONOLITHIC

TD62303P, TD62303F

6CH DIGIT DRIVER


The TD62303P and TD62303F are comprised of six NPN low saturation drivers.

These devices are specifically designed for multiplexed digit driving of six digits common cathode LED displays. This device is intended for use with TTL and 5V CMOS.


FEATURES

- Low saturation output : $V_{CE(sat)} = 0.8V$ (Max.)
- Output rating (single output) 17V (Min.) / 500mA (Max.)
- Input compatible with TTL and 5V CMOS
- Suitable for digit-driver of 6 digit common cathode LED displays.
- Package type-P : DIP-16pin
- Package type-F : SOP-16pin

PIN CONNECTION (TOP VIEW)




TD62303P



DIP16-P-300-2.54A

TD62303F




SOP16-P-225-1.27

Weight

DIP16-P-300-2.54A : 1.11g (Typ.)
SOP16-P-225-1.27 : 0.16g (Typ.)

SCHEMATICS (EACH DRIVER)



(Note) The input and output parasitic diodes cannot be used as clamp diodes.

961001EBA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Supply Voltage		V _{CC}	− 0.5~7.0	V
Output Sustaining Voltage		V _{CE (SUS)}	− 0.5~17	V
Output Current		I _{OUT}	500	mA / ch
Input Voltage		V _{IN}	− 0.5~V _{CC} + 0.5	V
Input Current		I _{IN}	− 10	mA
Power Dissipation	P	P _D	1.0	W
	F		0.625 (Note)	
Operating Temperature	P	T _{opr}	− 30~75	°C
	F		− 40~85	
Storage Temperature		T _{stg}	− 50~150	°C

(Note) On Glass Epoxy PCB (30×30×1.6mm Cu 50%)









RECOMMENDED OPERATING CONDITIONS (Ta = − 30~75°C and Ta = − 40~85°C for Type-F)

CHARACTERISTIC		SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Supply Voltage		V _{CC}	—	4.5	5.0	5.5	V
Output Sustaining Voltage		V _{CE (SUS)}	—	0	—	15	V
Output Current		I _{OUT}	DC 1 Circuit	0	—	350	mA / ch
Input Voltage		V _{IN}	—	0	—	V _{CC}	V
Power Dissipation	P	P _D	—	—	—	0.44	W
	F		(Note)	—	—	0.325	

(Note) On Glass Epoxy PCB (30×30×1.6mm Cu 50%)

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CIR-CUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Leakage Current	P	I _{CEX}	1	V _{CC} = 5.5V, V _{IN} = 0V V _{OUT} = 15V	—	—	100	μA
	F							
Output Saturation Voltage		V _{CE (sat)}	2	V _{CC} = 4.5V, I _{OUT} = 150mA	—	0.3	0.4	V
				V _{CC} = 4.5V, I _{OUT} = 350mA	—	0.65	0.8	
Input Current	Output On	I _{IN (ON)}	3	V _{CC} = 5.5V, V _{IN} = 5.5V	—	—	40	μA
	Output Off	I _{IN (OFF)}	4	V _{CC} = 5.5V, V _{IN} = 0.4V	—	—	− 0.36	mA
Input Voltage	Output On	V _{IN (ON)}	5	—	—	—	2.0	V
	Output Off	V _{IN (OFF)}	5	—	0.8	—	—	
Supply Current		I _{CC}	6	V _{CC} = 5.5V, V _{IN} = 5.5V	—	—	47	mA / Gate
Turn-On Delay		t _{ON}	7	V _{CC} = 5.0V, R _L = 37.5Ω V _{OUT} = 15V, C _L = 15pF	—	0.1	—	μs
Turn-Off Delay		t _{OFF}			—	0.7	—	μs



TEST CIRCUIT
1. I_{CEX}

2. $V_{CE(sat)}$

3. $I_{IN(ON)}$

4. $I_{IN(OFF)}$

5. $V_{IN(ON)}$, $V_{IN(OFF)}$

6. I_{CC}

7. t_{ON} , t_{OFF}


(Note 1) Pulse width $50\mu s$, duty cycle 10%
Output impedance 50Ω , $t_r \leq 5ns$, $t_f \leq 10ns$

(Note 2) C_L includes probe and jig capacitance.


PRECAUTIONS for USING

Utmost care is necessary in the design of the output line, V_{CC} and GND line since IC may be destroyed due to short-circuit between outputs, air contamination fault, or fault by improper grounding.



OUTLINE DRAWING
DIP16-P-300-2.54A


Unit : mm



Weight : 1.11g (Typ.)

OUTLINE DRAWING
SOP16-P-225-1.27

Unit : mm



Weight : 0.16g (Typ.)