



# MI-J00™

## Military DC-DC Converters 10 to 50W

### Product Highlights

The MI-J00 family of miniaturized DC-DC converters is designed for military applications utilizing distributed power architectures. Based on Vicor's 1st Generation family of zero-current/zero-voltage switching, component-level, DC-DC converters, the MI-J00 family offers state-of-the-art performance in terms of power density, efficiency, noise, ease of use, and reliability.

The MI-J00 family is designed to exceed all steady-state, transient and under/overvoltage requirements of MIL-STD-704D/E for both 28Vdc input (MI-J20) and 270Vdc input (MI-J60), and the worst case envelope of DOD-STD-1399A for 155Vdc input.

The output voltage can be externally trimmed or programmed from 50% to 110% of nominal output. Current limiting, remote sense, and an inhibit pin all combine to offer a high degree of protection, versatility, and reliability for military power systems.

All units are manufactured in ISO 9001-registered facilities. Full epoxy encapsulation in Vicor's industry standard package enables the MI-J00 family units to meet MIL-STD-810 environmental testing requirements for humidity, fungus, salt fog, explosive atmosphere, acceleration, vibration, and shock. (See page 32.)

### Features

- ✧ Inputs:
  - 28Vdc per MIL-STD-704D/E
  - 155Vdc per MIL-STD-1399A
  - 270Vdc per MIL-STD-704D/E
- ✧ Single output: 2 – 48Vdc
- ✧ Up to 23W/in<sup>3</sup>
- ✧ MIL-STD-810 environments
- ✧ Up to 90% efficiency
- ✧ Remote sense
- ✧ Current limit
- ✧ ZVS/ZCS power architecture
- ✧ Low noise FM control
- ✧ Size: 2.28" x 2.4" x 0.5" (57,9 x 61,0 x 12,7mm)

### Converter Specifications

(At  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified)

| PARAMETER                              | MIN                     | TYP       | MAX  | UNITS          | TEST CONDITIONS                    |
|----------------------------------------|-------------------------|-----------|------|----------------|------------------------------------|
| <b>Input Characteristics</b>           |                         |           |      |                |                                    |
| Input voltage range                    | See input voltage chart |           |      |                |                                    |
| No load power dissipation              |                         | 1.35      | 2.0  | Watts          |                                    |
| <b>Output Characteristics</b>          |                         |           |      |                |                                    |
| Set point accuracy                     |                         | 0.5       | 1.0  | % Vnom         |                                    |
| Load/line regulation                   |                         | 0.05      | 0.2  | % Vnom         | LL to HL, 10% to FL                |
|                                        |                         | 0.2       | 0.5  | % Vnom         | LL to HL, NL to 10%                |
| Output temperature drift               |                         | 0.01      | 0.02 | %/°C           |                                    |
| Output noise - pp                      |                         | 1.0       | 1.5  | % Vnom         | } Whichever is greater<br>20MHz BW |
|                                        |                         | 100       | 150  | mV             |                                    |
| Output voltage trimming <sup>(1)</sup> | 50                      |           | 110  | % Vnom         |                                    |
| Remote sense compensation              | 0.5                     |           |      | Vdc            |                                    |
| OVP set point                          |                         | N/A       |      |                |                                    |
| Current limit                          | 105                     |           | 125  | % Inom         | Auto restart                       |
| Short circuit current                  | 105                     |           | 130  | % Inom         |                                    |
| <b>Control Pin Characteristics</b>     |                         |           |      |                |                                    |
| Gate-in high threshold                 |                         | 6         |      | Vdc            |                                    |
| Gate-in low threshold                  | 0.65                    |           |      | Vdc            |                                    |
| Gate-in low current                    |                         |           | 6    | mA             |                                    |
| <b>Isolation Characteristics</b>       |                         |           |      |                |                                    |
| Isolation (input to output)            | 3,000                   |           |      | Vrms           |                                    |
| Isolation (output to baseplate)        | 500                     |           |      | Vrms           |                                    |
| Isolation (input to baseplate)         | 1,500                   |           |      | Vrms           |                                    |
| Input/output capacitance               |                         | 50        | 75   | pF             |                                    |
| <b>Environmental (MIL-STD-810)</b>     |                         |           |      |                |                                    |
| Altitude - method 500.2                | 70,000                  |           |      | feet           | Procedure II                       |
| Humidity - method 507.2                | 86/240                  |           |      | %/hours        | Procedure 1, cycle 1               |
| Acceleration - method 513.3            | 9                       |           |      | g's            | Procedure 2                        |
| Vibration - method 514.3               | 20                      |           |      | g's            | Procedure 1, category 6            |
| Shock - method 516.3                   | 40                      |           |      | g's            | Procedure 1                        |
| <b>Reliability (MIL-HDBK-217F)</b>     |                         |           |      |                |                                    |
| 25°C Ground Benign: G.B.               |                         | 2,871,050 |      | hours          |                                    |
| 50°C Naval Sheltered: N.S.             |                         | 667,568   |      | hours          |                                    |
| 65°C Airborne Inhabited Cargo: A.I.C.  |                         | 559,855   |      | hours          |                                    |
| <b>Thermal Characteristics</b>         |                         |           |      |                |                                    |
| Efficiency                             |                         | 80-90     |      | %              |                                    |
| Baseplate to sink                      |                         | 0.14      |      | °C/W           | With thermal pads                  |
| Thermal shutdown                       |                         | N/A       |      |                |                                    |
| Baseplate operating temperature        |                         |           | +100 | °C             | See product grade                  |
| Storage temperature                    |                         |           | +125 | °C             | See product grade                  |
| <b>Mechanical Specifications</b>       |                         |           |      |                |                                    |
| Weight                                 |                         | 3.0 (85)  |      | ounces (grams) |                                    |

<sup>(1)</sup> 10V, 12V, and 15V outputs, standard trim range  $\pm 10\%$ . Consult factory for wider trim range.

## Configuration Chart

### MI-J



Semi-custom modules available:  
Consult factory.

(1) 16V operation at 75% load.

(2) These units rated at 75%  
load from 125-150Vin:

MI-J6Z-xY

MI-J6Y-xY

MI-J60-xY

28Vdc input per MIL-STD 704D/E

155Vdc input per DOD-STD-1399A

270Vdc input per MIL-STD-704D/E

#### Input Voltage

| Nominal  | Range                     | Transient |
|----------|---------------------------|-----------|
| 2 = 28V  | 18 – 50V <sup>(1)</sup>   | 60V       |
| 5 = 155V | 100 – 210V                | 230V      |
| 6 = 270V | 125 – 400V <sup>(2)</sup> | 475V      |
| 7 = 165V | 100 – 310V                |           |

#### Output Voltage

|          |           |           |
|----------|-----------|-----------|
| Z = 2V   | T = 6.5V  | N = 18.5V |
| Y = 3.3V | R = 7.5V  | 3 = 24V   |
| O = 5V   | M = 10V   | L = 28V   |
| X = 5.2V | 1 = 12V   | J = 36V   |
| W = 5.5V | P = 13.8V | K = 40V   |
| V = 5.8V | 2 = 15V   | 4 = 48V   |

#### Product Grade Operating Temp.

|   |   |                 |
|---|---|-----------------|
| I | = | -40°C to +100°C |
| M | = | -55°C to +100°C |

#### Output Power / Current

|     |     |     |
|-----|-----|-----|
|     | ≥5V | <5V |
| A = | 10W | —   |
| Z = | 25W | 5A  |
| Y = | 50W | 10A |

## Product Grade Specifications

| PARAMETER                                 | PRODUCT GRADE                             |                                           |
|-------------------------------------------|-------------------------------------------|-------------------------------------------|
|                                           | I-Grade                                   | M-Grade                                   |
| Storage temperature                       | -55°C to +125°C                           | -65°C to +125°C                           |
| Operating temperature (baseplate)         | -40°C to +100°C                           | -55°C to +100°C                           |
| Power cycling burn-in                     | 12 hours, 25 cycles                       | 96 hours, 200 cycles                      |
| Temperature cycled with power off         | 48 hours, 12-16 cycles<br>-55°C to +100°C | 48 hours, 12-16 cycles<br>-65°C to +100°C |
| Test data supplied at these temperatures* | -40°C, +80°C                              | -55°C, +80°C                              |
| Warranty                                  | 2 years                                   | 2 years                                   |
| Environmental compliance                  | MIL-STD-810                               | MIL-STD-810                               |
| Derating                                  | NAVMAT P-4855-1A                          | NAVMAT P-4855-1A                          |

\*Test data available for review or download from [vicorpower.com](http://vicorpower.com)

## Mechanical Drawing

