


GW Bi-Color Type

Conventional Part No. Global Part No. Lighting Color
 LN2162C13 – (TR) … LNJ162C3XRA …… Red / Green

■ 絶対最大定格 Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Lighting Color	P_D (mW)	I_F (mA)	I_{FP} (mA)*	V_R (V)	T_{opr} ($^\circ\text{C}$)	T_{stg} ($^\circ\text{C}$)
Red	45	15	60	3	$-25 \sim +80$	$-30 \sim +85$
Green	45	15	60	4	$-25 \sim +80$	$-30 \sim +85$

I_{FP} の条件は $duty$ 10% Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec

■ 電気的光学的特性 Electro-Optical Characteristics ($T_a = 25^\circ\text{C}$)

Conventional Part No.	Lighting Color	Lens Color	I_O		I_F	V_F		λ_P	$\Delta\lambda$	I_F	I_R	
			Typ	Min		Typ	Max	Typ	Typ		Max	V_R
LN2162C13 – (TR)	Red	Clear	1.8	0.65	10	2.0	2.8	650	40	10	10	3
	Green		4.0	1.5	10	2.05	2.8	565	30	10	10	4
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

