

General Description

It's mainly suitable for use as a load switch.

FEATURES



- $V_{DS} = -20V$, $I_D = -3.7A$
- Drain to Source on-state Resistance
 $R_{DS(ON)} = 76m\ \Omega$ (Max.) @ $V_{GS} = -4.5V$
 $R_{DS(ON)} = 112m\ \Omega$ (Max.) @ $V_{GS} = -2.5V$

MAXIMUM RATING (Ta=25 °C)


CHARACTERISTIC		SYMBOL	P-Ch	UNIT
Drain to Source Voltage		V_{DS}	-20	V
Gate to Source Voltage		V_{GS}	± 12	V
Drain Current	DC@Ta=25°C (Note1)	I_D	-3.7	A
	Pulsed (Note1)	I_{DP}	-16	
Drain to Source Diode Forward Current		I_S	-16	A
Drain Power Dissipation	Ta=25°C (Note1)	P_D	1.25	W
	Ta=100°C (Note1)		0.6	
Maximum Junction Temperature		T_j	150	°C
Storage Temperature Range		T_{stg}	-55~150	°C
Thermal Resistance, Junction to Ambient (Note1)		R_{thJA}	100	°C/W

Note1) Surface Mounted on 1" × 1" FR4 Board, $t \leq 5sec$.

PIN CONNECTION (TOP VIEW)



Marking



KMA3D7P20SA

ELECTRICAL CHARACTERISTICS (Ta=25℃)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Static						
Drain to Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =-250μA	-20	-	-	V
Drain Cut-off Current	I _{DSS}	V _{GS} =0V, V _{DS} =-20V	-	-	-1	μA
Gate to Source Leakage Current	I _{GSS}	V _{GS} = ± 12V, V _{DS} =0V	-	-	± 100	nA
Gate to Source Threshold Voltage	V _{th}	V _{DS} =V _{GS} , I _D =-250μA	-0.55	-	-1.5	V
Drain to Source On Resistance	R _{DS(ON)}	V _{GS} =-4.5V, I _D =-2.8A (Note2)	-	65	76	m Ω
		V _{GS} =-2.5V, I _D =-2.3A (Note2)	-	90	112	
Dynamic						
Input Capacitance	C _{iss}	V _{DS} =-10V, f=1MHz , V _{GS} =0V	-	443	-	pF
Output Capacitance	C _{oss}		-	92	-	
Reverse Transfer Capacitance	C _{rss}		-	51	-	
Total Gate Charge	Q _g	V _{DS} =-10V, I _D =-2.8A , V _{GS} =-4.5V (Note2)	-	4.37	-	nC
Gate to Source Charge	Q _{gs}		-	0.54	-	
Gate to Drain Charge	Q _{gd}		-	1.54	-	
Turn-on Delay time	t _{d(on)}	V _{DD} =-10V, V _{GS} =-4.5V , I _D =-2.8A, R _G =6 Ω (Note2)	-	6.2	-	ns
Turn-on Rise time	t _r		-	18	-	
Turn-off Delay time	t _{d(off)}		-	50	-	
Turn-off Fall time	t _f		-	33	-	
Source to Drain Diode Ratings						
Source to Drain Forward Voltage	V _{SD}	V _{GS} =0V, I _S =-1.0A (Note2)	-	-0.8	-1.2	V
Note2) Pulse Test : Pulse width <300μs , Duty cycle < 2%						

Fig1. $I_D - V_{DS}$




Fig2. $R_{DS(ON)} - I_D$




Fig3. $I_D - V_{GS}$




Fig4. $R_{DS(ON)} - T_j$




Fig5. $V_{th} - T_j$





Fig6. $I_S - V_{SD}$



KMA3D7P20SA

Fig7. $R_{DS(ON)} - V_{GS}$




Fig8. $C - V_{DS}$




Fig9. $Q_g - V_{GS}$




Fig10. Safe Operation Area




Fig10. Transient Thermal Response Curve

