

CEM9953A



PRELIMINARY

Dual P-Channel Enhancement Mode MOSFET

FEATURES

5

- -30V , -2.9A , $R_{DS(ON)}=100m\Omega$ @ $V_{GS}=-10V$.
 $R_{DS(ON)}=150m\Omega$ @ $V_{GS}=-4.5V$.
- Super high dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handing capability.
- Surface Mount Package.



ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous ^a @ $T_J=125^\circ C$ -Pulsed ^b	I_D	± 2.9	A
	I_{DM}	± 10	A
Drain-Source Diode Forward Current ^a	I_S	-1.2	A
Maximum Power Dissipation ^a	P_D	2	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ C$

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient ^a	$R_{\theta JA}$	78	$^\circ C/W$
------------------------------------------------------	-----------------	----	--------------

CEM9953A

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ C$ unless otherwise noted)

5

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24V, V_{GS}=0V$			-2	μA
Gate-Body Leakage	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
ON CHARACTERISTICS^b						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D = -250\mu A$	-1	-1.6	-3	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=-10V, I_D = -1A$			100	$m\Omega$
		$V_{GS}=-4.5V, I_D = -0.5A$			150	$m\Omega$
On-State Drain Current	$I_{D(ON)}$	$V_{DS} = -5V, V_{GS} = -10V$	-10			A
Forward Transconductance	g_{FS}	$V_{DS} = -15V, I_D = -2.9A$	2			S
DYNAMIC CHARACTERISTICS^c						
Input Capacitance	C_{iss}	$V_{DS} = -10V, V_{GS} = 0V$ $f = 1.0MHz$		350	460	pF
Output Capacitance	C_{oss}			260	340	pF
Reverse Transfer Capacitance	C_{rss}			100	130	pF
SWITCHING CHARACTERISTICS^c						
Turn-On Delay Time	$t_{D(ON)}$	$V_{DD} = -10V,$ $R_L = 10\Omega ,$ $I_D = -1A,$ $V_{GEN} = -10V,$ $R_{GEN} = 6\Omega$		12	40	ns
Rise Time	t_r			13	40	ns
Turn-Off Delay Time	$t_{D(OFF)}$			18	90	ns
Fall Time	t_f			7	50	ns
Total Gate Charge	Q_g	$V_{DS} = -10V, I_D = -2.9A,$ $V_{GS} = -10V$		10	25	nC
Gate-Source Charge	Q_{gs}			2		nC
Gate-Drain Charge	Q_{gd}			3		nC

CEM9953A

5

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0\text{V}$, $I_S = -1.25\text{A}$		-0.8	-1.3	V

Notes

- a. Surface Mounted on FR4 Board, $t \leq 10\text{sec}$.
- b. Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2\%$.
- c. Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Drain Current and Temperature

CEM9953A

5




Figure 5. Gate Threshold Variation with Temperature




Figure 7. Transconductance Variation with Drain Current




Figure 9. Gate Charge




Figure 6. Breakdown Voltage Variation with Temperature




Figure 8. Body Diode Forward Voltage Variation with Source Current




Figure 10. Maximum Safe Operating Area

CEM9953A

5




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms




Figure 13. Normalized Thermal Transient Impedance Curve