


### Features

- Glass Passivated Die Construction
- Low Forward Voltage Drop and High Current Capability
- Surge Overload Rating to 30A Peak
- Ideally Suited for Automated Assembly

### Mechanical Data

- Case: Molded Plastic
- Case Material - UL Flammability Rating Classification 94V-0
- Moisture sensitivity: Level 1 per J-STD-020A
- Terminals: Solder Plated Terminal - Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band or Cathode Notch
- SMA Weight: 0.064 grams (approx.)
- SMB Weight: 0.093 grams (approx.)
- Marking: Type Number, See Page 2
- Ordering Information: See Page 2



|                      | SMA  |      | SMB  |      |
|----------------------|------|------|------|------|
| Dim                  | Min  | Max  | Min  | Max  |
| A                    | 2.29 | 2.92 | 3.30 | 3.94 |
| B                    | 4.00 | 4.60 | 4.06 | 4.57 |
| C                    | 1.27 | 1.63 | 1.96 | 2.21 |
| D                    | 0.15 | 0.31 | 0.15 | 0.31 |
| E                    | 4.80 | 5.59 | 5.00 | 5.59 |
| G                    | 0.10 | 0.20 | 0.10 | 0.20 |
| H                    | 0.76 | 1.52 | 0.76 | 1.52 |
| J                    | 2.01 | 2.62 | 2.00 | 2.62 |
| All Dimensions in mm |      |      |      |      |

A, B, D, G, J, K, M Suffix Designates SMA Package  
 AB, BB, DB, GB, JB, KB, MB Suffix Designates SMB Package

### Maximum Ratings and Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

| Characteristic                                                                                                        | Symbol                          | S1<br>A/AB  | S1<br>B/BB | S1<br>D/DB | S1<br>G/GB | S1<br>J/JB | S1<br>K/KB | S1<br>M/MB | Unit               |
|-----------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------|------------|------------|------------|------------|------------|------------|--------------------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage                                | $V_{RRM}$<br>$V_{RWM}$<br>$V_R$ | 50          | 100        | 200        | 400        | 600        | 800        | 1000       | V                  |
| RMS Reverse Voltage                                                                                                   | $V_{R(RMS)}$                    | 35          | 70         | 140        | 280        | 420        | 560        | 700        | V                  |
| Average Rectified Output Current @ $T_T = 100^\circ\text{C}$                                                          | $I_O$                           | 1.0         |            |            |            |            |            |            | A                  |
| Non-Repetitive Peak Forward Surge Current<br>8.3ms Single half sine-wave superimposed on rated load<br>(JEDEC Method) | $I_{FSM}$                       | 30          |            |            |            |            |            |            | A                  |
| Forward Voltage @ $I_F = 1.0\text{A}$                                                                                 | $V_{FM}$                        | 1.1         |            |            |            |            |            |            | V                  |
| Peak Reverse Leakage Current @ $T_A = 25^\circ\text{C}$<br>at Rated DC Blocking Voltage @ $T_A = 125^\circ\text{C}$   | $I_{RM}$                        | 5.0<br>100  |            |            |            |            |            |            | $\mu\text{A}$      |
| Typical Total Capacitance (Note 1)                                                                                    | $C_T$                           | 10          |            |            |            |            |            |            | pF                 |
| Typical Thermal Resistance, Junction to Terminal (Note 2)                                                             | $R_{\theta JT}$                 | 30          |            |            |            |            |            |            | $^\circ\text{C/W}$ |
| Operating and Storage Temperature Range                                                                               | $T_J, T_{STG}$                  | -65 to +150 |            |            |            |            |            |            | $^\circ\text{C}$   |

- Notes: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.  
 2. Thermal Resistance Junction to Terminal, unit mounted on PC board with 5.0 mm<sup>2</sup> (0.013 mm thick) copper pads as heat sink.


## Ordering Information (Note 3)

| Device*         | Packaging  | Shipping                             |
|-----------------|------------|--------------------------------------|
| S1x-7<br>S1xB-7 | SMA<br>SMB | 5000/Tape & Reel<br>3000/Tape & Reel |


Notes: 3. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

\* x = Device type, e.g. S1A-7 (SMA package); S1AB-7 (SMB package).


## Marking Information




XXX = Product type marking code, ex: S1A (SMA package)  
 XXXX = Product type marking code, ex: S1AB (SMB package)  
 D11 = Manufacturers' code marking  
 YWW = Date code marking  
 Y = Last digit of year ex: 2 for 2002  
 WW = Week code 01 to 52




$T_T$ , TERMINAL TEMPERATURE (°C)  
 Fig. 1 Forward Current Derating Curve



$V_F$ , INSTANTANEOUS FORWARD VOLTAGE (V)  
 Fig. 2 Typical Forward Characteristics



NUMBER OF CYCLES @ 60Hz  
 Fig. 3 Typical Forward Characteristics



PERCENT OF RATED PEAK REVERSE VOLTAGE (%)  
 Fig. 4 Typical Reverse Characteristics