


Series 714

PCB connectors carrier assemblies 2.54 mm

Single row / double row

Solder tail / press-fit



PCB "Zero profile" receptacles

Accept pins $\varnothing$ 0.40–0.54 mm



Single receptacle contacts for solder- and press-fit solderless mount into PCB, supplied on disposable carriers

For corresponding pin connectors see pages 43 to 46


Ordering information

Replace **xx** with the number of poles, e.g. 714-91-1xx-31-012 for a single row version with 8 pins per row becomes:
714-91-108-31-012

Option:

Double row, disposable carrier strip on request

Platings	Sleeve 	Clip 	Pin 
91	5 μ m Sn Pb	0.25 μ m Au	
93	5 μ m Sn Pb	0.75 μ m Au	
99	5 μ m Sn Pb	5 μ m Sn Pb	



714-91-1xx-31-012


714-93-1xx-31-012

714-99-1xx-31-012

Straight receptacle contacts: solder mount into PCB thickness 1 to 2.4 mm with hole $\varnothing$ 1 mm

Availability: supplied on single row, disposable carrier strip, from 2 to 64 contacts

Standard number of contacts 5, 6, 8, 10, 14, 16, 20, 21, 25, 30, 32, 48, 56, 60, 64



714-91-1xx-31-018


714-93-1xx-31-018

714-99-1xx-31-018

Straight receptacle contacts: solder mount into PCB thickness 1 to 3.4 mm with hole $\varnothing$ 1 mm

Availability: supplied on single row, disposable carrier strip, from 2 to 64 contacts

Standard number of contacts 5, 6, 8, 10, 14, 16, 20, 21, 25, 30, 32, 48, 56, 60, 64



714-91-1xx-31-008 **B**

714-93-1xx-31-008 **B**

714-99-1xx-31-008 **B**

Straight receptacle contacts: solderless press-fit mount into PCB thickness 1.5 to 2.5 mm with plated-thru hole $\varnothing$ 1.05 mm ($\pm$ 0.05)

Availability: supplied on single row, disposable carrier strip, from 2 to 64 contacts

Standard number of contacts 5, 6, 8, 10, 14, 16, 20, 21, 25, 30, 32, 48, 56, 60, 64