



SK52B THRU SK510B

5.0 AMPS. Surface Mount Schottky Barrier Rectifiers



Voltage Range
20 to 100 Volts
Current
5.0 Amperes


Features

- ✧ For surface mounted application
- ✧ Metal to silicon rectifier, majority carrier conduction
- ✧ Low forward voltage drop
- ✧ Easy pick and place
- ✧ High surge current capability
- ✧ Plastic material used carriers Underwriters Laboratory Classification 94V-O
- ✧ Epitaxial construction
- ✧ High temperature soldering: 260°C / 10 seconds at terminals

Mechanical Data

- ✧ Case: Molded plastic
- ✧ Terminals: Solder plated
- ✧ Polarity: Indicated by cathode band
- ✧ Packaging: 16mm tape per EIA STD RS-481
- ✧ Weight: 0.1 gram

SMB/DO-214AA



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SK 52B	SK 53B	SK 54B	SK 55B	SK 56B	SK 59B	SK 510B	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	90	100	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	63	70	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	90	100	V
Maximum Average Forward Rectified Current at T _L (See Fig. 1)	I _(AV)	5.0							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	100					150		A
Maximum Instantaneous Forward Voltage @ 5.0A	V _F	0.55			0.75		0.85		V
Maximum DC Reverse Current (Note 1) @ T _A =25℃ at Rated DC Blocking Voltage @ T _A =100℃	I _R	0.5					0.6		mA
		20			10.0		20.0		mA
Typical Thermal Resistance (Note 2)	R θ _{JL}	17							℃/W ℃/W
	R θ _{JA}	75							
Operating Temperature Range	T _J	-55 to +125				-55 to +150			℃
Storage Temperature Range	T _{STG}	-55 to +150							℃

Notes: 1. Pulse Test with PW=300 usec, 1% Duty Cycle

2. Measured on P.C.Board with 0.4 x 0.4"(10.0 x 10.0mm) Copper Pad Areas.

RATINGS AND CHARACTERISTIC CURVES (SK52B THRU SK510B)

FIG. 1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3- TYPICAL FORWARD CHARACTERISTICS




FIG. 4- TYPICAL REVERSE CHARACTERISTICS




FIG. 5- TYPICAL JUNCTION CAPACITANCE




FIG. 6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS

