

YSS220

(SP3)
Surround Processor 3

■ OUTLINE

YSS220(SP3) is an LSI which has surround capability by digital audio technology.

The LSI has built-in A/D, D/A converters which enable digital sound processing for analog signals.


With a 256k pseudo SRAM or SRAM connected, the LSI can process digital delay up to 512ms.

■ FEATURES

- Built-in 15-bit floating ADC (L, R 2 channels) and DAC (FL, FR, RL, RR4 channels) enable digital processing for analog signals with 32kHz internal sampling frequency.
- 4 channels except center output can output digital signals as well. With a DAC connected externally, it will be possible with up to 5 channels (FL, C, FR, RL, RR).
- Hi-performance surround by mixing many echoes with using up to 512ms digital delay.
- Preset mode for easy control by terminal setting.
- Register control mode where it is possible to set various coefficients using microprocessor serial interface for original sound processing.
- Internal DSP is a 24-bit × 13-bit high speed multiplier with 128 steps.
- One 256k (32k × 8) pseudo SRAM or SRAM to be connected.
- 12.288MHz (384fs) master clock.
- 5V single power supply, Si-gate CMOS process.
- 64-pin plastic QFP(YSS220-F)

Note: Due to the nature of the product, the preset data cannot be disclosed although partially.

■ PIN DESCRIPTION



〈64pin QFP Top View〉

No.	Name	I/O	Description
1	MD4	I/O	External RAM interface data terminal
2	MD3	I/O	External RAM interface data terminal
3	MD0	I/O	External RAM interface data terminal
4	MD1	I/O	External RAM interface data terminal
5	MD2	I/O	External RAM interface data terminal
6	MCKO	O	DOEN='L': Master clock output (12.288MHz) DOEN='H': Fixed to 'L'
7	XO	O	X'tal oscillator terminal
8	XI	I	X'tal oscillator terminal or external clock input(12.288MHz)
			MODE='H'
			MODE='L'
9	ER0/CSN	I+s	ER0 : E/R preset select 0 CSN : CPU I/F chip select
10	ER1/SCKN	I+s	ER1 : E/R preset select 1 SCKN : CPU I/F serial clock
11	ER2/CDI	I+s	ER2 : E/R preset select 2 CDI : CPU I/F serial data
12	REV0	I+	Reverbration preset select 0
13	REV1	I+	Reverbration preset select 1
14	REV2	I+	Reverbration preset select 2
15	MUTEN	I+	Output muting control (low-active)
16	ICN	Is	Initial clear input
17	PRG	I+	DSP program select (available only when MODE='H') 'L': Mode 0, 'H': Mode 1
18	MODE	I+	Operation mode select 'L': Register control mode, 'H': Preset mode
19	VSS	—	Ground (digital block)
20	AVSS	—A	Ground (analog block)
21	CVA	—A	L-ch ADC center voltage terminal
22	AORL	OA	Rear L-ch DAC output
23	AORR	OA	Rear R-ch DAC output
24	CHL	—A	AIL input sample/hold capacitor terminal
25	AIL	IA	L-ch ADC input
26	VDD	—	+5V power supply (digital block)
27	AIR	IA	R-ch ADC input
28	CHR	—A	AIR input sample/hold capacitor terminal
29	AOFL/AOCE	OA	DOEN='H': Front L-ch DAC output DOEN='L': C-ch DAC output
30	AOFR/AOCE	OA	DOEN='H': Front R-ch DAC output DOEN='L': C-ch DAC output
31	AVDD	—A	+5V power supply (analog block)
32	CVB	—A	R-ch, C-ch ADC center voltage terminal


No.	Name	I/O	Description	
33	AVDD	– A	+5V power supply (analog block)	
34	VDD	–	+5V power supply (digital block)	
35	TST0	I+	LSI test terminal (Connect to VDD)	
36	TST1	I+	LSI test terminal (Connect to VDD)	
37	DOEN	I+	Digital signal output/Analog C-ch output enable	
			DOEN= 'L'	DOEN= 'H'
38	SDO1	O	Digital signal output rear channel (RL, RR)	Fixed to 'L'
39	SDO0	O	Digital signal output front channel (FL, FR)	Fixed to 'L'
40	WC	O	Digital signal output word clock fs	Fixed to 'L'
41	BCO	O	Digital signal output bit clock 64fs	Fixed to 'H'
42	MA0	O	External RAM interface address terminal	
43	MA1	O	External RAM interface address terminal	
44	MA2	O	External RAM interface address terminal	
45	MA3	O	External RAM interface address terminal	
46	MA4	O	External RAM interface address terminal	
47	MA5	O	External RAM interface address terminal	
48	MA6	O	External RAM interface address terminal	
49	MA7	O	External RAM interface address terminal	
50	MA12	O	External RAM interface address terminal	
51	MA14	O	External RAM interface address terminal	
52	VSS	–	Ground (digital block)	
53	MA10	O	External RAM interface address terminal	
54	MA11	O	External RAM interface address terminal	
55	MA9	O	External RAM interface address terminal	
56	MA8	O	External RAM interface address terminal	
57	MA13	O	External RAM interface address terminal	
58	VDD	–	+5V power supply (digital block)	
59	WEN	O	External RAM interface write enable terminal	
60	OEN	O	External RAM interface output enable terminal	
61	CEN	O	External RAM interface chip enable terminal	
62	MD7	I/O	External RAM interface data terminal	
63	MD6	I/O	External RAM interface data terminal	
64	MD5	I/O	External RAM interface data terminal	

NOTE) I+: Input terminal with a pull-up resistor

IS : Schmitt input

A : analog terminal

■ BLOCK DIAGRAM



■ FUNCTION DESCRIPTION

1. Clocks XI, XO, MCKO

X'tal oscillation circuit is formed by using XI, XO terminals. The oscillation frequency is 12.288MHz ($f_s=32\text{KHz}$).

When DOEN='L', master clock is output through MCKO terminal.

2. ADCs and DACs AIL, AIR, CHL, CHR, AOFL/AOCE, AORL, AOFR/AOCE, AORR, CVA, CVB

L, R audio signals are input to AIL, AIR terminals. External capacitors are required to CHL, CHR terminals for sample/hold. CVA, CVB are center voltage terminals of L and R channels ADCs. Connect capacitors for stability, and bias AIL, AIR terminals with these voltages, respectively. The AIL and AIR signal are DC-cut by internal HPF after A/D conversion.

DAC sigals are output thorough AOFL/AOCE, AORL, AOFR/AOCE, AORR terminals. Connect capacitors for sample/hold, and buffer with a hi-impedance input for output.


According to setting of DOEN terminal, outputs from the DACs are as follows:

DOEN	MODE	AOFL/ AOCE	AOFR/ AOCE	AORL	AORR	DIGITAL OUT
'H'	4CHANNEL MODE	FLOUT	FROUT	RLOUT	RROUT	OFF
'L'	5CHANNEL MODE	COUT	COUT	RLOUT	RROUT	FL, FR, (RL, RR)

3. Digital output DOEN, BCO, WC, SD00, SD01

Except center channel, each channel can also output digital data.

If digital output is required, set DOEN terminal to 'L'.



4. Microprocessor interface MODE, PRG, MUTEN ER0/CSN, ER1/SCKN, ER2/CDI, REV0, REV1, REV2

LSI control method varies according to setting for MODE terminal.

(Each of ER0/CSN, ER1/SCKN, ER2/CDI terminals has different functions depending on its MODE setting and terminal names indicate both functions. In this section, however, only the name for the set mode is indicated.)

(1) Preset mode (MODE= 'H')

All control is done by terminal settings.

Use PRG terminal for program setting, ER0, ER1, ER2, REV0, REV1, REV2 terminals for preset selection.

In this mode, when MUTEN terminal is set to 'L', both DAC outputs and digital outputs are muted instantly.

(2) Register control mode (MODE= 'L')

All control is done by writing data to registers using microprocessor serial interface (using CSN, SCKN, CEDI terminals).

In this mode, REV0, REV1, REV2, MUTEN terminals are invalid.

5. External RAM interface MA0 ~ MA14, MD0 ~ 7, CEN, WEN, OEN


This LSI requires a 256K(32k*8word) pseudo SRAM or SRAM.

6. Initial clear ICN, TST0, TST1


This LSI requires initial clear when the power is turned on. Set ICN terminal to 'L' for one sampling period or more. TST0, TST1 are LSI test terminals. Connect them to VDD.

■ DSP SIGNAL FLOW

1. MODE 0



2. MODE 1




3. DSP signal flow description

- The number in the flow

In this flow, each number marked on the multiplier corresponds to the lower byte of the coefficient register address.

The number marked on delay tap (for discrimination, they are in different direction from those on the multiplier) corresponds to the lower byte of the memory pointer register addresses.

The box with 3 coefficient register addresses indicates the 1st order IIR filter.



- Processing blocks

The signal flow is divided into 3 processing blocks.

(1) VOL (VOLUME) block

This block consists of following attenuators immediately before output for each mode.

MODE 0 : 0250H, 02A8H, 027CH, 02AAH, 02D6H, 027EH, 02D4H, 0252H and 02EAH

MODE 1 : 0234H, 025CH, 02E6H, 0248H, 025EH, 02E8H, 02FAH, 0272H, 024AH, 02FCH,
0270H, 0236H and 0282H

(2) REV (REVERBERATOR) block

This block is indicated as 'REVERBERATOR' in the Mode 1 signal flow diagram. Eight types of reverberator can be selected for this block by setting the terminal or OPR1.

This block uses memory addresses 1B80H-3FFFH for Preset #0-5 and 2590H-3FFFH for Preset #6 and 7.

(3) E/R (EARLY REFLECTION) block

This block consists of other parts of the signal flow than the above. For this block, it is possible to select 4 types of preset patterns in MODE 0 and 7 types in MODE 1 (by setting the terminal or OPR1) or all parameters can be set. In MODE 1, care should be used as the REV block uses a part of the memory as described above.

- Registers not assigned in the flow

Do not write any data to the memory pointer registers and the coefficient registers which are not assigned in the flow.


■ CONTROL DESCRIPTION

1. Microprocessor interface


When in the register control mode (MODE='L'), function control and setting of DSP parameter are performed by writing data to the registers.

After setting the CSN terminal to 'L', send 2 bytes of the register addresses and then send the data, using SCKN and CDI terminals. As the register address where the data is written undergoes automatic increment at each sending of 1-byte data, the data is written in continuous addresses one after another only by sending them.

a) When address is 0000H or 0001H.



b) When address is 0100H or more.



2. Register map

Address (HEX)	Name	Description
0000	OPR0	Internal operation setting register
0001	OPR1	Preset data selection register
0100 ↓ 017F	M00 ↓ M7F	Memory pointer register
0200 ↓ 02FF	C00 ↓ CFF	Coefficient register

(Note)

* Do not write data in the other addresses.

* Data is not fixed when initial clear (except OPR0).

3. Data setting

(1)OPR0

- b0 (LSB) : Output muting ('1'=Muted)
- b1 : Program select ('0'=Mode 0, '1'=Mode 1)
- b2 : "VOL block" preset mode selection ('1'=preset)
- b3 : "E/R block" preset mode selection ('1'=preset)
- b4-b7 (MSB) : Set to '0' at all times.

(2)OPR1

- b0 (LSB), b1, b2 : "E/R block" preset pattern selection
(Preset # = $b2 \times 4 + b1 \times 2 + b0$)
- b3 : Don't care.
- b4, b5, b6 : "REV block" preset pattern selection (Mode 1 only)
(Preset # = $b6 \times 4 + b5 \times 2 + b4$)
- b7 (MSB) : don't care.

<Preset patterns>

	E/R Preset #	Guide name	REV Preset #	Rev. time
Mode 0	0	Hall 1	Fix to 0	
	1	Hall 2		
	2	Stadium		
	3	Disco 1		
Mode 1	0	Hall 3	0	Hall 1.0S
	1	Hall 4	1	Hall 1.5S
	2	Church 1	2	Hall 2.0s
	3	Church 2	3	Hall 2.5s
	4	Plate	4	Hall 3.0s
	5	Disco 2	5	Hall 3.5s
	6	«Mute»	6	Plate 1.5s
	7	(INHIBIT)	7	Plate 2.5s

4. Terminal control

When in the preset mode (MODE = 'H'), function control and setting of DSP parameter are performed by setting terminals.

Terminal	Function	Description
PRG	DSP mode selection	'L' : Mode 0 'H' : Mode 1
ER0 ER1 ER2	E/R Preset selection	Preset # = $ER2*4 + ER1*2 + ER0$ (0 = 'L', 1 = 'H') Refer to <Preset Patterns> table.
REV0 REV1 REV2	REV preset selection (Available only when in Mode 1. Fix all to 'L' when in Mode 0)	Preset # = $REV2*4 + REV1*2 + REV0$ (0 = 'L', 1 = 'H') Refer to <Preset Patterns> table.
MUTEN	Output Muting	'L' : Muting

■ ELECTRICAL CHARACTERISTICS

1. Absolute maximum ratings

Parameter	Symbol	Rating	Unit
Power supply voltage	V _{DD}	-0.3 ~ 7.0	V
Input voltage	V _I	-0.3 ~ V _{DD} +0.5	V
Operating temperature	T _{op}	-40 ~ 85	°C
Storage temperature	T _{stg}	-50 ~ 125	°C

2. Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
Power supply voltage	V _{DD}	4.5	5.0	5.5	V
Operating temperature	T _{op}	0	25	70	°C

3. DC Characteristics

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Power supply current	W	V _{DD} =5.0V			225	mW
Input voltage H level (1)	V _{IH1}	*1	2.2			V
Input voltage L level (1)	V _{IL1}	*1			0.8	V
Input voltage H level (2)	V _{IH2}	*2	3.5			V
Input voltage L level (2)	V _{IL2}	*2			1.5	V
Input voltage H level (3)	V _{IH3}	*3	3.5			V
Input voltage L level (3)	V _{IL3}	*3			0.8	V
Input leakage current	V _{LI}				10	μA
Input capacitance	C _I				10	pF
Input capacitance	C _O				10	pF
Output voltage H level (1)	V _{OL}	I _{OL} =0.4mA, *4	V _{DD} -1.0			V
Output voltage L level (1)	V _{OH}	I _{OH} =-1.6mA, *4			0.4	V
Output voltage H level (2)	V _{OL}	I _{OL} =0.4mA, *5	V _{DD} -1.0			V
Output voltage L level (2)	V _{OH}	I _{OH} =-1.6mA, *5			1.0	V

*1) Applicable to MD0 ~ MD7 terminals.

*2) Applicable to input terminals other than XI terminal.

*3) Applicable to XI terminal.



*4) Applicable to output terminals other than XO terminal.

*5) Applicable to XO terminal.

4. AC Characteristics

Parameter		Symbol	Min.	Typ.	Max.	Unit
XI	frequency	f_{XI}	11.0	12.288	13.0	MHz
XI	duty	D_{XI}		50		%
BCO	frequency	f_{BC}		$64f_{XI}$		Hz
BCO	ON/OFF time	t_{BCO}	180			ns
WC, SDO0, SDO1	output delay	t_{OD}	-40		40	ns
CSN	setup time	t_{CSS}	1/50fs			s
SCKN	ON/OFF time	t_{SCO}	1/50fs			s
CDI	setup time	t_{CDS}	1/100fs			s
CDI	hold time	t_{CDH}	1/100fs			s
CSN, SCKN	Transition time	t_{CST}			1/150fs	s

(Note) Load capacitance 30pF




5. Analog Characteristics

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Analog input voltage	VIA	Amplitude		4.70		V
Analog output voltage	VOA	Amplitude		4.70		V
DC offset voltage	Vc			2.5		V
Total harmonic distortion * 1	THD+N (1)	1kHz, 0dB		0.4	0.8	%
	THD+N (2)	1kHz, -30dB		0.6	1.2	%
Signal to noise ratio	S/N	S=0dB	80	85		dB

*1) LPF with fc=10kHz, 36dB/oct is used when OdB=4.70PP, A/D→D/A through.
*2) IHF-A is used when OdB=4.70VPP, A/D→D/A through.

■ EXTERNAL DIMENSIONS



Note) The specifications of this product are subject to improvement changes without prior notice.

IMPORTANT NOTICE

1. Yamaha reserves the right to make changes to its Products and to this document without notice. The information contained in this document has been carefully checked and is believed to be reliable. However, Yamaha assumes no responsibilities for inaccuracies and makes no commitment to update or to keep current the information contained in this document.
2. These Yamaha Products are designed only for commercial and normal industrial applications, and are not suitable for other uses, such as medical life support equipment, nuclear facilities, critical care equipment or any other application the failure of which could lead to death, personal injury or environmental or property damage. Use of the Products in any such application is at the customer's sole risk and expense.
3. YAMAHA ASSUMES NO LIABILITY FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES OR INJURY THAT MAY RESULT FROM MISAPPLICATION OR IMPROPER USE OR OPERATION OF THE PRODUCTS.
4. YAMAHA MAKES NO WARRANTY OR REPRESENTATION THAT THE PRODUCTS ARE SUBJECT TO INTELLECTUAL PROPERTY LICENSE FROM YAMAHA OR ANYTHIRD PARTY, AND YAMAHA MAKES NO WARRANTY OR REPRESENTATION OF NON-INFRINGEMENT WITH RESPECT TO THE PRODUCTS. YAMAHA SPECIFICALLY EXCLUDES ANY LIABILITY TO THE CUSTOMER OR ANY THIRD PARTY ARISING FROM OR RELATED TO THE PRODUCTS' INFRINGEMENT OF ANY THIRD PARTY'S INTELLECTUAL PROPERTY RIGHTS, INCLUDING THE PATENT, COPYRIGHT, TRADEMARK OR TRADE SECRET RIGHTS OF ANY THIRD PARTY.
5. EXAMPLES OF USE DESCRIBED HEREIN ARE MERELY TO INDICATE THE CHARACTERISTICS AND PERFORMANCE OF YAMAHA PRODUCTS. YAMAHA ASSUMES NO RESPONSIBILITY FOR ANY INTELLECTUAL PROPERTY CLAIMS OR OTHER PROBLEMS THAT MAY RESULT FROM APPLICATIONS BASED ON THE EXAMPLES DESCRIBED HEREIN. YAMAHA MAKES NO WARRANTY WITH RESPECT TO THE PRODUCTS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR USE AND TITLE.

AGENCY

YAMAHA CORPORATION

**Address inquiries to:
Semiconductor Sales & Marketing Department**

- Head Office 203, Matsunokijima, Toyooka-mura,
Iwata-gun, Shizuoka-ken, 438-0192
Tel. +81-539-62-4918 Fax. +81-539-62-5054
- Tokyo Office 2-17-11, Takanawa, Minato-ku,
Tokyo, 108-8568
Tel. +81-3-5488-5431 Fax. +81-3-5488-5088
- Osaka Office Namba Tsujimoto Nissei Bldg. 4F
1-13-17, Namba Naka, Naniwa-ku,
Osaka City, Osaka, 556-0011
Tel. +81-6-6633-3690 Fax. +81-6-6633-3691
- U.S.A. Office YAMAHA Systems Technology
100 Century Center Court, San Jose,
CA 95112
Tel. +1-408-467-2300 Fax. +1-408-437-8791

YAMAHA LSI

APPLICATION NEWS

No. : AN 079

Date of Issue : 1995. 8. 1

Device Name : YSS220 (SP3)

YAMAHA CORPORATION


Semi-conductor Sales Department

Sales Engineering Section

YSS220 (SP3) MICROPROCESSOR INTERFACE

■ ADDITIONAL SPECIFICATION

● Data transmission to discontinuous address



When sending the data to the discontinuous address, it is necessary to set the timing as shown above.