





“Ecoline Series 504”
PLCC sockets are designed for JEDEC type substrates and will operate safely under normal to moderately severe conditions

Bottom cover is designed to minimize danger of flux wicking and brown PPS insulator (RYTON R-4) with ventilation zone underneath component greatly improves heat dissipation



Plating	Stamped contacts
99	tin-lead over nickel Please note: 99 is the only plating available for this product.

Ordering information

For standard part numbers please refer to table Order Codes

For PCB hole patterns see page 94

No. of poles	Order Codes		Dimensions						
			A ₁	A ₂	B ₁	B ₂	C ₁	C ₂	E
20	504-99-020-24-000		15.56	15.56	5.08	5.08	9.62	9.62	18.06
28	504-99-028-24-000		18.10	18.10	7.62	7.62	11.90	11.90	21.70
32*	504-99-032-24-000		18.10	20.64	7.62	10.16	11.84	14.40	23.70
44	504-99-044-24-000		23.18	23.18	12.70	12.70	17.00	17.00	28.50
52	504-99-052-24-000		25.72	25.72	15.24	15.24	19.50	19.50	32.46
68	504-99-068-24-000		30.80	30.80	20.32	20.32	24.65	24.65	39.94
84	504-99-084-24-000		35.88	35.88	25.40	25.40	29.65	29.65	47.00
100	504-99-100-24-000		not available from stock, please consult						
	* rectangular								