

NC7SP74

TinyLogic® ULP D-Type Flip-Flop with Preset and Clear

General Description

The NC7SP74 is a single D-type CMOS Flip-Flop with preset and clear from Fairchild's Ultra Low Power (ULP) Series of TinyLogic®. Ideal for applications where battery life is critical, this product is designed for ultra low power consumption within the V_{CC} operating range of 0.9V to 3.6V.

The internal circuit is composed of a minimum of inverter stages including the output buffer, to enable ultra low static and dynamic power.

The NC7SP74, for lower drive requirements, is uniquely designed for optimized power and speed, and is fabricated with an advanced CMOS technology to achieve best in class speed operation while maintaining extremely low CMOS power dissipation.

The signal level applied to the D input is transferred to the Q output during the positive going transition of the CLK pulse.


Features

- Space saving US8 surface mount package
- MicroPak™ leadless package
- 0.9V to 3.6V V_{CC} supply operation
- 3.6V overvoltage tolerant I/Os at V_{CC} from 0.9V to 3.6V
- t_{PD}
 - 3.0 ns typ for 3.0V to 3.6V V_{CC}
 - 4.0 ns typ for 2.3V to 2.7V V_{CC}
 - 5.0 ns typ for 1.65V to 1.95V V_{CC}
 - 6.0 ns typ for 1.40V to 1.60V V_{CC}
 - 9.0 ns typ for 1.10V to 1.30V V_{CC}
 - 24.0 ns typ for 0.90V V_{CC}
- Power-Off high impedance inputs and outputs
- Static Drive (I_{OH}/I_{OL})
 - ±2.6 mA @ 3.00V V_{CC}
 - ±2.1 mA @ 2.30V V_{CC}
 - ±1.5 mA @ 1.65V V_{CC}
 - ±1.0 mA @ 1.40V V_{CC}
 - ±0.5 mA @ 1.10V V_{CC}
 - ±20 μ A @ 0.9V V_{CC}
- Uses patented Quiet Series™ noise/EMI reduction circuitry
- Ultra low dynamic power

Ordering Code:

Order Number	Package Number	Product Code Top Mark	Package Description	Supplied As
NC7SP74K8X	MAB08A	P74	8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide	3k Units on Tape and Reel
NC7SP74L8X	MAC08A	X9	8-Lead MicroPak, 1.6 mm Wide	5k Units on Tape and Reel

Battery Life vs. V_{CC} Supply Voltage



TinyLogic ULP and ULP-A with up to 50% less power consumption can extend your battery life significantly.

$$\text{Battery Life} = (V_{\text{battery}} \cdot I_{\text{battery}} \cdot 9) / (P_{\text{device}}) / 24 \text{hrs/day}$$

$$\text{Where, } P_{\text{device}} = (I_{CC} \cdot V_{CC}) + (C_{PD} + C_L) \cdot V_{CC}^2 \cdot f$$

Assumes ideal 3.6V Lithium Ion battery with current rating of 900mAh and derated 90% and device frequency at 10MHz, with $C_L = 15$ pF load

TinyLogic® is a registered trademark of Fairchild Semiconductor Corporation.

MicroPak™ and Quiet Series™ are trademarks of Fairchild Semiconductor Corporation.

Pin Descriptions

Pin Names	Description
D	Data Input
CK	Clock Pulse Input
$\overline{\text{CLR}}$	Direct Clear Input
Q, $\overline{\text{Q}}$	Flip-Flop Output
$\overline{\text{PR}}$	Direct Preset Input

Truth Table

Inputs				Outputs		Function
$\overline{\text{CLR}}$	$\overline{\text{PR}}$	D	CK	Q	$\overline{\text{Q}}$	
L	H	X	X	L	H	Clear
H	L	X	X	H	L	Preset
L	L	X	X	H	H	—
H	H	L	$\uparrow$	L	H	—
H	H	H	$\uparrow$	H	L	—
H	H	X	$\downarrow$	Q_n	$\overline{Q}_n$	No Change

H = HIGH Logic Level

L = LOW Logic Level


 Q_n = No change in data

X = Immaterial

Z = High Impedance


 $\uparrow$ = Rising Edge $\downarrow$ = Falling edge

Logic Symbol




Connection Diagrams

Pin Assignments for US8



(Top View)


Pin One Orientation Diagram



AAA represents Product Code Top Mark - see ordering code

Note: Orientation of Top Mark determines Pin One location. Read the top product code mark left to right, Pin One is the lower left pin (see diagram).

Pad Assignments for MicroPak



(Top Thru View)

Absolute Maximum Ratings(Note 1)

Supply Voltage (V_{CC})	-0.5V to +4.6V
DC Input Voltage (V_{IN})	-0.5V to +4.6V
DC Output Voltage (V_{OUT})	-0.5V to +7.0V
HIGH or LOW State (Note 2)	-0.5V to $V_{CC} + 0.5V$
$V_{CC} = 0V$	-0.5V to 4.6V
DC Input Diode Current (I_{IK}) $V_{IN} < 0V$	± 50 mA
DC Output Diode Current (I_{OK})	
$V_{OUT} < 0V$	-50 mA
$V_{OUT} > V_{CC}$	+50 mA
DC Output Source/Sink Current (I_{OH}/I_{OL})	± 50 mA
DC V_{CC} or Ground Current per	
Supply Pin (I_{CC} or Ground)	± 50 mA
Storage Temperature Range (T_{STG})	-65°C to +150°C

Recommended Operating Conditions (Note 3)

Power Supply	0.9V to 3.6V
Input Voltage (V_{IN})	0V to 3.6V
Output Voltage (V_{OUT})	
HIGH or LOW State	0V to V_{CC}
$V_{CC} = 0V$	0V to 3.6V
Output Current in (I_{OH}/I_{OL})	
$V_{CC} = 3.0V$ to 3.6V	± 2.6 mA
$V_{CC} = 2.3V$ to 2.7V	± 2.1 mA
$V_{CC} = 1.65V$ to 1.95V	± 1.5 mA
$V_{CC} = 1.40V$ to 1.60V	± 1.0 mA
$V_{CC} = 1.10V$ to 1.30V	± 0.5 mA
$V_{CC} = 0.9V$	± 20 μ A
Free Air Operating Temperature (T_A)	-40°C to +85°C
Minimum Input Edge Rate ($\Delta t/\Delta V$)	
$V_{IN} = 0.8V$ to 2.0V, $V_{CC} = 3.0V$	10 ns/V

Note 1: Absolute Maximum Ratings: are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 2: I_O Absolute Maximum rating must be observed.

Note 3: Unused inputs must be held HIGH or LOW. They may not float.

DC Electrical Characteristics

Symbol	Parameter	V_{CC} (V)	$T_A = +25^\circ\text{C}$		$T_A = -40^\circ\text{C to } +85^\circ\text{C}$		Units	Conditions
			Min	Max	Min	Max		
V_{IH}	HIGH Level Input Voltage	0.90		$0.65 \times V_{CC}$		$0.65 \times V_{CC}$	V	
		$1.10 \leq V_{CC} \leq 1.30$		$0.65 \times V_{CC}$		$0.65 \times V_{CC}$		
		$1.40 \leq V_{CC} \leq 1.60$		$0.65 \times V_{CC}$		$0.65 \times V_{CC}$		
		$1.65 \leq V_{CC} \leq 1.95$		$0.65 \times V_{CC}$		$0.65 \times V_{CC}$		
		$2.30 \leq V_{CC} \leq 2.70$		1.6		1.6		
V_{IL}	LOW Level Input Voltage	$3.00 \leq V_{CC} \leq 3.60$		2.1		2.1	V	
		0.90		$0.35 \times V_{CC}$		$0.35 \times V_{CC}$		
		$1.10 \leq V_{CC} \leq 1.30$		$0.35 \times V_{CC}$		$0.35 \times V_{CC}$		
		$1.40 \leq V_{CC} \leq 1.60$		$0.35 \times V_{CC}$		$0.35 \times V_{CC}$		
		$1.65 \leq V_{CC} \leq 1.95$		$0.35 \times V_{CC}$		$0.35 \times V_{CC}$		
V_{OH}	HIGH Level Output Voltage	$2.30 \leq V_{CC} \leq 2.70$		0.7		0.7	V	$I_{OH} = -20 \mu\text{A}$
		$3.00 \leq V_{CC} \leq 3.60$		0.9		0.9		
		0.90	$V_{CC} - 0.1$		$V_{CC} - 0.1$			
		$1.10 \leq V_{CC} \leq 1.30$	$V_{CC} - 0.1$		$V_{CC} - 0.1$			
		$1.40 \leq V_{CC} \leq 1.60$	$V_{CC} - 0.1$		$V_{CC} - 0.1$			
		$1.65 \leq V_{CC} \leq 1.95$	$V_{CC} - 0.1$		$V_{CC} - 0.1$			
		$2.30 \leq V_{CC} \leq 2.70$	$V_{CC} - 0.1$		$V_{CC} - 0.1$			
		$3.00 \leq V_{CC} \leq 3.60$	$V_{CC} - 0.1$		$V_{CC} - 0.1$			
		$1.10 \leq V_{CC} \leq 1.30$	$0.75 \times V_{CC}$		$0.70 \times V_{CC}$			$I_{OH} = -0.5 \text{ mA}$
		$1.40 \leq V_{CC} \leq 1.60$	1.07		0.99			$I_{OH} = -1.0 \text{ mA}$
		$1.65 \leq V_{CC} \leq 1.95$	1.24		1.22			$I_{OH} = -1.5 \text{ mA}$
		$2.30 \leq V_{CC} \leq 2.70$	1.95		1.87			$I_{OH} = -2.1 \text{ mA}$
		$3.00 \leq V_{CC} \leq 3.60$	2.61		2.55			$I_{OH} = -2.6 \text{ mA}$

DC Electrical Characteristics (Continued)


Symbol	Parameter	V _{CC} (V)	T _A = +25°C		T _A = −40°C to +85°C		Units	Conditions
			Min	Max	Min	Max		
V _{OL}	LOW Level Output Voltage	0.90		0.1		0.1	V	I _{OL} = 20 μA
		1.10 ≤ V _{CC} ≤ 1.30		0.1		0.1		
		1.40 ≤ V _{CC} ≤ 1.60		0.1		0.1		
		1.65 ≤ V _{CC} ≤ 1.95		0.1		0.1		
		2.30 ≤ V _{CC} ≤ 2.70		0.1		0.1		
		3.00 ≤ V _{CC} ≤ 3.60		0.1		0.1		
		1.10 ≤ V _{CC} ≤ 1.30	0.30 × V _{CC}		0.30 × V _{CC}			I _{OL} = 0.5 mA
		1.40 ≤ V _{CC} ≤ 1.60	0.31		0.37			I _{OL} = 1.0 mA
		1.65 ≤ V _{CC} ≤ 1.95	0.31		0.35			I _{OL} = 1.5 mA
		2.30 ≤ V _{CC} ≤ 2.70	0.31		0.33			I _{OL} = 2.1 mA
		3.00 ≤ V _{CC} ≤ 3.60	0.31		0.33			I _{OL} = 2.6 mA
I _{IN}	Input Leakage Current	0.90 to 3.60	±0.1		±0.5		μA	0 ≤ V _I ≤ 3.6V
I _{OFF}	Power Off Leakage Current	0	0.5		0.5		μA	0 ≤ (V _I , V _O) ≤ 3.6V
I _{CC}	Quiescent Supply Current	0.90 to 3.60	0.9		0.9		μA	V _I = V _{CC} or GND

AC Electrical Characteristics (10pF, 1MΩ)										
Symbol	Parameter	V _{CC} (V)	T _A = +25°C			T _A = −40°C to +85°C		Units	Conditions	Figure Number
			Min	Typ	Max	Min	Max			
f _{MAX}	Maximum Clock Frequency	0.90	50 40.0			50 150		MHz	C _L = 10 pF R _D = 1 MΩ	Figures 1, 5
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								
t _{PLH} t _{PHL}	Propagation Delay CK to Q, $\overline{Q}$	0.90	4.0 15.0 22.0 2.0 9.0 13.0 1.5 7.0 11.0 1.0 5.0 8.0 1.0 4.0 7.0			3.5 31.0 1.5 14.0 1.0 13.0 0.8 9.0 0.5 8.0		ns	C _L = 10 pF R _D = 1 MΩ	Figures 1, 3
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								
t _{PLH} t _{PHL}	Propagation Delay $\overline{\text{CLR}}$, $\overline{\text{PR}}$, to Q, $\overline{Q}$	0.90	4.0 12.0 23.0 2.0 9.0 12.0 1.5 7.0 11.0 1.0 5.0 9.0 1.0 4.0 7.0			4.0 34.0 2.0 14.0 1.5 13.0 1.0 9.0 1.0 8.0		ns	C _L = 10 pF R _D = 1 MΩ	Figures 1, 3
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								
t _S	Setup Time, CK to D	0.90	7.0 10.0 3.0 2.0 1.5 1.0			7.0 3.0 2.0 1.5 1.0		ns	C _L = 10 pF R _D = 1 MΩ	Figures 1, 4
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								
t _H	Hold Time, CK to D	0.90	0.5 1.0 0.5 0.5 0.5 0.5			0.5 0.5 0.5 0.5 0.5		ns	C _L = 10 pF R _D = 1 MΩ	Figures 1, 4
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								
t _W	Pulse Width, CK, $\overline{\text{PR}}$, $\overline{\text{CLR}}$	0.90	5.0 5.0 3.0 2.5 2.5 2.0			5.0 3.0 2.5 2.5 2.0		ns	C _L = 10 pF R _D = 1 MΩ	Figures 1, 5
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								
t _{REC}	Recover Time $\overline{\text{CLR}}$, $\overline{\text{PR}}$ to CK	0.90	8.5 12.0 3.5 3.0 2.5 2.0			8.5 3.5 3.0 2.5 2.0		ns	C _L = 10 pF R _D = 1 MΩ	Figures 1, 4
		1.10 ≤ V _{CC} ≤ 1.30								
		1.40 ≤ V _{CC} ≤ 1.60								
		1.65 ≤ V _{CC} ≤ 1.95								
		2.30 ≤ V _{CC} ≤ 2.70								
		3.00 ≤ V _{CC} ≤ 3.60								

AC Electrical Characteristics (15pF, 1MΩ)								
Symbol	Parameter	V _{CC} (V)	T _A = +25°C			T _A = -40°C to +85°C		Figure Number
			Min	Typ	Max	Min	Max	
t _{MAX}	Maximum Clock Frequency	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	50 75 100 125 150	40.0		150 200 250 175 200	MHz	Figures 1, 5
t _{PLH} t _{PHL}	Propagation Delay CK to Q, $\overline{Q}$	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	5.0 3.0 2.0 1.5 1.0	27.0 16.0 10.0 7.0 4.0	23.0 14.0 11.0 8.0 7.0	4.5 34.0 2.5 16.0 2.0 13.0 1.0 9.0 0.5 8.0	ns	Figures 1, 3
t _{PLH} t _{PHL}	Propagation Delay $\overline{CLR}$, $\overline{PR}$, to Q, $\overline{Q}$	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	5.0 3.0 2.0 1.5 1.0	27.0 15.0 10.0 7.0 4.0	24.0 13.0 11.0 9.0 7.0	5.0 37.0 3.0 16.0 2.0 13.0 1.5 9.0 1.0 8.0	ns	Figures 1, 3
t _S	Setup Time, CK to D	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	7.0 3.0 2.0 1.5 1.0	10.0		7.0 3.0 2.0 1.5 1.0	ns	Figures 1, 4
t _H	Hold Time, CK to D	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	0.5 0.5 0.5 0.5 0.5	1.0		0.5 0.5 0.5 0.5 0.5	ns	Figures 1, 4
t _W	Pulse Width, CK, $\overline{PR}$, $\overline{CLR}$	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	5.0 3.0 2.5 2.5 2.0	5.0		5.0 3.0 2.5 2.5 2.0	ns	Figures 1, 5
t _{REC}	Recover Time $\overline{CLR}$, $\overline{PR}$ to CK	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	8.5 3.5 3.0 2.5 2.0	12.0		8.5 3.5 3.0 2.5 2.0	ns	Figures 1, 4


AC Electrical Characteristics (30pF, 1MΩ)										
Symbol	Parameter	V _{CC} (V)	T _A = +25°C			T _A = −40°C to +85°C		Units	Conditions	Figure Number
			Min	Typ	Max	Min	Max			
f _{MAX}	Maximum Clock Frequency	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	50 75 100 125 150	40.0		150 200 250 175 200		MHz	C _L = 30 pF R _D = 1 MΩ	Figures 1, 5
t _{PLH} t _{PHL}	Propagation Delay CK to Q, $\overline{Q}$	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	6.0 4.0 2.0 1.0 0.8	34.0 18.0 11.0 8.0 5.0	27.0 17.0 13.0 10.0 8.0	5.0 3.0 2.0 1.0 0.5	43.0 18.0 15.0 11.0 10.0	ns	C _L = 30 pF R _D = 1 MΩ	Figures 1, 3
t _{PLH} t _{PHL}	Propagation Delay CLR, $\overline{PR}$, to Q, $\overline{Q}$	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	6.0 4.0 2.0 1.0 0.8	34.0 17.0 11.0 8.0 5.0	28.0 16.0 13.0 9.0 8.0	5.5 3.5 2.5 1.5 1.0	46.0 18.0 15.0 11.0 10.0	ns	C _L = 30 pF R _D = 1 MΩ	Figures 1, 3
t _S	Setup Time, CK to D	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	7.0 3.0 2.0 1.5 1.0	10.0		7.0 3.0 2.0 1.5 1.0		ns	C _L = 30 pF R _D = 1 MΩ	Figures 1, 4
t _H	Hold Time, CK to D	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	0.5 0.5 0.5 0.5 0.5	1.0		0.5 0.5 0.5 0.5 0.5		ns	C _L = 30 pF R _D = 1 MΩ	Figures 1, 4
t _W	Pulse Width, CK, $\overline{PR}$, CLR	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	5.0 3.0 2.5 2.5 2.0	5.0		4.0 3.0 2.0 3.0 2.0		ns	C _L = 30 pF R _D = 1 MΩ	Figures 1, 5
t _{REC}	Recover Time $\overline{CLR}$, $\overline{PR}$ to CK	0.90 1.10 ≤ V _{CC} ≤ 1.30 1.40 ≤ V _{CC} ≤ 1.60 1.65 ≤ V _{CC} ≤ 1.95 2.30 ≤ V _{CC} ≤ 2.70 3.00 ≤ V _{CC} ≤ 3.60	8.5 3.5 3.0 2.5 2.0	12.0		8.5 3.5 3.0 2.5 2.0		ns	C _L = 30 pF R _D = 1 MΩ	Figures 1, 4
Capacitance										
Symbol	Parameter				Typ	Max	Units	Conditions		Figure Number
C _{IN}	Input Capacitance				2.0		pF	V _{CC} = 0V		
C _{OUT}	Output Capacitance				4.0		pF	V _{CC} = 0V		
C _{PD}	Power Dissipation Capacitance				8.0		pF	V _I = 0V or V _{CC} f = 10 MHz		Figure 2

AC Loading and Waveforms



C_L includes load and stray capacitance
Input PRR = 1.0 MHz; $t_w = 500$ ns

FIGURE 1. AC Test Circuit



CP Input = AC Waveform; $t_r = t_f = 2.5$ ns;
CP Input PRR = 10 MHz; Duty Cycle = 50%
D Input PRR = 5MHz; Duty Cycle = 50%

FIGURE 2. I_{CCD} Test Circuit




FIGURE 3. AC Waveforms




FIGURE 4. AC Waveforms









FIGURE 5. AC Waveforms

Physical Dimensions inches (millimeters) unless otherwise noted



LAND PATTERN RECOMMENDATION



DETAIL A


NOTES:

- A. CONFORMS TO JEDEC REGISTRATION MO-187
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- D. DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MAB08AREVC

8-Lead US8, JEDEC MO-187, Variation CA 3.1mm Wide
Package Number MAB08A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



Notes:

1. PACKAGE REGISTRATION WITH JEDEC IS ANTICIPATED
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y.14M-1994

MAC08AREVB

8-Lead MicroPak, 1.6 mm Wide
Package Number MAC08A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com