



Low Capacitance ESD Protection Diodes for High-Speed Data Interfaces

Features

- Transient protection for data lines as per IEC 61000-4-2 (ESD) 15 kV (air) 8 kV (contact) IEC 61000-4-5 (Lightning) see I_{PPM} below
- Small package for use in portable electronics



- High temperature soldering guaranteed: 260 °C/ 10 sec. at terminals
- Low capacitance for high speed data lines, cellular handsets, USB port protection, LAN equipment, peripherals

Mechanical Data

Case: SOT-23 Plastic Package

Molding Compound Flammability Rating: UL 94 V-0

Terminals: High temperature soldering guaranteed: 260 °C/10 sec. at terminals

Weight: 8 mg

Absolute Maximum Ratings

Ratings at 25 °C, ambient temperature unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Peak pulse power	8/20 μ s waveform	P_{PK}	300	W
ESD voltage	ESD per IEC 61000-4-2	V_{ESD}	>25	kV

Thermal Characteristics


Ratings at 25 °C, ambient temperature unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Operation temperature		T_J	- 55 to + 125	°C
Storage temperature		T_{stg} , T_{STG}	- 55 to + 150	°C


Electrical Characteristics

Part Number	Marking Code	V_{RWM}	$V_{BR(min)}$	$I_{R(max)}$	$V_{C(max)}^{1)}$		I_{PPM}	C_j Pin1 to Pin2 Pin3 NC
			@ $I_t = 1.0$ mA	@ V_{RWM}	$I_{PP} = 1.0$ A	$I_{PP} = 5.0$ A	$t_p = 8/20$ μ s	$V_R = 0$ V $f = 1$ MHz
		V	V	μ A	V		A	pF
GL05T	L05	5	6	20	9.8	11	17	5
GL12T	L12	12	13.3	1	19	24	12	5
GL15T	L15	15	16.7	1	24	33	10	5
GL24T	L24	24	26.7	1	43	55	5	5

Package Dimensions in Inches (mm)



Top View



17418



Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423