

ZXMP3A17E6


30V P-CHANNEL ENHANCEMENT MODE MOSFET

SUMMARY

$V_{(BR)DSS} = -30V$; $R_{DS(ON)} = 0.07\Omega$ $I_D = -4.0A$

DESCRIPTION

This new generation of TRENCH MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.




SOT23-6

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- SOT23-6 package

APPLICATIONS

- DC - DC Converters
- Power Management Functions
- Disconnect switches
- Motor control




ORDERING INFORMATION

DEVICE	REEL SIZE	TAPE WIDTH	QUANTITY PER REEL
ZXMP3A17E6TA	7"	8mm	3000 units
ZXMP3A17E6TC	13"	8mm	10000 units

DEVICE MARKING

- 317

PINOUT



Top View

ZXMP3A17E6

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DSS}	-30	V
Gate Source Voltage	V_{GS}	± 20	V
Continuous Drain Current $V_{GS}=10V$; $T_A=25^\circ C$ (b) $V_{GS}=10V$; $T_A=70^\circ C$ (b) $V_{GS}=10V$; $T_A=25^\circ C$ (a)	I_D	-4.0 -3.2 -3.2	A
Pulsed Drain Current (c)	I_{DM}	-14.4	A
Continuous Source Current (Body Diode) (b)	I_S	-2.5	A
Pulsed Source Current (Body Diode) (c)	I_{SM}	-14.4	A
Power Dissipation at $T_A=25^\circ C$ (a) Linear Derating Factor	P_D	1.1 8.8	W mW/ $^\circ C$
Power Dissipation at $T_A=25^\circ C$ (b) Linear Derating Factor	P_D	1.7 13.6	W mW/ $^\circ C$
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150	$^\circ C$

THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient (a)	$R_{\theta JA}$	113	$^\circ C/W$
Junction to Ambient (b)	$R_{\theta JA}$	73	$^\circ C/W$

NOTES


(a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions

(b) For a device surface mounted on FR4 PCB measured at $t \leq 5$ secs.

(c) Repetitive rating 25mm x 25mm FR4 PCB, $D = 0.05$, pulse width $10\mu s$ - pulse width limited by maximum junction temperature. Refer to Transient Thermal Impedance graph.

ZXMP3A17E6

CHARACTERISTICS



ZXMP3A17E6

ELECTRICAL CHARACTERISTICS (at $T_A = 25^\circ\text{C}$ unless otherwise stated).


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	-30			V	I _D =-250μA, V _{GS} =0V
Zero Gate Voltage Drain Current	I _{DSS}			-0.5	μA	V _{DS} =-30V, V _{GS} =0V
Gate-Body Leakage	I _{GSS}			100	nA	V _{GS} =±20V, V _{DS} =0V
Gate-Source Threshold Voltage	V _{GS(th)}	-0.8			V	I _D =-250μA, V _{DS} = V _{GS}
Static Drain-Source On-State Resistance (1)	R _{DS(on)}			0.070 0.110	Ω Ω	V _{GS} =-10V, I _D =-3.2A V _{GS} =-4.5V, I _D =-2.5A
Forward Transconductance (1)(3)	g _{fs}		6.4		S	V _{DS} =-15V, I _D =-3.2A
DYNAMIC (3)						
Input Capacitance	C _{iss}		630		pF	V _{DS} =-15V, V _{GS} =0V, f=1MHz
Output Capacitance	C _{oss}		113		pF	
Reverse Transfer Capacitance	C _{rss}		78		pF	
SWITCHING(2) (3)						
Turn-On Delay Time	t _{d(on)}		1.74		ns	V _{DD} = -15V, I _D =-1A R _G =6.0Ω, V _{GS} =-10V
Rise Time	t _r		2.87		ns	
Turn-Off Delay Time	t _{d(off)}		29.2		ns	
Fall Time	t _f		8.72		ns	
Gate Charge	Q _g		8.28		nC	V _{DS} =-15V, V _{GS} =-5V, I _D =-3.2A
Total Gate Charge	Q _g		15.8		nC	V _{DS} =-15V, V _{GS} =-10V, I _D =-3.2A
Gate-Source Charge	Q _{gs}		1.84		nC	
Gate-Drain Charge	Q _{gd}		2.8		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage (1)	V _{SD}		-0.85	-1.2	V	T _J =25°C, I _S =-2.5A, V _{GS} =0V
Reverse Recovery Time (3)	t _{rr}		19.5		ns	T _J =25°C, I _F =-1.7A, di/dt= 100A/μs
Reverse Recovery Charge (3)	Q _{rr}		16.3		nC	

NOTES

- (1) Measured under pulsed conditions. Width=300 μs . Duty cycle $\leq 2\%$.
 (2) Switching characteristics are independent of operating junction temperature.
 (3) For design aid only, not subject to production testing.


ZXMP3A17E6

TYPICAL CHARACTERISTICS




ZXMP3A17E6

TYPICAL CHARACTERISTICS




ZXMP3A17E6

PACKAGE OUTLINE



PAD LAYOUT DETAILS



CONTROLLING DIMENSIONS IN MILLIMETRES APPROX CONVERSIONS INCHES.

PACKAGE DIMENSIONS

DIM	Millimetres		Inches		DIM	Millimetres		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	0.90	1.45	0.35	0.057	E	2.60	3.00	0.102	0.118
A1	0.00	0.15	0	0.006	E1	1.50	1.75	0.059	0.069
A2	0.90	1.30	0.035	0.051	L	0.10	0.60	0.004	0.002
b	0.35	0.50	0.014	0.019	e	0.95 REF		0.037 REF	
C	0.09	0.20	0.0035	0.008	e1	1.90 REF		0.074 REF	
D	2.80	3.00	0.110	0.118	L	0°	10°	0°	10°

© Zetex plc 2002

Europe	Americas	Asia Pacific
Zetex plc Fields New Road Chadderton Oldham, OL9 8NP United Kingdom Telephone (44) 161 622 4422 Fax: (44) 161 622 4420 uk.sales@zetex.com	Zetex GmbH Streitfeldstraße 19 D-81673 München Germany Telefon: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europe.sales@zetex.com	Zetex (Asia) Ltd 3701-04 Metroplaza, Tower 1 Hing Fong Road Kwai Fong Hong Kong Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com

PROVISIONAL ISSUE C - AUGUST 2002

