

ESD NOISE CLIPPING DIODE

NNCD5.6J to NNCD36J

ELECTROSTATIC DISCHARGE NOISE CLIPPING DIODE

2-PIN ULTRA SUPER MINI MOLD (FLAT TYPE)

★ DESCRIPTION

These products are a diode developed for ESD (Electrostatic Discharge) absorption. Based on the IEC-61000-4-2 test on electromagnetic interference (EMI), the diode assures an endurance, thus making itself most suitable for external interface circuit protection.

These products are can cope with more high density assembling.

FEATURES

- ★ Base on the electrostatic discharge immunity test (IEC 61000-4-2), the product assures the minimum endurance.
- Mounted in the ultra super mini mold (flat) package, the product can achieve high density and automatic packaging.


APPLICATIONS

- External interface circuit ESD absorption.
- Circuits for waveform clipper, surge absorber

MAXIMUM RATINGS (T_A = 25°C)

Item	Symbol	Rating	Unit	Remark
Power Dissipation	P	150	mW	Total
Surge Reverse Power	P _{RSM}	85 (t = 10 μs, 1 pulse)	W	
Junction Temperature	T _j	150	°C	
Storage Temperature	T _{stg}	-55 to +150	°C	

PACKAGE DRAWING (Unit: mm)



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.
Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.

ELECTRICAL CHARACTERISTICS (T_A = 25°C)


TYPE No.	Breakdown Voltage ^{Note1}			Capacitance		Reverse Leakage		ESD Voltage ^{Note2}	
	V _{BR} (V)			C _i (pF)		I _R (μA)		(kV)	
	MIN.	MAX.	I _T (mA)	TYP.	Condition	MAX.	V _R (V)	MIN.	I _T (mA)
NNCD5.6J	5.3	6.3	5	110	V _R = 0 V f = 1 MHz	5	2.5	30	C = 150 pF R = 330 Ω Contact discharge
NNCD6.8J	6.2	7.1	5	90		2	3.5	30	
NNCD8.2J	7.7	8.7	5	70		2	5.0	30	
NNCD10J	9.0	11.0	5	55		2	7.0	30	
NNCD16J	15.0	17.0	5	30		2	12.0	30	
NNCD18J	16.2	19.8	5	25		2	13.0	23	
NNCD24J	22.0	26.0	5	20		2	19.0	15	
NNCD36J	34.0	38.0	2	15		2	27.0	12	

Notes 1. Tested with pulse (40 ms)

2. Based upon with IEC 61000-4-2


TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

Figure 1. POWER DISSIPATION vs. AMBIENT TEMPERATURE



★

Figure 2. I_T - V_{BR} CHARACTERISTICS



★

Figure 3. C_t - V_R CHARACTERISTICS




Figure 4. SURGE REVERSE POWER RATINGS





Figure 5. TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS



Remark When using ceramic board of 10 x 7.5 x 0.75 mm (Cu film 11 x 2 x 0.035 mm)

- **The information in this document is current as of January, 2005. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**
- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".
 The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.
 "Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.
 "Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).
 "Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).