



## STANDARD CAPACITANCE TVS ARRAY

### APPLICATIONS

- ✓ Low Frequency I/O Ports
- ✓ RS-232 & RS-423 Data Lines
- ✓ Power Bus Lines
- ✓ Monitoring & Industrial Signal and Data Ports
- ✓ Microprocessor Based Equipment

### IEC COMPATIBILITY (EN61000-4)


- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns
- ✓ 61000-4-5 (Surge): 24A, 8/20μs Level 2 (Line-Ground) & Level 3 (Line-Line)

### FEATURES

- ✓ 800 Watts Peak Pulse Power per Line (tp=8/20μs)
- ✓ Unidirectional & Bidirectional Configuration
- ✓ ESD Protection > 40 kilovolts
- ✓ Available in 5V, 12V, 15V & 24V
- ✓ Standard Dual-In-Line Package
- ✓ Protects 8 to 12 Lines


### MECHANICAL CHARACTERISTICS

- ✓ Molded 16 Pin Dual-In-Line (DIP) Package
- ✓ Weight 1.2 grams (Approximate)
- ✓ Flammability rating UL 94V-0
- ✓ Packaging: 25 Pieces Per Tube
- ✓ Marking: Logo, Part Number, Date Code & Pin One Defined By Dot on Top of Package




## PIN CONFIGURATIONS

### UNIDIRECTIONAL



### BIDIRECTIONAL



## DEVICE CHARACTERISTICS


| MAXIMUM RATINGS @ 25°C Unless Otherwise Specified     |           |                |       |
|-------------------------------------------------------|-----------|----------------|-------|
| PARAMETER                                             | SYMBOL    | VALUE          | UNITS |
| Peak Pulse Power ( $t_p = 8/20\mu s$ ) - See Figure 1 | $P_{PP}$  | 800            | Watts |
| Operating Temperature                                 | $T_j$     | -55°C to 150°C | °C    |
| Storage Temperature                                   | $T_{STG}$ | -55°C to 150°C | °C    |
| Forward Surge Rating (See Note 1)                     | $I_F$     | 10             | Amps  |

| ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified |                                                  |                                                               |                                                                                 |                                                                                  |                                                               |                                                       |
|-----------------------------------------------------------------------|--------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------|----------------------------------------------------------------------------------|---------------------------------------------------------------|-------------------------------------------------------|
| PART NUMBER<br>(See Note 1)                                           | RATED STAND-OFF VOLTAGE<br><br>$V_{WM}$<br>VOLTS | MINIMUM BREAKDOWN VOLTAGE<br><br>@ 1mA<br>$V_{(BR)}$<br>VOLTS | MAXIMUM CLAMPING VOLTAGE<br>(See Fig. 2)<br><br>@ $I_P = 10A$<br>$V_C$<br>VOLTS | MAXIMUM CLAMPING VOLTAGE<br>(See Fig. 2)<br><br>@ 8/20 $\mu s$<br>$V_C @ I_{PP}$ | MAXIMUM LEAKAGE CURRENT<br><br>@ $V_{WM}$<br>$I_D$<br>$\mu A$ | TYPICAL CAPACITANCE<br><br>@ 0V, 1 MHz<br>$C_j$<br>pF |
| DA05N                                                                 | 5.0                                              | 6.0                                                           | 12.5                                                                            | 24.6V @ 45A                                                                      | 200                                                           | 880                                                   |
| DA12N                                                                 | 12.0                                             | 13.3                                                          | 26.0                                                                            | 32.9V @ 34A                                                                      | 2                                                             | 440                                                   |
| DA15N                                                                 | 15.0                                             | 16.7                                                          | 33.0                                                                            | 37.7V @ 27A                                                                      | 2                                                             | 400                                                   |
| DA24N                                                                 | 24.0                                             | 26.7                                                          | 52.1                                                                            | 48.5V @ 22A                                                                      | 2                                                             | 275                                                   |
| DA05P                                                                 | 5.0                                              | 6.0                                                           | 12.5                                                                            | 24.6V @ 45A                                                                      | 200                                                           | 880                                                   |
| DA12P                                                                 | 12.0                                             | 13.3                                                          | 26.0                                                                            | 32.9V @ 34A                                                                      | 2                                                             | 440                                                   |
| DA15P                                                                 | 15.0                                             | 16.7                                                          | 33.0                                                                            | 37.7V @ 27A                                                                      | 2                                                             | 400                                                   |
| DA24P                                                                 | 24.0                                             | 26.7                                                          | 52.1                                                                            | 48.5V @ 22A                                                                      | 2                                                             | 275                                                   |
| DA05CN                                                                | 5.0                                              | 6.0                                                           | 12.5                                                                            | 24.6V @ 45A                                                                      | 200                                                           | 500                                                   |
| DA12CN                                                                | 12.0                                             | 13.3                                                          | 26.0                                                                            | 32.9V @ 34A                                                                      | 2                                                             | 385                                                   |
| DA15CN                                                                | 15.0                                             | 16.7                                                          | 33.0                                                                            | 37.7V @ 27A                                                                      | 2                                                             | 300                                                   |
| DA24CN                                                                | 24.0                                             | 26.7                                                          | 52.1                                                                            | 48.5V @ 22A                                                                      | 2                                                             | 200                                                   |
| DA05CP                                                                | 5.0                                              | 6.0                                                           | 12.5                                                                            | 24.6V @ 45A                                                                      | 200                                                           | 500                                                   |
| DA12CP                                                                | 12.0                                             | 13.3                                                          | 26.0                                                                            | 32.9V @ 34A                                                                      | 2                                                             | 385                                                   |
| DA15CP                                                                | 15.0                                             | 16.7                                                          | 33.0                                                                            | 37.7V @ 27A                                                                      | 2                                                             | 300                                                   |
| DA24CP                                                                | 24.0                                             | 26.7                                                          | 52.1                                                                            | 48.5V @ 22A                                                                      | 2                                                             | 200                                                   |


**Note 1:** The "C" suffix specifies a bidirectional device, such as DA05CN or DA12CP.

GRAPHS


**FIGURE 1**  
**PEAK PULSE POWER VS PULSE TIME**



**FIGURE 2**  
**PULSE WAVE FORM**




**FIGURE 3**  
**POWER DERATING CURVE**




## PACKAGE OUTLINE & DIMENSIONS

### PACKAGE OUTLINE



### 16 PIN DIP



### DIMENSIONS

| DIM | MILLIMETERS |          | INCHES    |           |
|-----|-------------|----------|-----------|-----------|
|     | MIN         | MAX      | MIN       | MAX       |
| A   | -           | 19.8     | -         | 0.780     |
| B   | 6.10        | 6.60     | 0.240     | 0.260     |
| C   | 7.37        | 7.87     | 0.290     | 0.310     |
| D   | 0.25        | 0.50     | 0.010     | 0.020     |
| E   | 0°          | 10°      | 0°        | 10°       |
| F   | 0.51        | -        | 0.020     | -         |
| G   | -           | 5.08     | -         | 0.200     |
| H   | 3.17        | -        | 0.125     | -         |
| I   | -           | 1.78     | -         | 0.070     |
| J   | 0.84 TYP    | 0.84 TYP | 0.033 TYP | 0.033 TYP |
| K   | 0.38        | 0.53     | 0.015     | 0.021     |
| L   | 2.54 TYP    | 2.54 TYP | 0.100 TYP | 0.100 TYP |

#### NOTES:

1. Dimensions are exclusive of mold flash and metal burrs.

#### BULK ORDERING NOMENCLATURE:

1. No Suffix = Product Shipped in Tubes of 25 pcs per Tube.

Outline & Dimensions: Rev 1 - 11/01, 06003

COPYRIGHT © ProTek Devices 2005

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

#### ProTek Devices

2929 South Fair Lane, Tempe, AZ 85282

Tel: 602-431-8101 Fax: 602-431-2288

E-Mail: [sales@protekdevices.com](mailto:sales@protekdevices.com)

Web Site: [www.protekdevices.com](http://www.protekdevices.com)