


### DO-35(GLASS)

#### Features

- Low capacitance. ( $C = 3.0\text{pF max}$ )
- Short reverse recovery time. ( $t_{rr} = 8.0\text{ns max}$ )
- High reliability with glass seal.

#### Mechanical Data

- Case: DO-35, glass case
- Polarity: Color band denotes cathode
- Weight: 0.004 ounces, 0.13 grams



Dimensions in millimeters

#### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )


| Characteristic                            | Symbol      | Value       | Unit             |
|-------------------------------------------|-------------|-------------|------------------|
| Peak reverse voltage                      | $V_{RM}$    | 35          | V                |
| Reverse voltage                           | $V_R$       | 30          | V                |
| Peak forward current                      | $I_{FM}$    | 450         | mA               |
| Non-Repetitive peak forward surge current | $I_{FSM}^*$ | 1           | A                |
| Average forward current                   | $I_O$       | 150         | mA               |
| Power dissipation                         | $P_d$       | 250         | mW               |
| Junction temperature                      | $T_j$       | 175         | $^\circ\text{C}$ |
| Storage temperature                       | $T_{stg}$   | -65 to +175 | $^\circ\text{C}$ |

Note: Within 1s forward surge current.


#### Electrical Characteristics ( $T_a = 25^\circ\text{C}$ )

| Characteristic        | Symbol     | Min  | Typ | Max  | Unit          | Test Condition                                    |
|-----------------------|------------|------|-----|------|---------------|---------------------------------------------------|
| Forward voltage       | $V_F$      | 0.64 | —   | 0.80 | V             | $I_F = 10\text{mA}$                               |
| Reverse current       | $I_R$      | —    | —   | 0.1  | $\mu\text{A}$ | $V_R = 30\text{V}$                                |
| Capacitance           | $C$        | —    | —   | 3.0  | pF            | $V_R = 1\text{V}$ , $f = 1\text{MHz}$             |
| Reverse recovery time | $t_{rr}^*$ | —    | —   | 8.0  | ns            | $I_F = I_R = 10\text{mA}$ , $I_{rr} = 1\text{mA}$ |


Note: Reverse recovery time test circuit



**Fig.1 Forward current Vs. Forward voltage**



**Fig.2 Reverse current Vs. Reverse voltage**



**Fig.3 Capacitance Vs. Reverse voltage**