

TWO-CHANNEL EMI FILTER FOR AUDIO SPEAKER/AVIF CONNECTOR


Check for Samples: [TPD2F702](#)

FEATURES

- Two-Channel EMI Filter for Audio Speaker or AVIF Ports
- Best in class EMI Noise Filtering for Audio Applications (-3dB Bandwidth = 1.2MHz)
- > 50 dB Crosstalk Attenuation at 100 MHz
- Integrated ESD Protection Exceeds IEC61000-4-2 (Level 4) at the Connector Ports (Level 4) on the Connector Side
 - ±15-kV Human-Body Model (HBM)
 - ±30-kV IEC 61000-4-2 Contact Discharge
 - ±30-kV IEC 61000-4-2 Air-Gap Discharge
- Pi-Style (C-R-C) Filter Configuration (C1 = 30 pF, R = 15 Ω, C2 = 5000 pF)
- Ultra Low Leakage Current (100-nA max)
- Space-Saving WCSP Package and Flow-Through Pin Mapping
- Industrial Temperature Range: –40°C to 85°C

APPLICATIONS

- Mobile Phones
- PDAs
- Headsets
- Portable Gaming



TERMINAL ASSIGNMENTS

	1	2
A	Ch 1 Input, ESD Level 1	Ch 1 Output, ESD Level 4
B	Depopulated Ball	Ground
C	Ch 2 Input, ESD Level 1	Ch 2 Output, ESD Level 4

DESCRIPTION/ORDERING INFORMATION

The TPD2F702 is a two-channel EMI filter for audio interface applications. With the integration of 5000 pF capacitor in a space saving low noise WCSP package, the TPD2F702 offers superior EMI noise suppression (2MHz to 6GHz) compared to discrete implementation. The device is optimized for AVIF connector or speaker port interfaces. This low-pass filter array also provides system level ESD protection to eliminate the need for external ESD clamps. The TPD2F702 exceeds ±30-kV ratings per IEC6100-4-2 Contact and Air-Gap specifications. It is primarily used in the mobile-phone audio headphone speaker interface, but can be used in other audio applications.

The TPD2F702 is a highly integrated device designed to suppress EMI/RFI noise in all systems subjected to electromagnetic interferences. This filter includes ESD protection circuitry which prevents damage to the application when subjected to ESD surges far exceeding IEC 61000-4-2 (Level 4).

The TPD2F702 is specified for –40°C to 85°C operation.




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

ORDERING INFORMATION

T _A	PACKAGE ^{(1) (2)}		ORDERABLE PART NUMBER	TOP-SIDE MARKING
–40°C to 85°C	WCSP – YFK	Tape and reel	TPD2F702YFKR	5V

- (1) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.
 (2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI Web site at www.ti.com.

**SCHEMATIC
(One of Two Channels)****ABSOLUTE MAXIMUM RATINGS⁽¹⁾**

over operating free-air temperature range (unless otherwise noted)

	MIN	MAX	UNIT
V _{IO} Continuous IO voltage	–5.5	5.5	V
Total power dissipation		200	mW
T _A Characterized free-air operating temperature range	–40	85	°C
Reflow temperature 1.6 mm (1/16 inch) from case for 10 seconds		260	°C

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rated conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING CONDITIONS

	MIN	MAX	UNIT
V _{IO} Continuous IO voltage	–5	5	V

ESD RATINGS

ESD TYPE	TERMINAL	TYP	UNIT
IEC 61000-4-2 Contact Discharge	Input	±4	kV
	Output	±30	
IEC 61000-4-2 Air-Gap Discharge	Input	±4	kV
	Output	±30	
Human-Body Model	Input	±15	kV
	Output	±15	

ELECTRICAL CHARACTERISTICS

 $T_A = -40^{\circ}\text{C}$ to 85°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
V_{BR}	DC break-down voltage	$I_I = 1\text{ mA}$	Input pin	± 14		± 18.2	V
		$I_O = 1\text{ mA}$	Output pin	± 14		± 18.2	
I_{IO}	Current from input or output	V_I or $V_O = 2.5\text{ V}$	Input, output pins		0.01	0.1	μA
C1	Capacitance of the input terminal	$V_I = 0\text{ V}$, $V_{OSC} = 30\text{ mV}$, $f = 100\text{ kHz}$	Input pin		30		pF
C2	Capacitance of the output terminal	$V_O = 0\text{ V}$, $V_{OSC} = 30\text{ mV}$, $f = 100\text{ kHz}$	Output pin		5000		pF
R	Series resistor			12	15	18	Ω
R_{dyn}	Dynamic resistance	$I_I = 1.5\text{ A}$ or $I_O = 1.5\text{ A}$	Output clamp		1		Ω
			Input clamp		3		
f_C	Cut-off frequency	$Z_{SOURCE} = 50\ \Omega$, $Z_{LOAD} = 50\ \Omega$			1.2		MHz

TYPICAL OPERATING CHARACTERISTICS




Figure 1. Insertion Loss




Figure 2. Channel-to-Channel Crosstalk with 50 Ω Termination for the Non-Measuring Pins

TYPICAL OPERATING CHARACTERISTICS (continued)




Figure 3. Channel-to-Channel Crosstalk with No Termination for the Non-Measuring Pins




Figure 4. IO Capacitance Versus IO Voltage (Measured at $f = 100$ kHz)




Figure 5. IEC Clamping Waveforms +8 kV Contact, Out Stressed and In Measured




Figure 6. IEC Clamping Waveforms -8 kV Contact, Out Stressed and In Measured

TYPICAL OPERATING CHARACTERISTICS (continued)




Figure 7. IEC Clamping Waveforms +15 kV Contact, Out Stressed and In Measured





Figure 8. IEC Clamping Waveforms -15 kV Contact, Out Stressed and In Measured

TAPE AND REEL INFORMATION


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPD2F702YFKR	DSBGA	YFK	5	3000	180.0	8.4	1.02	1.42	0.62	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPD2F702YFKR	DSBGA	YFK	5	3000	190.5	212.7	31.8

YFK (R-XBGA-N5)

(CUSTOM) DIE-SIZE BALL GRID ARRAY



4210407/A 07/2009

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. NanoFree™ package configuration.
 - D. This is a Pb-free solder ball design.

NanoFree is a trademark of Texas Instruments.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DLP® Products	www.dlp.com	Communications and Telecom	www.ti.com/communications
DSP	dsp.ti.com	Computers and Peripherals	www.ti.com/computers
Clocks and Timers	www.ti.com/clocks	Consumer Electronics	www.ti.com/consumer-apps
Interface	interface.ti.com	Energy	www.ti.com/energy
Logic	logic.ti.com	Industrial	www.ti.com/industrial
Power Mgmt	power.ti.com	Medical	www.ti.com/medical
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
RFID	www.ti-rfid.com	Space, Avionics & Defense	www.ti.com/space-avionics-defense
RF/IF and ZigBee® Solutions	www.ti.com/lprf	Video and Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless-apps