

Part No.

NPAK-TRSO

Liquid trap with male Quick-test top port, Female Quick-test bottom port

Eliminates unwanted fluid or moisture that can contaminate any gas system.

Features

- Quick-release lid allows for easy cleaning of dirt or liquid without tools
- Entraps fluid and debris out of system to prevent blocking or plugging
- High pressure trap is ideal for pneumatic systems
- Compatible with all Ralston Instruments Quick-test hoses and adapters
- Comes with either only Quick-test ports (for use with Nitropak) or with both Quick-test ports and NPT top and bottom connections
- Made in U.S.A.



NPAK-TRSO

Item Includes

- Assembly - TRAP Assembly (TRAP)
- Top Connection - Male Quick-test, stainless steel (QTHA-3SS0)
- Bottom Connection - Female Quick-test, stainless steel (QTHA-3SSA-LD)

Specifications

Pressure Range	0 to 3000 psi (0 to 207 bar)
Temperature range	0 to 130 °F (-18 to 54 °C)
Construction	Anodized Aluminum, Stainless Steel
Seal materials	Buna-N, Teflon
Weight	1.139375 lb (0.5 kg)
Dimensions	H: 5.5 in (13.97 cm) x W: 2 in (5.08 cm) x D: 2 in (5.08 cm)