Rating	20A 12VDC
Contact Resistance	50m ohm max.
Insulation Resistance	DC 500V 100M ohm min.
Dielectric Strength	AC 1500V 1 minute
Operating Temperature	-20°C ~ 85°C

Mounting Hole



Thickness	X	Y
0.75 - 1.25	19.2 - 0.1	13.0 + 0.1
1.25 - 2.00	19.4 - 0.1	13.0 + 0.1
2.00 - 3.00	19.8 - 0.1	13.0 + 0.1

Circuit Diagram



SPST ON - OFF (LED)

LED RATING:
Red:@20mA, If=2.0VDC
Amber:@20mA, If=2.1VDC
Green:@20mA, If=2.2VDC

BASE COLOR: Black
BUTTON COLOR: Black
LED LENS: PC, Green



RoHS Compliant

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.

CW INDUSTRIES
Southampton, Pa. 18966
Tel 215.355.7080/www.cwind.com

Date Drawn: 12/17/09	Rev. 0	Unit: mm	Checked By: G. Guld
Title: ROCKER SWITCH		CW P/N: GRB066L02BBGGL1	