



Ceramic Capacitor Stacks



MODEL GFWQ



^{*} Dimensions in mm

DESIGN:

Ceramic capacitor stacks with solder tags

RATED VOLTAGE UR:

see table below

DIELECTRIC STRENGTH:

see table below (Test voltage between solder tags)

DISSIPATION FACTOR tan δ :

 $\leq 25 \cdot 10^{-3}$

INSULATION RESISTANCE Ris:

 \geq 1 • 10¹⁰ Ω (R 2005)

CATEGORY TEMPERATURE RANGE 9A:

(- 10 to + 85) °C

| MODEL | CAPACITANCE (pF) | TOLERANCE | RATED VOLTAGE* (KVp) | TEST VOLTAGE** (KV _{DC}) | CERAMIC DIELECTRIC | NO. OF DISCS IN SERIES | LENGTH L (mm/inches) | Ø D (mm/inches) |
|-----------|------------------|--------------------|----------------------------|--|-----------------------|------------------------------|-------------------------|-----------------------------|
| | | OF THE SINGLE DISC | | | | IN SERIES | | |
| GFMQ 1010 | 370 | °æ 20 % | 8 | 13 | R 2005 | 10 | 61/2.4 MAX. | 10.5 ± 0.3/ 0.41 ± 0.012 |
| GFWQ 1010 | | | | | | 10 | 61/2.4 MAX. | |
| GFMQ 1012 | | | | | | 12 | 74/2.91 MAX. | |
| GFWQ 1012 | | | | | | 12 | 74/2.91 MAX. | |
| GFMQ 1208 | | | | | | 8 | 51/2 MAX. | |
| GFWQ 1208 | | | | | | 8 | 51/2 MAX. | |
| GFMQ 1210 | 500 | °æ 20 % | 8 | 13 | R 2005 | 10 | 65/2.56 MAX. | 12.0 ± 0.2/ 0.47 ± 0.008 |
| GFWQ 1210 | | | | | | 10 | 65/2.56 MAX. | |
| GFMQ 1212 | | | | | | 12 | 74/2.91 MAX | |
| GFWQ 1212 | | | | | | 12 | 74/2.91 MAX | |

In an insulating environment

Other capacitance values and number of discs are available on request

| ORDERING INFORMATION | | | | | | | | | |
|----------------------|-------------------|--------|--------|--------|--|--|--|--|--|
| GFWQ 1212 | 8 KV _p | 500 pF | ± 20 % | R 2005 | | | | | |

Document Number: 22034 Revision: 10-Jun-05

^{**} Min. 3 s in an insulating liquid



Vishay

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Revision: 18-Jul-08

Document Number: 91000 www.vishay.com