

ERB05GGR & ERB05JGR

SINTERED GLASS JUNCTION
FAST SWITCHING PLASTIC RECTIFIER
VOLTAGE:400 & 600V **CURRENT: 0.5A**




FEATURE

High temperature metallurgically bonded construction
Sintered glass cavity free junction
Capability of meeting environmental standard of MIL-S-19500
High temperature soldering guaranteed
350°C /10sec/0.375"lead length at 5 lbs tension
Operate at Ta =55°C with no thermal run away
Typical Ir<0.1μA

MECHANICAL DATA

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO-41\DO-204AL



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	ERB05GGR	ERB05JGR	units
Maximum Recurrent Peak Reverse Voltage	Vrrm	400	600	V
Maximum RMS Voltage	Vrms	280	420	V
Maximum DC blocking Voltage	Vdc	400	600	V
Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C	If(av)	0.5		A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm	10.0		A
Maximum Forward Voltage at rated Forward Current and 25°C IF=0.5A	Vf	1.2		V
Maximum full load reverse current full cycle average at 55°C Ambient	Ir(av)	100.0		μA
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	Ir	5.0 100.0		μA μA
Maximum Reverse Recovery Time (Note 1)	Trr	150		nS
Typical Junction Capacitance (Note 2)	Cj	15.0		pF
Typical Thermal Resistance (Note 3)	R(ja)	55.0		°C /W
Storage and Operating Junction Temperature	Tstg, Tj	-65 to +175		°C

Note:

- Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A
- Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
- Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

RATINGS AND CHARACTERISTIC CURVES ERB05GGR & ERB05JGR

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE




FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE

