


LXG Series

- Endurance with ripple current : 105°C 5000 hours
- Non solvent-proof type
- Pb-free design




SPECIFICATIONS

Items	Characteristics								
Category	-40 to +105°C								
Temperature Range									
Rated Voltage Range	10 to 100V _{dc} (at 20°C, 120Hz)								
Capacitance Tolerance	±20% (M)								
Leakage Current	I=0.02CV or 3mA, whichever is smaller. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 5 minutes)								
Dissipation Factor (tanδ)	Rated voltage (V _{dc})	10V	16V	25V	35V	50V	63V	80 & 100V	
	tanδ (Max.)	0.60	0.45	0.30	0.25	0.20	0.15	0.15	(at 20°C, 120Hz)
Low Temperature Characteristics (Max. Impedance Ratio)	Capacitance change : Capacitance at the lowest operating temperature shall not be less than 70% of the 20°C value.								
	Rated voltage (V _{dc})	10V	16V	25V	35V	50V	63V	80 & 100V	
	Z(-25°C)/Z(+20°C)	4	4	3	3	2	2	2	
	Z(-40°C)/Z(+20°C)	15	15	10	8	6	6	5	(at 120Hz)
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with rated ripple current is applied for 5000 hours at 105°C.								
	Capacitance change	≤±25% of the initial value							
	D.F. (tanδ)	≤250% of the initial specified value							
	Leakage current	≤The initial specified value							
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 500 hours at 105°C without voltage applied.								
	Capacitance change	≤±20% of the initial value							
	D.F. (tanδ)	≤150% of the initial specified value							
	Leakage current	≤The initial specified value							

DIMENSIONS [mm]


- Terminal Code : VS (φ22 to φ35) : Standard




*φD=35mm : 3.5±0.5mm

No plastic disk is the standard design

- Terminal Code : LI (φ35)



PART NUMBERING SYSTEM



Please refer to "A guide to global code (snap-in type)"

RATED RIPPLE CURRENT MULTIPLIERS

- Frequency Multipliers

Frequency (Hz)	50	120	300	1k	10k	50k
10 to 50V _{dc}	0.95	1.00	1.03	1.05	1.08	1.08
63 to 100V _{dc}	0.92	1.00	1.07	1.13	1.19	1.20

◆STANDARD RATINGS

WV (Vdc)	Cap (μF)	Case size φD×L(mm)	tanδ	Rated ripple current (Arms/ 105°C,120Hz)	Part No.	WV (Vdc)	Cap (μF)	Case size φD×L(mm)	tanδ	Rated ripple current (Arms/ 105°C,120Hz)	Part No.
10	6800	22×25	0.60	1.30	ELXG100VSN682MP25S	35	5600	25.4×35	0.25	1.98	ELXG350VSN562MQ35S
	10000	22×30	0.60	1.65	ELXG100VSN103MP30S		5600	30×30	0.25	1.98	ELXG350VSN562MR30S
	10000	25.4×25	0.60	1.64	ELXG100VSN103MQ25S		5600	35×25	0.25	2.03	ELXG350VSN562MA25S
	12000	22×35	0.60	1.85	ELXG100VSN123MP35S		6800	22×50	0.25	2.26	ELXG350VSN682MP50S
	12000	25.4×30	0.60	1.85	ELXG100VSN123MQ30S		6800	25.4×40	0.25	2.24	ELXG350VSN682MQ40S
	12000	30×25	0.60	1.89	ELXG100VSN123MR25S		8200	25.4×50	0.25	2.57	ELXG350VSN822MQ50S
	15000	22×40	0.60	2.12	ELXG100VSN153MP40S		8200	30×35	0.25	2.50	ELXG350VSN822MR35S
	15000	25.4×35	0.60	2.16	ELXG100VSN153MQ35S		8200	35×30	0.25	2.55	ELXG350VSN822MA30S
	18000	22×50	0.60	2.45	ELXG100VSN183MP50S		10000	30×40	0.25	2.86	ELXG350VSN103MR40S
	18000	25.4×40	0.60	2.43	ELXG100VSN183MQ40S		10000	35×35	0.25	2.88	ELXG350VSN103MA35S
	18000	30×30	0.60	2.37	ELXG100VSN183MR30S		12000	30×50	0.25	3.32	ELXG350VSN123MR50S
	18000	35×25	0.60	2.42	ELXG100VSN183MA25S		12000	35×40	0.25	3.30	ELXG350VSN123MA40S
	22000	30×35	0.60	2.73	ELXG100VSN223MR35S		18000	35×50	0.25	4.29	ELXG350VSN183MA50S
	22000	35×30	0.60	2.79	ELXG100VSN223MA30S	50	1500	22×25	0.20	1.02	ELXG500VSN152MP25S
	27000	25.4×50	0.60	3.11	ELXG100VSN273MQ50S		1800	22×30	0.20	1.17	ELXG500VSN182MP30S
	27000	30×40	0.60	3.13	ELXG100VSN273MR40S		1800	25.4×25	0.20	1.17	ELXG500VSN182MQ25S
	33000	35×35	0.60	3.49	ELXG100VSN333MA35S		2200	22×35	0.20	1.33	ELXG500VSN222MP35S
	39000	30×50	0.60	3.99	ELXG100VSN393MR50S		2700	22×40	0.20	1.51	ELXG500VSN272MP40S
	39000	35×40	0.60	3.96	ELXG100VSN393MA40S		2700	25.4×30	0.20	1.47	ELXG500VSN272MQ30S
	47000	35×50	0.60	4.62	ELXG100VSN473MA50S		2700	30×25	0.20	1.50	ELXG500VSN272MR25S
16	5600	22×25	0.45	1.44	ELXG160VSN562MP25S		3300	25.4×35	0.20	1.70	ELXG500VSN332MQ35S
	6800	22×30	0.45	1.66	ELXG160VSN682MP30S		3300	30×30	0.20	1.70	ELXG500VSN332MR30S
	6800	25.4×25	0.45	1.66	ELXG160VSN682MQ25S		3300	35×25	0.20	1.74	ELXG500VSN332MA25S
	8200	22×35	0.45	1.87	ELXG160VSN822MP35S		3900	22×50	0.20	1.91	ELXG500VSN392MP50S
	10000	22×40	0.45	2.12	ELXG160VSN103MP40S		3900	25.4×40	0.20	1.89	ELXG500VSN392MQ40S
	10000	25.4×30	0.45	2.07	ELXG160VSN103MQ30S		4700	30×35	0.20	2.11	ELXG500VSN472MR35S
	10000	30×25	0.45	2.11	ELXG160VSN103MR25S		4700	35×30	0.20	2.16	ELXG500VSN472MA30S
	12000	25.4×35	0.45	2.37	ELXG160VSN123MQ35S		5600	25.4×50	0.20	2.38	ELXG500VSN562MQ50S
	12000	30×30	0.45	2.37	ELXG160VSN123MR30S		5600	30×40	0.20	2.39	ELXG500VSN562MR40S
	12000	35×25	0.45	2.42	ELXG160VSN123MA25S		5600	35×35	0.20	2.41	ELXG500VSN562MA35S
	15000	22×50	0.45	2.74	ELXG160VSN153MP50S		6800	30×50	0.20	2.79	ELXG500VSN682MR50S
	15000	25.4×40	0.45	2.71	ELXG160VSN153MQ40S		6800	35×40	0.20	2.78	ELXG500VSN682MA40S
	18000	25.4×50	0.45	3.11	ELXG160VSN183MQ50S	63	10000	35×50	0.20	3.57	ELXG500VSN103MA50S
	18000	30×35	0.45	3.02	ELXG160VSN183MR35S		1000	22×25	0.15	1.00	ELXG630VSN102MP25S
	18000	35×30	0.45	3.09	ELXG160VSN183MA30S		1200	22×30	0.15	1.15	ELXG630VSN122MP30S
	22000	30×40	0.45	3.46	ELXG160VSN223MR40S		1200	25.4×25	0.15	1.15	ELXG630VSN122MQ25S
	22000	35×35	0.45	3.49	ELXG160VSN223MA35S		1500	22×35	0.15	1.32	ELXG630VSN152MP35S
	27000	30×50	0.45	4.07	ELXG160VSN273MR50S		1800	22×40	0.15	1.49	ELXG630VSN182MP40S
	27000	35×40	0.45	4.04	ELXG160VSN273MA40S		1800	25.4×30	0.15	1.45	ELXG630VSN182MQ30S
	39000	35×50	0.45	5.16	ELXG160VSN393MA50S		1800	30×25	0.15	1.48	ELXG630VSN182MR25S
25	3900	22×25	0.30	1.31	ELXG250VSN392MP25S		2200	25.4×35	0.15	1.67	ELXG630VSN222MQ35S
	4700	22×30	0.30	1.51	ELXG250VSN472MP30S		2200	30×30	0.15	1.68	ELXG630VSN222MR30S
	4700	25.4×25	0.30	1.51	ELXG250VSN472MQ25S		2200	35×25	0.15	1.71	ELXG630VSN222MA25S
	5600	22×35	0.30	1.70	ELXG250VSN562MP35S		2700	22×50	0.15	1.92	ELXG630VSN272MP50S
	6800	22×40	0.30	1.92	ELXG250VSN682MP40S		2700	25.4×40	0.15	1.90	ELXG630VSN272MQ40S
	6800	25.4×30	0.30	1.87	ELXG250VSN682MQ30S		2700	30×35	0.15	1.93	ELXG630VSN272MR35S
	6800	30×25	0.30	1.90	ELXG250VSN682MR25S		3300	25.4×50	0.15	2.20	ELXG630VSN332MQ50S
	8200	25.4×35	0.30	2.14	ELXG250VSN822MQ35S		3300	35×30	0.15	2.18	ELXG630VSN332MA30S
	8200	30×30	0.30	2.15	ELXG250VSN822MR30S		3900	30×40	0.15	2.41	ELXG630VSN392MR40S
	8200	35×25	0.30	2.19	ELXG250VSN822MA25S		3900	35×35	0.15	2.43	ELXG630VSN392MA35S
	10000	22×50	0.30	2.45	ELXG250VSN103MP50S		4700	30×50	0.15	2.80	ELXG630VSN472MR50S
	10000	25.4×40	0.30	2.43	ELXG250VSN103MQ40S		4700	35×40	0.15	2.78	ELXG630VSN472MA40S
	12000	25.4×50	0.30	2.78	ELXG250VSN123MQ50S	80	6800	35×50	0.15	3.55	ELXG630VSN682MA50S
	12000	30×35	0.30	2.70	ELXG250VSN123MR35S		680	22×25	0.15	0.97	ELXG800VSN681MP25S
	12000	35×30	0.30	2.76	ELXG250VSN123MA30S		820	22×30	0.15	1.12	ELXG800VSN821MP30S
	15000	30×40	0.30	3.13	ELXG250VSN153MR40S		1000	22×35	0.15	1.27	ELXG800VSN102MP35S
	15000	35×35	0.30	3.16	ELXG250VSN153MA35S		1000	25.4×25	0.15	1.23	ELXG800VSN102MQ25S
	18000	30×50	0.30	3.64	ELXG250VSN183MR50S		1200	22×40	0.15	1.42	ELXG800VSN122MP40S
	18000	35×40	0.30	3.61	ELXG250VSN183MA40S		1200	25.4×30	0.15	1.39	ELXG800VSN122MQ30S
	27000	35×50	0.30	4.70	ELXG250VSN273MA50S		1200	30×25	0.15	1.41	ELXG800VSN122MR25S
35	2200	22×25	0.25	1.10	ELXG350VSN222MP25S		1500	25.4×35	0.15	1.62	ELXG800VSN152MQ35S
	3300	22×30	0.25	1.42	ELXG350VSN332MP30S		1800	22×50	0.15	1.84	ELXG800VSN182MP50S
	3300	25.4×25	0.25	1.41	ELXG350VSN332MQ25S		1800	25.4×40	0.15	1.82	ELXG800VSN182MQ40S
	3900	22×35	0.25	1.58	ELXG350VSN392MP35S		1800	30×30	0.15	1.78	ELXG800VSN182MR30S
	3900	25.4×30	0.25	1.58	ELXG350VSN392MQ30S		1800	35×25	0.15	1.82	ELXG800VSN182MA25S
	4700	22×40	0.25	1.78	ELXG350VSN472MP40S		2200	25.4×50	0.15	2.11	ELXG800VSN222MQ50S
	4700	30×25	0.25	1.77	ELXG350VSN472MR25S		2200	30×35	0.15	2.05	ELXG800VSN222MR35S

◆STANDARD RATINGS

WV (Vdc)	Cap (μF)	Case size φD×L(mm)	tanδ	Rated ripple current (Arms/ 105°C,120Hz)	Part No.
80	2200	35×30	0.15	2.09	ELXG800VSN222MA30S
	2700	30×40	0.15	2.35	ELXG800VSN272MR40S
	2700	35×35	0.15	2.37	ELXG800VSN272MA35S
	3300	30×50	0.15	2.75	ELXG800VSN332MR50S
	3300	35×40	0.15	2.73	ELXG800VSN332MA40S
	4700	35×50	0.15	3.46	ELXG800VSN472MA50S
100	390	22×25	0.15	0.78	ELXG101VSN391MP25S
	560	22×30	0.15	0.99	ELXG101VSN561MP30S
	560	25.4×25	0.15	0.98	ELXG101VSN561MQ25S
	680	22×35	0.15	1.12	ELXG101VSN681MP35S
	820	22×40	0.15	1.26	ELXG101VSN821MP40S
	820	25.4×30	0.15	1.23	ELXG101VSN821MQ30S
	820	30×25	0.15	1.25	ELXG101VSN821MR25S
WV (Vdc)	Cap (μF)	Case size φD×L(mm)	tanδ	Rated ripple current (Arms/ 105°C,120Hz)	Part No.
100	1000	25.4×35	0.15	1.41	ELXG101VSN102MQ35S
	1000	30×30	0.15	1.42	ELXG101VSN102MR30S
	1000	35×25	0.15	1.45	ELXG101VSN102MA25S
	1200	22×50	0.15	1.60	ELXG101VSN122MP50S
	1200	25.4×40	0.15	1.59	ELXG101VSN122MQ40S
	1200	30×35	0.15	1.61	ELXG101VSN122MR35S
	1500	25.4×50	0.15	1.86	ELXG101VSN152MQ50S
	1500	30×40	0.15	1.87	ELXG101VSN152MR40S
	1500	35×30	0.15	1.85	ELXG101VSN152MA30S
	1800	35×35	0.15	2.07	ELXG101VSN182MA35S
	2200	30×50	0.15	2.40	ELXG101VSN222MR50S
	2200	35×40	0.15	2.39	ELXG101VSN222MA40S
	2700	35×50	0.15	2.81	ELXG101VSN272MA50S

◆MAXIMUM IMPEDANCE [mΩ/20°C, 30kHz]

Case size φD×L (mm)	V _{dc}	10 to 63	80	100
22×25		120	150	
22×30		100	120	
22×35		80	95	
22×40		70	80	
22×50		50	60	
25.4×25		90	110	
25.4×30		70	85	
25.4×35		60	70	
25.4×40		50	60	
25.4×50		40	45	
30×25		70	80	
30×30		50	60	
30×35		40	50	
30×40		35	40	
30×50		25	30	
35×25		65	70	
35×30		45	50	
35×35		38	40	
35×40		30	30	
35×50		23	25	

●105°C Endurance with Rated Ripple Current

