

CTE9000 / CTU9000 Series

OEM pressure transmitters for industrial media



FEATURES

- 0...0.35 to 0...35 bar, 0...5 to 0...500 psi gage¹ or absolute¹⁰
- 0...10 V, 0.5...4.5 V, 0...5 V, 1...6 V or 4...20 mA output
- Field interchangeable
- For industrial use
- All welded stainless steel diaphragm construction

MEDIA COMPATIBILITY

Wetted materials:
stainless steel 1.4404 (316)⁹

Housing:
stainless steel, protection class IP 64 (according to DIN EN 60529) respectively NEMA 4X¹




SPECIFICATIONS^{11,12}

Maximum ratings


Supply voltage (reverse polarity protection)	
CTE(M)/CTU9...0	12...32 V
CTE(M)/CTU9...1, ...6, ...7	9...32 V
CTE(M)/CTU9...4 ²	9...32 V
Maximum load current (source)	
CTE(M)/CTU9...0, ...1, ...6, ...7	1 mA
Temperature limits	
Storage	-55 to 100°C
Operating	-40 to 100°C
Compensated	0 to 70°C
Humidity limits	0 - 98 %RH
Vibration (5 to 500 Hz)	10 g _{RMS}
Mechanical shock	50 g
Proof pressure ³	
CTEM9350...	1000 mbar
CTU9005...	15 psi
all others	2 x rated pressure

ELECTRICAL CONNECTION

0...10 V, 0.5...4.5 V, 0...5 V, 1...6 V output



4...20 mA output



CTE9000 / CTU9000 Series

OEM pressure transmitters for industrial media

COMMON PERFORMANCE CHARACTERISTICS

Characteristics			Min.	Typ.	Max.	Unit
Operating pressure	CTEM9350...		0		0.35	bar
	CTE9001...		0		1	
	CTE9N01...		-1		1	
	CTE9P01...		-1		0	
	CTE9002...		0		2	
	CTE9003...		0		3	
	CTE9005...		0		5	
	CTE9010...		0		10	
	CTE9016...		0		16	
	CTE9020...		0		20	
	CTE9035...		0		35	
	CTU9005...		0		5	psi
	CTU9015...		0		15	
	CTU9N15...		-15		15	
	CTU9P15		-15		0	
	CTU9030...		0		30	
	CTU9050...		0		50	
	CTU9100...		0		100	
	CTU9300...		0		300	
	CTU9500...		0		500	
Thermal effects (0 to 70°C) ⁴	Offset			±0.02	±0.05	%FSO/°C
	Span			±0.02	±0.05	
Thermal effects (-40 to 0°C, 70 to 100°C)	Offset			±0.03		%FSO/°C
	Span			±0.03		
Non-linearity and hysteresis (BSL) ⁵				±0.2	±0.5	%FSO
Repeatability				±0.1		
Long term stability ⁶				±0.1		
Output noise (0 < f < 1 kHz)				±0.04		
Response time (10 to 90 %)				1		ms
Power supply rejection	Offset	CTE(M)/CTU9...4 all others		±0.05 ±0.002		%FSO/V
	Span	CTE(M)/CTU9...4 all others		±0.08 ±0.002		

CTE9000 / CTU9000 Series

OEM pressure transmitters for industrial media

INDIVIDUAL PERFORMANCE CHARACTERISTICS

0...10 V output ($V_s = 15 \text{ V}$, $R_L > 100 \text{ k}\Omega$, $t_{amb} = 25^\circ\text{C}$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	CT...9N...	4.9	5	5.1	V
	all others	-0.1	0	0.1	
Full scale span ⁷	CT...9N...	4.9	5	5.1	
	all others	9.9	10	10.1	
Output impedance				25	Ω
Current consumption (no load)			4	9.5	mA

0.5...4.5 V output ($V_s = 15 \text{ V}$, $R_L > 100 \text{ k}\Omega$, $t_{amb} = 25^\circ\text{C}$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	CT...9N...	2.45	2.5	2.55	V
	all others	0.45	0.5	0.55	
Full scale span ⁷	CT...9N...	1.95	2	2.05	
	all others	3.95	4	4.05	
Output impedance				25	Ω
Current consumption (no load)			4	8.5	mA

0...5 V output ($V_s = 15 \text{ V}$, $R_L > 100 \text{ k}\Omega$, $t_{amb} = 25^\circ\text{C}$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	CT...9N...	2.45	2.5	2.55	V
	all others	-0.05	0	0.05	
Full scale span ⁷	CT...9N...	2.45	2.5	2.55	
	all others	4.95	5.0	5.05	
Output impedance				25	Ω
Current consumption (no load)			4	8.5	mA

1...6 V output ($V_s = 15 \text{ V}$, $R_L > 100 \text{ k}\Omega$, $t_{amb} = 25^\circ\text{C}$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	CT...9N...	3.45	3.5	3.55	V
	all others	0.95	1	1.05	
Full scale span ⁷	CT...9N...	2.45	2.5	2.55	
	all others	4.95	5.0	5.05	
Output impedance				25	Ω
Current consumption (no load)			4	8.5	mA

4...20 mA output ($V_s = 15 \text{ V}$, $R_L = 100 \Omega$, $t_{amb} = 25^\circ\text{C}$)

Characteristics		Min.	Typ.	Max.	Unit
Zero pressure offset	CT...9N...	11.8	12.0	12.2	mA
	all others	3.8	4.0	4.2	
Full scale span ⁷	CT...9N...	7.8	8.0	8.2	
	all others	15.8	16.0	16.2	
Power consumption ($I_L = 20 \text{ mA}$)			260		mW


CTE9000 / CTU9000 Series

OEM pressure transmitters for industrial media

Specification notes:

1. IP 64 protection is given when the connector is locked. For proper function the gage port is vented to the atmosphere through the connector/cable assembly. Thus the cable end must have access to the ambient pressure.
2. The minimum supply voltage is directly proportional to the load resistance seen by the transmitter. For more details see the load limitation diagram.
3. Proof pressure is the maximum pressure which may be applied without causing damage to the sensing element.
4. Thermal effects tested and guaranteed from 0 to 70°C relative to 25°C. All specifications shown are relative to 25°C.
5. Non-linearity refers to the **Best Straight Line** fit measured for offset, full scale span and 1/2 full scale span.
6. Long term stability is the change in output after one year or 1 million pressure cycles.
7. Span is the arithmetic difference in transmitter output signal measured at zero pressure and the maximum operating pressure.
8. Tests are in accordance with EN61000-6-2, April 1999.
9. When using devices with optional nickel plated fittings, consider the media compatibility of the fittings also.
10. Available for pressure ranges from 1 bar (15 psi) absolute upwards only.
11. CE-labelling is in accordance with 89/336/EEC.
12. The pressure transmitters must not be used as safety accessories according to article 1, 2.1.3 of the directive 97/23/EC.

OUTLINE DRAWING




CTE9000 / CTU9000 Series

OEM pressure transmitters for industrial media

RECOMMENDED ACCESSORY (not included in delivery)

ZK000101: Connector/cable assembly (different cable lengths available)
ZP000112-B: Mating Connector (without cable)



PIN CONNECTION	
Pin	Flying lead end
1	Brown
2	Green
3	White and shield
4	Yellow


Note:
For proper function of all gage devices the vent tube must have access to the ambient atmosphere.

dimensions in mm



OPTIONAL PRESSURE FITTINGS (brass, nickel plated)

LOAD LIMITATION 4...20 mA output version

Male fittings



Female fittings



Dimensions in mm (inches)			
A	B	C	D (Hex.)
1/8" BSPT	8 (0.315)	13 (0.512)	14 (9/16")
1/4" BSPT	12 (0.472)	5.5 (0.217)	14 (9/16")
3/8" BSPT	11.5 (0.453)	5 (0.197)	17 (11/16")
1/2" BSPT	16 (0.630)	7 (0.276)	22 (7/8")
1/8" BSP	12.5 (0.492)	11 (0.433)	14 (9/16")
1/4" BSP	8.5 (0.335)	5 (0.197)	19 (3/4")
3/8" BSP	12.5 (0.492)	7 (0.276)	22 (7/8")
1/8" NPT	10 (0.394)	13 (0.512)	17 (11/16")
1/4" NPT	14 (0.551)	6 (0.236)	22 (7/8")

Dimensions in mm (inches)			
E	F	G	H (Hex.)
1/8" BSP	5 (0.197)	15 (0.591)	14 (9/16")
1/4" BSP	7 (0.276)	20 (0.787)	17 (11/16")
3/8" BSP	6 (0.236)	20 (0.787)	22 (7/8")
1/2" BSP	18 (0.707)	23 (0.906)	24 (15/16")

CTE9000 / CTU9000 Series

OEM pressure transmitters for industrial media

ELECTROMAGNETIC CAPABILITY⁸

	Test conditions	Criterion	Interference
Radiated, radio frequency electromagnetic field immunity (RFI)	EN61000-4-3: Grade 3, 10 V/m, 80 to 1000 MHz 80 % AMC (1 kHz)	A	<1 %FSO
Electrical fast transient / burst immunity (EFT)	EN61000-4-4: Grade 3, ±2 kV	B	<1 %FSO
Electrostatic discharge immunity test (ESD)	EN61000-4-2: Grade 4, ±8 kV, contact discharge	B	<1 %FSO
Immunity to conducted disturbances induced by radio-frequency fields	EN61000-4-6: Grade 3, 0.15 to 80 MHz 10 V, 80 % AMC (1 kHz)	A	<1 %FSO

ORDERING INFORMATION

	CTx	M	9xxx	x	x	x
E: bar calibration						Output signal
U: psi calibration						0: 0...10 V
						1: 1...6 V
						4: 4...20 mA
						6: 0.5...4.5 V
						7: 0...5 V
mbar-ranges (only)						Fitting size⁹
CTE9000 series						D: 1/8" BSPT male, brass, nickel plated
350: 0 to 350 mbar (gage only)						E: 1/4" BSPT male, brass, nickel plated
001: 0 to 1 bar						F: 3/8" BSPT male, brass, nickel plated
N01: -1 to +1 bar (gage only)						G: 1/2" BSPT male, brass, nickel plated
P01: -1 to 0 bar (gage only)						K: 1/8" NPT male, brass
002: 0 to 2 bar						L: 1/4" NPT male, brass
003: 0 to 3 bar						M: 1/8" NPT male, SS 1.4305 (303)
005: 0 to 5 bar						N: 1/4" NPT male, SS 1.4305 (303)
010: 0 to 10 bar						P: G 1/8" (BSP) male, brass, nickel plated
016: 0 to 16 bar						Q: G 1/4" (BSP) male, brass, nickel plated
020: 0 to 20 bar						R: G 3/8" (BSP) male, brass, nickel plated
035: 0 to 35 bar						S: G 1/2" (BSP) male, brass, nickel plated
CTU9000 series						U: G 1/8" (BSP) female, brass, nickel plated
005: 0 to 5 psi (gage only)						V: G 1/4" (BSP) female, brass, nickel plated
015: 0 to 15 psi						W: G 3/8" (BSP) female, brass, nickel plated
N15: -15 to +15 psi (gage only)						X: G 1/2" (BSP) female, brass, nickel plated
P15: -15 to 0 psi (gage only)						Y: G 1/8" (BSP) male, SS 1.4404 (316) no optional fitting
030: 0 to 30 psi						
050: 0 to 50 psi						
100: 0 to 100 psi						
300: 0 to 300 psi						
500: 0 to 500 psi						
Pressure mode						
G: gage pressure ¹						
A: absolute pressure						
(available for pressure ranges from 1 bar /15 psi absolute upwards only)						

Note: Other pressure ranges and options are widely available.
Please contact your nearest Sensorteknics sales representative.

Sensorteknics reserves the right to make changes to any products herein. Sensorteknics does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.