

Ordering Code

CTMD 5 P - 5 J 1 S AO 1500

MiniDIN Cable Assembly

Pin Count (1st End):
3,4,5,6,7,8 and 9

Connector Type (1st End):

P = Male
J = Female

Pin Count (2nd End):

3,4,5,6,7,8 and 9
0 = Open End

Connector Type (2nd End):

P = Male
J = Female
O = Open End (Cut Off)
V = Open End, Jacket Stripped 40mm, Wire Ends Twisted and Tinned 5mm

Housing Types (See Drawings Below):

1 = Type 1 (Standard)
4 = Type 4
5 = Type 5 (Male with 3 to 8 pins and Female with 8 pins only)

Colour Code:

S = Black (Standard) G = Grey B = Beige

Cable (Shielding and UL-Approval):

AO = AWG26 (Standard) with Alu-foil, without UL-Approval
AX = AWG24 or AWG28 with Alu-foil, without UL-Approval
AU = AWG24, 26 or 28 with Alu-foil, with UL-Approval
CU = AWG24, 26 or 28 with Cu braided Shield and with Alu-foil, with UL-Approval
OO = AWG 24, 26 or 28 Unshielded, without UL-Approval

Info: Shielded cables always come with Drain Wire!


OO = Minimum Ordering Length for Cable is 3,000 meters
All others = Minimum Ordering Length for Cable 1,000 meters

Overall Length

Housing Types

Type 1 (Moulded)


Round Type (std.)



Male or Female
3 to 9 pins
Min. Order Qty. 100 pcs.

Type 4 (Moulded)


Conical Type



Male or Female
3 to 9 pins
Min. Order Qty. 100 pcs.

Type 5 (Mounted)

'Quick Lock' Housing



Male 3 to 8 pins
Female 8 pins only
Min. Order Qty. 100 pcs.