




PART NUMBER: CP30338

DESCRIPTION: PELTIER MODULE

FEATURES

- solid state device
- small and lightweight
- precise temperature control
- quiet operation
- RoHS compliant



INPUT

parameter	conditions/description	min	nom	max	units
resistance	measured by AC 4-terminal method at 25°C	3.6	4.0	4.4	Ω
current	maximum current at ΔT_{max}			3	A
voltage	maximum voltage at ΔT_{max}			15.4	V

OUTPUT

parameter	conditions/description	min	nom	max	units
Q_{max}^1	$T_h = 27^\circ\text{C}$			27	W
	$T_h = 50^\circ\text{C}$			30.1	W
ΔT_{max}^2	$T_h = 27^\circ\text{C}$			66	$^\circ\text{C}$
	$T_h = 50^\circ\text{C}$			72	$^\circ\text{C}$

Notes: 1. Maximum cooling capacity at I_{max} , V_{max} , and $\Delta T = 0^\circ\text{C}$
2. Maximum temperature difference at I_{max} , V_{max} , $Q = 0$ W (maximum parameters are measured in a vacuum)

GENERAL

parameter	conditions/description	min	nom	max	units
solder melting temperature	connection between thermoelectric pairs			138	$^\circ\text{C}$
assembly compression				98.07	N/cm^2
				10	kgf/cm^2
hot side plate				90	$^\circ\text{C}$
MTBF				200,000	hours


*for further information and product selection refer to peltier application notes.pdf




PART NUMBER: CP30338

DESCRIPTION: PELTIER MODULE




PERFORMANCE (Th=27°C)



PERFORMANCE (Th=50°C)



REV.	DESCRIPTION	DATE
A	NEW DRAWING	10/3/2007



TOLERANCE:
±0.1mm UNLESS OTHERWISE
NOTED



20050 SW 112th Ave.
Tualatin, OR 97062
Phone: 503-612-2300
800-275-4899
Fax: 503-612-2383
Website: www.cui.com

TITLE	REV.	SCALE
PELTIER MODULE	A	2:1
PART NO.	UNITS	APPROVED BY:
CP30338	MM [INCHES]	ZRJ
DRAWN BY:	APPROVED BY:	SCALE:
ZRJ		2:1

CERAMIC PLATE	MATERIAL	PLATING
SEALER	Al ₂ O ₃ (Alumina)	White Color
LEAD WIRE	Silicon Rubber RTV	White Color
JOINT COVER	UL1332	Tin
	Silicon Rubber RTV	White Color